



# IRS

---

## **RULES FOR BUILDING AND CLASSING STEEL VESSELS**

### **PART 5 STABILITY**

**JANUARY 2015**

---

**INTERNATIONAL REGISTER OF SHIPPING**

Technical Appraisal Department

4770 Biscayne Boulevard

Suite 800

Miami, Florida 33137, USA



**CHANGES**

---

**CONTENTS**

CHAPTER 1 INTRODUCTION.....	5
SECTION 1 PURPOSE .....	6
SECTION 2 DEFINITIONS.....	8
CHAPTER 2 MANDATORY CRITERIA .....	12
SECTION 1 GENERAL .....	13
SECTION 2 GENERAL CRITERIA .....	15
SECTION 3 SPECIAL CRITERIA FOR CERTAIN TYPES OF SHIPS .....	22
CHAPTER 3 RECOMMENDATIONS FOR CERTAIN TYPES OF SHIPS AND ADDITIONAL GUIDELINES .....	25
SECTION 1 GENERAL .....	26
SECTION 2 RECOMMENDED DESIGN CRITERIA FOR CERTAIN TYPES OF SHIPS .....	28
SECTION 3 GUIDANCE IN PREPARING STABILITY INFORMATION .....	47
SECTION 4 STABILITY CALCULATIONS PERFORMED BY STABILITY INSTRUMENTS .....	57
SECTION 5 OPERATIONAL PROVISIONS AGAINST CAPSIZING .....	63
SECTION 6 ICING CONSIDERATIONS .....	66
SECTION 7 CONSIDERATIONS FOR WATERTIGHT AND WEATHERTIGHT INTEGRITY.....	71
SECTION 8 DETERMINATION OF LIGHTSHIP PARAMETERS.....	79
CHAPTER 4 DAMAGE STABILITY .....	85
SECTION 1 DAMAGE STABILITY .....	86
SECTION 2 SUBDIVISION, WATERTIGHT AND WEATHERTIGHT INTEGRITY .....	102
ANNEX 1 DETAILED GUIDANCE FOR THE CONDUCT OF AN INCLINING TEST.....	105
ANNEX 2 RECOMMENDATIONS FOR SKIPPERS OF FISHING VESSELS ON ENSURING A VESSEL'S ENDURANCE IN CONDITIONS OF ICE FORMATION.....	125

---

# CHAPTER 1 INTRODUCTION

## CONTENTS

SECTION 1 PURPOSE .....	6
SECTION 2 DEFINITIONS .....	8

## SECTION 1 PURPOSE

### Contents

1.1	PURPOSE.....	7
-----	--------------	---

**1.1 Purpose**

- 1.1.1. The purpose of this part, prepared in reference to the Intact Stability Code (Code on Intact Stability for all types of ships covered by IMO instruments, adopted by the Organization by Resolution A.749 (18), as amended by Resolution MSC.75 (69)), and SOLAS regulations, is to present mandatory and recommendatory stability criteria and other measures for ensuring the safe operation of ships, to minimize the risk to such ships, to the personnel on board and to the environment.
- 1.1.2. This Code contains intact stability criteria for the following types of ships and other marine vehicles of 24 m in length and above, unless otherwise stated:
  - a. Cargo ships;
  - b. Cargo ships carrying timber deck cargoes;
  - c. Passenger ships;
  - d. Fishing vessels;
  - e. Special purpose ships;
  - f. Offshore supply vessels;
  - g. Pontoons; and
  - h. Cargo ships carrying containers on deck and containerships.
- 1.1.3. Administrations may impose additional requirements regarding the design aspects of ships of novel design or ships not otherwise covered by the Code.

---

## SECTION 2 DEFINITIONS

### Contents

2.1 Definitions ..... 9

---

**2.1 Definitions**

- 2.1.1. For the purpose of this Code the definitions given hereunder shall apply. For terms used, but not defined in this Code, the definitions as given in the 1974 SOLAS Convention, as amended, shall apply.

**Administration** refers to the Government of the State whose flag the ship is entitled to fly.

**Passenger ship:** A passenger ship carries more than twelve passengers as defined in regulation I/2 of the 1974 SOLAS Convention, as amended.

**Cargo ship:** A cargo ship transports goods and materials. It is not a passenger ship, a ship of war or a troopship. It is not propelled by any mechanical means, a wooden ship of primitive build, a fishing vessel or a mobile offshore drilling unit.

**Oil tanker:** An oil tanker is a ship constructed or adapted primarily to carry oil in bulk in its cargo spaces. It includes combination of carriers and any chemical tanker as defined in Annex II of the MARPOL Convention when it is carrying a cargo or part cargo of oil in bulk.

- a) **Combination carrier** means a ship designed to carry either oil or solid cargoes in bulk.
- b) **Crude oil tanker:** A crude oil tanker is an oil tanker which is engaged in the trade of transportation of crude oil.
- c) **Product carrier:** This is one type of oil tanker which is engaged in the trade of transportation of oil other than crude oil.

**Fishing vessel:** A fishing vessel is engaged in catching fish, whales, seals, walrus and various other living resources found in the sea.

**Special purpose ship** has the same definition as in the Code of Safety for Special Purpose Ships, 2008 (resolution MSC. 266(84)).

**Offshore supply vessel:** An offshore supply vessel is primarily engaged in the transportation of stores, materials and equipment to offshore installations. The forward part of the vessel is designed with accommodation and bridge erections and the after part has an exposed cargo deck for the purpose of handling cargo at sea.

**Mobile offshore drilling unit (MODU or unit):** This ship is involved with various drilling operations for the exploration or exploitation of resources which lie beneath the sea-bed such as liquid or gaseous hydrocarbons, sulfur or salt, etc.

- a) **Column-stabilized unit:** This unit is fitted with the main deck and is connected to the underwater hull or footings by columns or caissons.
- b) **Surface unit:** This unit is attached to the ship- or barge-type displacement hull of single or multiple hull construction for operation in the floating condition.
- c) **Self-elevating unit:** This unit consists of moveable legs and is capable of raising its hull above the surface of the sea.

**Coastal State:** This refers to the Government of the State who is exercising administrative control over the drilling operations of a particular unit.

**Mode of operation:** This refers to the condition or manner in which a unit carries out the function while on location or in transit. The basic modes of operation are as follows:

- a) Operating conditions are those conditions to which a unit is exposed to on location while it is conducting drilling operations. Combined environmental and operational loadings are within the appropriate design limits established for such operations. The unit may be either afloat or supported on the sea-bed, as applicable;
- b) Severe storm conditions refer to such conditions where a unit is exposed to harsh environmental loadings for the purpose for which it has been designed. Drilling operations are usually discontinued under severe environmental loadings. The unit may be either afloat or supported on the sea-bed, as applicable; and
- c) Transit conditions refer to the conditions wherein a unit is moving from one geographical location to another.

**High-speed craft (HSC)** is a craft capable of a maximum speed, in meters per second (m/s), equal to or exceeding:

$$3.7 * \nabla^{0.1667}$$

Where:  $\nabla$  displacement corresponding to the design waterline (m<sup>3</sup>).

**Containership:** Containership is a cargo ship which is primarily engaged for transportation of marine containers.

**Freeboard:** The space that lies in between the assigned load line and freeboard deck.

**Length of ship:** The length of a ship is measured as 96% of its total length on a waterline at 85% of the least molded depth measured from top of the keel, or the length from the fore side of the stem to the axis of the rudder stock on the waterline, if it is greater. For ships designed with a rake of keel, the measured waterline should be parallel to the designed waterline.

**Molded breadth:** The molded breadth is the greatest breadth of a ship and is measured from the midship section to the molded line of its frame with a metal shell. In case the shell is made up of any other material, the measurement is extended to the outer surface of the hull in the ship.

**Molded depth:** This is the vertical distance between the top of the keel and top of the freeboard deck beam at side. For wood and composite ships, the molded depth is measured from the lower edge of the keel rabbet. If the form at the lower part of the midship section is hollow or are fitted with thick garboards, then the measurement is taken from the point where the line of the flat of the bottom continued inward cuts the side of the keel. For ships with rounded gunwales, it is measured to the point of intersection of the molded lines of the deck and side shell plating, the lines extending as though the gunwale were of angular design. In ships having stepped freeboard deck, the raised part of the deck extends over the point at which the molded depth is to be determined. So, the molded depth should be measured to a line of reference extending from the lower part of the deck along a line parallel with the raised part.

**Near-coastal voyage:** This is a voyage in the areas close to the coastline of a State as defined by the Administration of that State.

**Pontoon:** Pontoon has a hollow structure with block coefficient of 0.9 or more and breadth/depth ratio greater than 3. It does not have hatchways in the deck except small manholes closed with gasketed covers. It is normally unmanned, non-self-propelled and carries deck cargo only.

**Timber:** This term refers to sawn wood or lumber, cants, logs, poles, pulpwood or any other type of timber in either loose or packaged forms. It does not include wood pulp or similar kind of cargo.

**Timber deck cargo:** This refers to a cargo of timber which is carried on an uncovered part of the freeboard or superstructure deck. This term does not include wood pulp or any similar cargo.

**Timber load line:** Timber load line is a special load line assigned to ships complying with certain conditions related to their construction set out in the International Convention on Load Lines and used when the cargo complies with the stowage and securing conditions of the Code of Safe Practice for Ships Carrying Timber Deck Cargoes, 1991 (resolution A.715(17)).

**Certification of the inclining test weights** is the verification of the weight marked on a test weight. Test weights should be certified with the help of a certificated scale. The weighing is carried out at a time close enough to the inclining test to ensure a high level of accuracy for the measured weight.

**Draught:** It is the vertical distance  $d$  from the molded baseline to the waterline.

**Inclining test:** During this test, a series of known weights are moved normally in the transverse direction to measure the resulting change in the in the equilibrium heel angle of the ship. This information is vital as it is used along with basic naval architecture principles to determine the ship's vertical center of gravity (VCG or KG).

**Lightweight Survey:** Lightweight survey involves auditing the items that are to be added, deducted or relocated on the ship at the time of the inclining test so that the observed condition of the ship can be adjusted to the lightship condition. The weight and longitudinal, transverse and vertical location of each item are to be accurately determined and recorded. The lightship displacement and longitudinal center of gravity (LCG) can be obtained using this information, as well as the static waterline of the ship at the time of the inclining test as determined by measuring the freeboard or verified draught marks of the ship, the ship's hydrostatic data and the sea water density.

**Lightship condition:** It is a ship complete in all respects without any consumables, stores, cargo, crew and effects and without any liquids onboard except some machinery and piping fluids like lubricants and hydraulics, which are at operating levels.

**In-service inclining test:** This is a form of inclining test which is performed for the verification of the pre-calculated  $GM_C$  and the deadweight's center of gravity of an actual loading condition.

**Stability instrument:** This instrument is installed on board of a particular ship by means of which it can be ascertained that stability requirements specified for the ship in the Stability Booklet are met in any operational loading condition. A stability instrument comprises hardware and software.

---

## CHAPTER 2 MANDATORY CRITERIA

### CONTENTS

SECTION 1 GENERAL.....	13
SECTION 2 GENERAL CRITERIA.....	15
SECTION 3 SPECIAL CRITERIA FOR CERTAIN TYPES OF SHIPS .....	22

## SECTION 1 GENERAL

### Contents

1.1	Application .....	14
1.2	Dynamic stability phenomena in waves .....	14

**1.1 Application**

- 1.1.1. The criteria stated under Section 2 of this Chapter, present a set of minimum requirements that shall apply to cargo and passenger ships of 24 m in length and over.

For containerships of 100 m in length and over, provisions of Chapter 3, Section 2, 2.3 may be applied as an alternative to the application of Section 2.2 of this Chapter. Offshore supply vessels and special purpose ships are not required to comply with provisions of Chapter 2, Section 3. For offshore supply vessels, provisions of Chapter 3, Section 2, 2.4, may be applied as an alternative to the application of Section 2, 2.2 of this Chapter. For special purpose ships, provisions of Section 2, 2.5 of Chapter 3 may be applied as an alternative to the application of Section 2, 2.2 of this Chapter.

- 1.1.2. The criteria stated under Section 3 of this chapter are special criteria for certain types of ships. For the purpose of Chapter 2, the definitions given in the Introduction shall apply.

**1.2 Dynamic stability phenomena in waves**

Administrations shall be aware that some ships are more at risk of encountering critical stability situations in waves. Necessary precautionary provisions may need to be taken in the design to address the severity of such phenomena. The phenomena in seaways which may cause large roll angles and/or accelerations have been identified hereunder. Having regard to the phenomena described in this section, the Administration may for a particular ship or group of ships apply criteria demonstrating that the safety of the ship is sufficient. Any Administration which applies such criteria should communicate to the Organization particulars thereof. It is recognized by the Organization that performance oriented criteria for the identified phenomena listed in this section need to be developed and implemented to ensure a uniform international level of safety.

**1.2.1 Righting lever variation**

Any ship exhibiting large righting lever variations between wave trough and wave crest condition may experience parametric roll or pure loss of stability or combinations thereof.

**1.2.2 Resonant roll in dead ship condition**

Ships without propulsion or steering ability may be endangered by resonant roll while drifting freely.

**1.2.3 Broaching and other maneuvering related phenomena**

Ships in following and quartering seas may not be able to keep constant course despite maximum steering efforts which may lead to extreme angles of heel.

---

## SECTION 2 GENERAL CRITERIA

### Contents

2.1	General.....	16
2.2	Criteria regarding righting lever curve properties.....	16
2.3	Severe wind and rolling criterion.....	16

**2.1 General**

- 2.1.1. All criteria shall be applied for all conditions of loading as set out in Chapter 3 Section 3, 3.3 & 3.4.
- 2.1.2. Free surface effects (Chapter 3 Section 3, 3.1.) shall be accounted for in all conditions of loading as set out in Chapter 3, Section 3, 3.3 & 3.4.
- 2.1.3. Where anti-rolling devices are installed in a ship, the Administration shall be satisfied that the criteria can be maintained when the devices are in operation and that failure of power supply or the failure of the device(s) will not result in the vessel being unable to meet the relevant provisions of this Code.
- 2.1.4. A number of influences such as icing of topsides, water trapped on deck, etc., adversely affect stability and the Administration is advised to take these into account, so far as is deemed necessary.
- 2.1.5. Provisions shall be made for a safe margin of stability at all stages of the voyage, regard being given to additions of weight, such as those due to absorption of water and icing (details regarding ice accretion are given in Chapter 3, Section 6 - Icing considerations) and to losses of weight such as those due to consumption of fuel and stores.
- 2.1.6. Each ship shall be provided with a stability booklet, approved by the Administration, which contains sufficient information (see Chapter 3 Section 3, 3.6) to enable the master to operate the ship in compliance with the applicable requirements contained in the Code. If a stability instrument is used as a supplement to the stability booklet for the purpose of determining compliance with the relevant stability criteria such instrument shall be subject to the approval by the Administration (see Chapter 3, Section 4, Stability calculations performed by stability instruments).
- 2.1.7. If curves or tables of minimum operational metacentric height (GM) or maximum center of gravity (VCG) are used to ensure compliance with the relevant intact stability criteria those limiting curves shall extend over the full range of operational trims, unless the Administration agrees that trim effects are not significant. When curves or tables of minimum operational metacentric height (GM) or maximum center of gravity (VCG) versus draught covering the operational trims are not available, the master must verify that the operating condition does not deviate from a studied loading condition, or verify by calculation that the stability criteria are satisfied for this loading condition taking into account trim effects.

**2.2 Criteria regarding righting lever curve properties**


- 2.2.1. The area under the righting lever curve (GZ curve) shall not be less than 0.055 meter-radians up to  $\Phi = 30^\circ$  angle of heel and not less than 0.09 meter-radians up to  $\Phi = 40^\circ$  or the angle of down-flooding  $\Phi_f$  if this angle is less than  $40^\circ$ . Additionally, the area under the righting lever curve (GZ curve) between the angles of heel of  $30^\circ$  and  $40^\circ$  or between  $30^\circ$  and  $\Phi_f$ , if this angle is less than  $40^\circ$ , shall not be less than 0.03 meter-radians.
- 2.2.2. The righting lever GZ shall be at least 0.2 m at an angle of heel equal to or greater than  $30^\circ$ .
- 2.2.3. The maximum righting lever shall occur at an angle of heel not less than  $25^\circ$ . If this is not practicable, alternative criteria, based on an equivalent level of safety, may be applied subject to the approval of the Administration.
- 2.2.4. The initial metacentric height  $GM_0$  shall not be less than 0.15 m.

**2.3 Severe wind and rolling criterion**

- 2.3.1. The ability of a ship to withstand the combined effects of beam wind and rolling shall be demonstrated, with reference to figure 2.2.1 as follows:

- The ship is subjected to a steady wind pressure acting perpendicular to the ship's centerline which results in a steady wind heeling lever ( $l_{w1}$ );
- From the resultant angle of equilibrium ( $\Phi_0$ ), the ship is assumed to roll owing to wave action to an angle of roll ( $\Phi_1$ ) to windward. The angle of heel under action of steady wind ( $\Phi_0$ ) should not exceed  $16^\circ$  or 80% of the angle of deck edge immersion, whichever is less;
- The ship is then subjected to a gust wind pressure which results in a gust wind heeling lever ( $l_{w2}$ ); and
- Under these circumstances, area  $b$  shall be equal to or greater than area  $a$ , as indicated in figure 2.2.1 below:

Figure 2.2.1:



Where the angles in figure 2.2.1 are defined as follows:

- $\Phi_0$  = Angle of heel under action of steady wind;
- $\Phi_1$  = Angle of roll to windward due to wave action (see 2.3.1.b, 2.3.4);
- $\Phi_2$  = Angle of down-flooding ( $\Phi_f$ ) or  $50^\circ$  or  $\Phi_c$ , whichever is less,

Where:

$\Phi_f$  = Angle of heel at which openings in the hull, superstructures or deckhouses which cannot be closed weather tight immerse. In applying this criterion, small openings through which progressive flooding cannot take place need not be considered as open.

$\Phi_c$  = Angle of second intercept between wind heeling lever  $l_{w2}$  and GZ curves.

### 2.3.2. Wind heeling levers

The wind heeling levers  $l_{w1}$  and  $l_{w2}$  referred to in 2.3.1a & c above, are constant values at all angles of inclination and shall be calculated as follows:

$$l_{w1} = \frac{P * A * Z}{1000 * g * \Delta} \quad (\text{m}) \text{ and}$$

$$l_{w2} = 1.5 * l_{w1}(m)$$

Where:

$P$  = Wind pressure of 504 Pa. The value of  $P$  used for ships in restricted service may be reduced subject to the approval of the Administration.

$A$  = Projected lateral area of the portion of the ship and deck cargo above the waterline ( $m^2$ ).

$Z$  = Vertical distance from the center of  $A$  to the center of the underwater lateral area or approximately to a point at one half the mean draught (m).

$\Delta$  = Displacement (t);

$g$  = Gravitational acceleration of  $9.81 \text{ m/s}^2$ .

- 2.3.3. Alternative means for determining the wind heeling lever ( $l_{w1}$ ) may be accepted, to the satisfaction of the Administration, as an equivalent to calculation in 2.3.2 above.

When such alternative tests are carried out, reference shall be made based on the Guidelines developed by the Organization. The wind velocity used in the tests shall be 26 m/s in full scale with uniform velocity profile. The value of wind velocity used for ships in restricted services may be reduced to the satisfaction of the Administration.

- 2.3.4. Angle of roll

The angle of roll ( $\Phi_1$ ) referred to in 2.3.1 b above, shall be calculated as follows:

$$\varphi_1 = 109 * k * X_1 * X_2 * \sqrt{r * s} \text{ (Degrees)}$$

Where:

$X_1$  = Factor as shown in Table 2.2.1;

$X_2$  = Factor as shown in Table 2.2.2;

$k$  = Factor as follows:

$k$  = 1.0 for round-bilged ship having no bilge or bar keels;

$k$  = 0.7 for a ship having sharp bilges;

$k$  = As shown in Table 2.2.3 for a ship having bilge keels, a bar keel or both.

$$r = 0.73 + 0.6 \text{ OG}/T_m$$

With:

$$\text{OG} = \text{KG} - T_m$$

$T_m$  = Mean molded draught of the ship (m)

$s$  = Factor as shown in Table 2.2.4, where  $T$  is the ship roll natural period. In absence of sufficient information, the following approximate formula can be used:

Rolling period

$$T = \frac{2 * C * B_m}{\sqrt{GM}} (s)$$

Where,

$$C = 0.373 + 0.023(B_m/T_m) - 0.043(L_{wl}/100)$$

The symbols in tables 2.2.1, 2.2.2, 2.2.3 and 2.2.4 and the formula for the rolling period are defined as follows:

$L_{wl}$  = Length of the ship at waterline (m);

$B_m$  =Molded breadth of the ship (m);

$T_m$  =Mean molded draught of the ship (m);

$C_B$  =Block coefficient (-);

$A_k$  =Total overall area of bilge keels, or area of the lateral projection of the bar keel, or sum of these areas (m<sup>2</sup>);

$GM$  =Metacentric height corrected for free surface effect (m).

Table 2.2.1: Values of factor  $X_1$ 

$B_m/T_m$	$X_1$
$\leq 2.4$	1.0
2.5	0.98
2.6	0.96
2.7	0.95
2.8	0.93
2.9	0.91
3.0	0.90
3.1	0.88
3.2	0.86
3.4	0.82
$\geq 3.5$	0.80

Table 2.2.2: Values of factor  $X_2$ 

$C_B$	$X_2$
$\leq 0.45$	0.75
0.50	0.82
0.55	0.89
0.60	0.95
0.65	0.97
$\geq 0.70$	1.00

Table 2.2.3: Values of factor  $k$ 

$\frac{A_k \times 100}{L_{WL} \times B_m}$	$k$
0	1.0
1.0	0.98
1.5	0.95
2.0	0.88
2.5	0.79
3.0	0.74
3.5	0.72
$\geq 4.0$	0.70

Table 2.2.4: Values of factor  $s$ 

T	s
≤6	0.100
7	0.098
8	0.093
12	0.065
14	0.053
16	0.044
18	0.038
≥20	0.035

(Intermediate values in these tables shall be obtained by linear interpolation)

2.3.5. The tables and formulae described in 2.3.4 above, are based on data from ships having:

- a.  $B_m/T_m$  smaller than 3.5;
- b.  $(KG/T_m-1)$  between - 0.3 and 0.5; and
- c. T smaller than 20 s.

For ships with parameters outside of the above limits the angle of roll ( $\Phi_1$ ) may be determined with model experiments of a subject ship as the alternative. In addition, the Administration may accept such alternative determinations for any ship, if deemed appropriate.

---

**SECTION 3 SPECIAL CRITERIA FOR CERTAIN TYPES OF SHIPS**

**Contents**

3.1. Passenger ships..... 23

3.2. Oil tankers of 5,000 dwt and above ..... 23

3.3. Cargo ships carrying timber deck cargoes ..... 24

3.4. Cargo ships carrying grain in bulk..... 24

3.5. High Speed Craft..... 24

**3.1. Passenger ships**

Passenger ships shall comply with the requirements of Chapter 2, Section 2, 2.2 & 2.3.

3.1.1. In addition, the angle of heel on account of crowding of passengers to one side as defined below shall not exceed 10°.

3.1.1.1. A minimum weight of 75 kg shall be assumed for each passenger except that this value may be increased subject to the approval of the Administration. In addition, the mass and distribution of the luggage shall be approved by the Administration.

3.1.1.2. The height of the center of gravity for passengers shall be assumed equal to:

- 1 m above deck level for passengers standing upright. Account may be taken, if necessary, of camber and sheer of deck; and,
- 0.3 m above the seat in respect of seated passengers.

3.1.1.3. Passengers and luggage shall be considered to be in the spaces normally at their disposal, when assessing compliance with the criteria given in Section 2, 2.2 of Chapter 2.

3.1.1.4. Passengers without luggage shall be considered as distributed to produce the most unfavorable combination of passenger heeling moment and/or initial metacentric height, which may be obtained in practice, when assessing compliance with the criteria given in 3.1.1 and 3.1.2, respectively, of this Chapter. In this connection, a value higher than four persons per square meter is not necessary.

3.1.2. In addition, the angle of heel on account of turning shall not exceed 10° when calculated using the following formula:

$$M_R = 0 \cdot 200 * \frac{V_s^2}{L_{WL}} * \Delta * \left( KG - \frac{T_m}{2} \right)$$

Where:

$M_R$  = Heeling moment (kN-m);

$V_s$  = Service speed (m/s);

$L_{WL}$  = Length of ship at waterline (m);

$\Delta$  = Displacement (t);

$T_m$  = Mean draught (m);

$KG$  = Height of center of gravity above baseline (m).

**3.2. Oil tankers of 5,000 dwt and above**

Oil tankers, as defined in Introduction Chapter 1, Section 2 (Definitions), shall comply with regulation 27 of Annex I to MARPOL 73/78.

**3.3. Cargo ships carrying timber deck cargoes**

Cargo ships carrying timber deck cargoes shall comply with the requirements of Chapter 2, Section 2 and Section 3, unless the Administration is satisfied with the application of alternative provision 3.3.2 below.

**3.3.1. Scope**

The provisions given hereunder apply to all ships of 24 m in length and over engaged in the carriage of timber deck cargoes. Ships that are provided with, and make use of, their timber load line shall also comply with the requirements of regulations 41 to 45 of the 1966 Load Line Convention.

**3.3.2. Alternative stability criteria**

For ships loaded with timber deck cargoes and provided that the cargo extends longitudinally between superstructures (where there is no limiting superstructure at the after end, the timber deck cargo shall extend at least to the after end of the aftermost hatchway) transversely for the full beam of ship, after due allowance for a rounded gunwale, not exceeding 4% of the breadth of the ship and/or securing the supporting uprights and which remains securely fixed at large angles of heel may be:

3.3.2.1. The area under the righting lever curve (GZ curve) shall not be less than 0.08 meter-radians up to  $\Phi = 40^\circ$  or the angle of flooding if this angle is less than  $40^\circ$ .

3.3.2.2. The maximum value of the righting lever (GZ) shall be at least 0.25 m.

3.3.2.3. At all times during a voyage, the metacentric height  $GM_0$  shall not be less than 0.1 m, taking into account the absorption of water by the deck cargo and/or ice accretion on the exposed surfaces.

3.3.2.4. When determining the ability of the ship to withstand the combined effects of beam wind and rolling according to Chapter 2, Section 2, 2.3 the  $16^\circ$  limiting angle of heel under action of steady wind shall be complied with, but the additional criterion of 80% of the angle of deck edge immersion may be ignored.

**3.4. Cargo ships carrying grain in bulk**

The intact stability of ships engaged in the carriage of grain shall comply with the requirements of the International Code for the Safe Carriage of Grain in Bulk adopted by resolution MSC.23 (59).

**3.5. High Speed Craft**

High-speed craft, as defined in Chapter 1, Section 2 (Definitions), constructed on or after 1 January 1996 but before 1 July 2002, to which chapter X of the 1974 SOLAS Convention applies, shall comply with stability requirements of the 1994 HSC Code (resolution MSC.36(63)). Any high-speed craft to which chapter X of the 1974 SOLAS Convention applies, irrespective of its date of construction, which has undergone repairs, alterations or modifications of a major character; and a high-speed craft constructed on or after 1 July 2002, shall comply with stability requirements of the 2000 HSC Code (resolution MSC.97(73)).

---

## CHAPTER 3 RECOMMENDATIONS FOR CERTAIN TYPES OF SHIPS AND ADDITIONAL GUIDELINES

### CONTENTS

SECTION 1 GENERAL .....	26
SECTION 2 RECOMMENDED DESIGN CRITERIA FOR CERTAIN TYPES OF SHIPS.....	28
SECTION 3 GUIDANCE IN PREPARING STABILITY INFORMATION.....	47
SECTION 4 STABILITY CALCULATIONS PERFORMED BY STABILITY INSTRUMENTS.....	57
SECTION 5 OPERATIONAL PROVISIONS AGAINST CAPSIZING .....	63
SECTION 6 ICING CONSIDERATIONS.....	66
SECTION 7 CONSIDERATIONS FOR WATERTIGHT AND WEATHERTIGHT INTEGRITY.....	71
SECTION 8 DETERMINATION OF LIGHTSHIP PARAMETERS.....	79

---

## SECTION 1 GENERAL

### Contents

1.1 Purpose.....	27
1.2 Application.....	27

**1.1 Purpose**

The purpose of this part of the Code is to:

- a. Recommend stability criteria and other measures for ensuring the safe operation of certain types of ships to minimize the risk to such ships, to the personnel on board and to the environment; and
- b. Provide guidelines for stability information, operational provisions against capsizing, icing considerations, considerations for watertight integrity and the determination of lightship parameters.

**1.2 Application**

- 1.2.1. This part of the Code contains recommended intact stability criteria for certain types of ships and other marine vehicles not included in Chapter 2 or intended to supplement those of Chapter 2 in particular cases regarding size or operation.
- 1.2.2. Administrations may impose additional requirements regarding the design aspects of ships of novel design or ships not otherwise covered by the Code.
- 1.2.3. The criteria stated in this part should give guidance to Administrations if no national requirements are applied.

---

## SECTION 2 RECOMMENDED DESIGN CRITERIA FOR CERTAIN TYPES OF SHIPS

### Contents

2.1	Fishing Vessels .....	29
2.2	Pontoons .....	31
2.3	Containerships Greater Than 100 M.....	32
2.4	Offshore Supply Vessels.....	34
2.5	Special Purpose Ships .....	36
2.6	Mobile Offshore Drilling Units (MODUs).....	36

---

## 2.1 Fishing Vessels

### 2.1.1. Scope

The provisions given hereunder apply to decked seagoing fishing vessels as defined in [2.5] Introduction. The stability criteria given in 2.1.3 and 2.1.4 below should be complied with for all conditions of loading as specified in Chapter 3, Section 3, 3.4.1.6, unless the Administration is satisfied that operating experience justifies departures there from.

### 2.1.2. General precautions against capsizing

Apart from general precautions referred to in Section 5 of Chapter 3, the following measures should be considered as preliminary guidance on matters influencing safety as related to stability:

- a. All fishing gear and other heavy material should be properly stowed and placed as low in the vessel as possible;
- b. Particular care should be taken when pull from fishing gear might have a negative effect on stability, e.g., when nets are hauled by power-block or the trawl catches obstructions on the sea-bed. The pull of the fishing gear should be from as low a point on the vessel, above the waterline, as possible;
- c. Gear for releasing the deck load in fishing vessels which carry the catch on deck, e.g., herring, should be kept in good working condition;
- d. When the main deck is prepared for carrying deck load by dividing it with pound boards, there should be slots between them of suitable size to allow easy flow of water to freeing ports, thus preventing trapping of water;
- e. To prevent a shift of the fish load carried in bulk, portable divisions in the holds should be properly installed;
- f. Reliance on automatic steering may be dangerous as this prevents changes to course which may be needed in bad weather;
- g. Necessary care should be taken to maintain adequate freeboard in all loading conditions, and where load line regulations are applicable they should be strictly adhered to at all times; and
- h. Particular care should be taken when the pull from fishing gear results in dangerous heel angles. This may occur when fishing gear fastens onto an underwater obstacle or when handling fishing gear, particularly on purse seiners, or when one of the trawl wires tears off. The heel angles caused by the fishing gear in these situations may be eliminated by employing devices which can relieve or remove excessive forces applied through the fishing gear. Such devices should not impose a danger to the vessel through operating in circumstances other than those for which they were intended.

### 2.1.3. Recommended general criteria

- 2.1.3.1. The general intact stability criteria given in Chapter 2, 2.2.1 to 2.2.3, should apply to fishing vessels having a length of 24 m and over, with the exception of requirements on the initial metacentric height GM (Chapter 2, Section 2, 2.2.1 to 2.2.3), which, for fishing vessels, should not be less than 0.35 m for single-deck vessels. In vessels with complete superstructure or vessels of 70 m in length and over the metacentric height may be reduced to the satisfaction of the Administration but in no case should be less than 0.15 m.
- 2.1.3.2. The adoption by individual countries of simplified criteria which apply such basic stability values to their own types and classes of vessels is recognized as a practical and valuable method of economically judging the stability.
- 2.1.3.3. Where arrangements other than bilge keels are provided to limit the angle of roll, the Administration should be satisfied that the stability criteria referred to in 2.1.3.1

above, are maintained in all operating conditions.

#### 2.1.4. Severe wind and rolling criterion (weather criterion) for fishing vessels

The Administration may apply the provisions of Chapter 2, Section 2, 2.3 to fishing vessels of 45 m length and over.

For fishing vessels in the length range between 24 m and 45 m, the Administration may apply the provisions of Chapter 2, Section 2, 2.3. Alternatively, the values of wind pressure (Chapter 2, Section 2, 2.3.2) may be taken from the following table:

$h(m)$	1	2	3	4	5	6 and over
$P(Pa)$	316	386	429	460	485	504

where 'h' is the vertical distance from the center of the projected vertical area of the vessel above the waterline, to the waterline.

#### 2.1.5. Recommendation for an interim simplified stability criterion for decked fishing vessels under 30 m in length

2.1.5.1. For decked vessels with a length less than 30 m, the following approximate formula for the minimum metacentric height  $GM_{min}$  (in meters) for all operating conditions should be used as the criterion:

$$GM_{min} = 0.53 + 2B_{wlm} \left[ 0.075 - 0.37 \left( \frac{f}{B_{wlm}} \right) + 0.082 \left( \frac{f}{B_{wlm}} \right)^2 - 0.014 \left( \frac{B_{wlm}}{D} \right) - 0.032 \left( \frac{l_s}{L} \right) \right]$$

where:

$L$  = Length of the vessel on the waterline in maximum load condition (m).

$l_s$  = Actual length of enclosed superstructure extending from side to side of the vessel (m).

$B_{wlm}$  = Extreme breadth of the vessel on the waterline in maximum load condition (m).

$D$  = Depth of the vessel measured vertically amidships from the base line to the top of the upper deck at side (m).

$f$  = Smallest freeboard measured vertically from the top of the upper deck at side to the actual waterline (m).

The formula is applicable for vessels having:

- $f/B_{wlm}$  between 0.02 and 0.2;
- $l_s/L$  smaller than 0.6;
- $B_{wlm}/D$  between 1.75 and 2.15;
- Sheer fore and aft at least equal to or exceeding the standard sheer prescribed in regulation 38(8) of the International Convention on Load Lines, 1966 or the

- Protocol of 1988 as amended, as applicable; and
- e. Height of superstructure included in the calculation is not less than 1.8 m.

For ships with parameters outside the above limits the formula should be applied with special care.

2.1.5.2. The above formula is not intended as a replacement for the basic criteria given in 2.1.3 & 2.1.4, but is to be used only if circumstances are such that cross curves of stability, KM curve and subsequent GZ curves are not and cannot be made available for judging a particular vessel's stability.

2.1.5.3. The calculated value of GM, should be compared with actual GM values of the vessel in all loading conditions. If an inclining experiment based on estimated displacement, or another approximate method of determining the actual GM is used, a safety margin should be added to the calculated  $GM_{min}$ .

## 2.2 Pontoons

### 2.2.1. Application

The provisions given hereunder apply to seagoing pontoons. A pontoon is considered to be normally:

- a. Non self-propelled;
- b. Unmanned;
- c. Carrying only deck cargo;
- d. Having a block coefficient of 0.9 or greater;
- e. Having a breadth/depth ratio of greater than 3; and
- f. Having no hatchways in the deck except small manholes closed with gasketed covers.

### 2.2.2. Stability drawings and calculations

The following information is typical of that required to be submitted to the Administration for approval:

- a. Lines drawing;
- b. Hydrostatic curves;
- c. Cross curves of stability;
- d. Report of draught and density readings and calculation of lightship displacement and longitudinal center of gravity;
- e. Statement of justification of assumed vertical center of gravity; and
- f. Simplified stability guidance such as a loading diagram, so that the pontoon maybe loaded in compliance with the stability criteria.

### 2.2.3. Concerning the performance of calculations

The following guidance is suggested:

- a. No account should be taken of the buoyancy of deck cargo (except buoyancy credit for adequately secured timber);
- b. Consideration should be given to such factors as water absorption (e.g., timber), trapped water in cargo (e.g., pipes) and ice accretion;
- c. In performing wind heel calculations:
  - The wind pressure should be constant and for general operations be considered to act on a solid mass extending over the length of the cargo deck and to an assumed height above the deck;

- The center of gravity of the cargo should be assumed at a point mid-height of the cargo; and
  - The wind lever should be taken from the center of the deck cargo to a point at one half the mean draught;
- d. Calculations should be performed covering the full range of operating draughts; and,
- e. The down-flooding angle should be taken as the angle at which an opening through which progressive flooding may take place is immersed. This would not be an opening closed by a watertight manhole cover or a vent fitted with an automatic closure.
- 2.2.4. Intact stability criteria
- 2.2.4.1. The area under the righting lever curve up to the angle of maximum righting lever should not be less than 0.08 meter-radians.
- 2.2.4.2. The static angle of heel due to a uniformly distributed wind load of 540 Pa (wind speed 30 m/s) should not exceed an angle corresponding to half the freeboard for the relevant loading condition, where the lever of wind heeling moment is measured from the centroid of the windage area to half the draught.
- 2.2.4.3. The minimum range of stability should be:
- For  $L \leq 100$  m:  $20^{\circ}$ ;
  - For  $L \geq 150$  m:  $15^{\circ}$ ;
  - For intermediate length: by interpolation.

## 2.3 Containerships Greater Than 100 M

### 2.3.1. Application

These requirements apply to containerships greater than 100 m in length as defined in Chapter 1, Section 2 (Definitions). They may also be applied to other cargo ships in this length range with considerable flare or large water plane areas. The Administration may apply the following criteria instead of those in Chapter 2, Section 2, 2.2.

### 2.3.2. Intact stability

- 2.3.2.1. The area under the righting lever curve (GZ curve) should not be less than  $0.009/C$  meter-radians up to  $\Phi = 30^{\circ}$  angle of heel, and not less than  $0.016/C$  meter-radians up to  $\Phi = 40^{\circ}$  or the angle of flooding  $\Phi_f$  (as defined in Chapter 2, Section 2, 2.2) if this angle is less than  $40^{\circ}$ .
- 2.3.2.2. Additionally, the area under the righting lever curve (GZ curve) between the angles of heel of  $30^{\circ}$  and  $40^{\circ}$  or between  $30^{\circ}$  and  $\Phi_f$ , if this angle is less than  $40^{\circ}$ , should not be less than  $0.006/C$  meter-radians.
- 2.3.2.3. The righting lever GZ should be at least  $0.033/C$  m at an angle of heel equal or greater than  $30^{\circ}$ .
- 2.3.2.4. The maximum righting lever GZ should be at least  $0.042/C$  m.
- 2.3.2.5. The total area under the righting lever curve (GZ curve) up to the angle of flooding  $\Phi_f$  should not be less than  $0.029/C$  meter-radians.

2.3.2.6. In the above criteria the form factor  $C$  should be calculated using the formula and figure 3.2.1:

$$C = \frac{T_m D'}{B_M^2} \sqrt{\frac{T_m}{KG} \left(\frac{C_B}{C_W}\right)^2} \sqrt{\frac{100}{L}}$$

Where:

$T_m$  = Mean draught (m);

$D'$  = Molded depth of the ship, corrected for defined parts of volumes within the hatch coamings according to the formula:

$$D' = D_m + h \left( \frac{2b - B_m}{B_m} \right) \left( \frac{2 \sum l_H}{L} \right),$$

as defined in figure 3.2.1;

$D_m$  = Molded depth of the ship (m);

$B_M$  = Molded breadth of the ship (m);

$KG$  = Height of the center of mass above base, corrected for free surface effect, not be taken as less than  $d$  (m);

$C_B$  = Block coefficient;

$C_W$  = Water plane coefficient;

$l_H$  = Length of each hatch coaming within  $L/4$  forward and aft from amidships (m) (see figure 3.2.1);

$b$  = Mean width of hatch coamings within  $L/4$  forward and aft from amidships (m) (see figure 3.2.1);

$h$  = Mean height of hatch coamings within  $L/4$  forward and aft from amidships (m) (see figure 3.2.1);

$L$  = Length of the ship (m);

$B$  = Breadth of the ship on the waterline (m);

$B_{wl}$  = Breadth of the ship on the waterline at half mean draught (m).




Figure 3.2.1

The shaded areas in figure 3.2.1 represent partial volumes within the hatch coamings considered contributing to resistance against capsizing at large heeling angles when the ship is on a wave crest.

2.3.2.7. The use of electronic loading and stability instrument is encouraged in determining the ship's trim and stability during different operational conditions.

## 2.4 Offshore Supply Vessels

### 2.4.1. Application

2.4.1.1. The provisions given hereunder apply to offshore supply vessels, as defined in Chapter 1, Section 2 (Definitions), of 24 m in length and over. The alternative stability criteria contained in 2.4.5 below, apply to vessels of not more than 100 m in length.

2.4.1.2. For a vessel engaged in near-coastal voyages, as defined in section "Definitions", the principles given in 2.4.2 below should guide the Administration in the development of its national standards. Relaxations from the requirements of the Code may be permitted by an Administration for vessels engaged in near-coastal voyages off its own coasts provided the operating conditions are, in the opinion of that Administration, such as to render compliance with the provisions of the Code unreasonable or unnecessary.

2.4.1.3. Where a ship other than an offshore supply vessel, as defined in section "Definitions", is employed on a similar service, the Administration should determine the extent to which compliance with the provisions of the Code is required.

- 
- 2.4.2. Principles governing near-coastal voyages
- 2.4.2.1. The Administration defining near-coastal voyages for the purpose of the present Code should not impose design and construction standards for a vessel entitled to fly the flag of another State and engaged in such voyages in a manner resulting in a more stringent standard for such a vessel than for a vessel entitled to fly its own flag. In no case should the Administration impose, in respect of a vessel entitled to fly the flag of another State, standards in excess of the Code for a vessel not engaged in near-coastal voyages.
- 2.4.2.2. With respect to a vessel regularly engaged in near-coastal voyages off the coast of another State the Administration should prescribe design and construction standards for such a vessel at least equal to those prescribed by the Government of the State off whose coast the vessel is engaged, provided such standards do not exceed the Code in respect of a vessel not engaged in near-coastal voyages.
- 2.4.2.3. A vessel which extends its voyages beyond a near-coastal voyage should comply with the present Code.
- 2.4.3. Constructional precautions against capsizing
- 2.4.3.1. Access to the machinery space should, if possible, be arranged within the forecastle. Any access to the machinery space from the exposed cargo deck should be provided with two weather tight closures. Access to spaces below the exposed cargo deck should preferably be from a position within or above the superstructure deck.
- 2.4.3.2. The area of freeing ports in the side bulwarks of the cargo deck should at least meet the requirements of regulation 24 of the International Convention on Load Lines, 1966 or the Protocol of 1988 relating thereto, as amended, as applicable. The disposition of the freeing ports should be carefully considered to ensure the most effective drainage of water trapped in pipe deck cargoes or in recesses at the after end of the forecastle. In vessels operating in areas where icing is likely to occur, no shutters should be fitted in the freeing ports.
- 2.4.3.3. The Administration should give special attention to adequate drainage of pipe stowage positions having regard to the individual characteristics of the vessel. However, the area provided for drainage of the pipe stowage positions should be in excess of the required freeing port area in the cargo deck bulwarks and should not be fitted with shutters.
- 2.4.3.4. A vessel engaged in towing operations should be provided with means for quick release of the towing hawser.
- 2.4.4. Operational procedures against capsizing
- 2.4.4.1. The arrangement of cargo stowed on deck should be such as to avoid any obstruction of the freeing ports or of the areas necessary for the drainage of pipe stowage positions to the freeing ports.
- 2.4.4.2. A minimum freeboard at the stern of at least 0.005 *L* should be maintained in all operating conditions.
- 2.4.5. Stability criteria
- 2.4.5.1. The stability criteria given in Chapter 2, Section 2, should apply to all offshore supply

vessels except those having characteristics which render compliance with Chapter 2, Section 2 impracticable.

2.4.5.2. The following equivalent criteria should be applied where a vessel's characteristics render compliance with Chapter 2, Section 2, impracticable:

- a. The area under the curve of righting levers (GZ curve) should not be less than 0.07 meter-radians up to an angle of 15° when the maximum righting lever (GZ) occurs at 15° and 0.055 meter-radians up to an angle of 30° when the maximum righting lever (GZ) occurs at 30° or above. Where the maximum righting lever (GZ) occurs at angles of between 15° and 30°, the corresponding area under the righting lever curve should be:

$$0.055 + 0.001 (30^\circ - \Phi_{max}) \text{ metre-radians};$$

- b. The area under the righting lever curve (GZ curve) between the angles of heel of 30° and 40°, or between 30° and  $\Phi_i$  if this angle is less than 40°, should be not less than 0.03 meter-radians;
- c. The righting lever (GZ) should be at least 0.2 m at an angle of heel equal to or greater than 30°;
- d. The maximum righting lever (GZ) should occur at an angle of heel not less than 15°;
- e. The initial transverse metacentric height ( $GM_o$ ) should not be less than 0.15 m; and,
- f. Reference is made also to Chapter 2, Section 2, 2.1.3 to 2.1.5 and Chapter 3, Section 5, 5.1.

## 2.5 Special Purpose Ships

### 2.5.1. Application

The provisions given hereunder apply to special purpose ships, as defined in Chapter 1, Section 2 (Definitions), of not less than 500 gross tonnage. The Administration may also apply these provisions as far as reasonable and practicable to special purpose ships of less than 500 gross tonnage.

### 2.5.2. Stability criteria

The intact stability of special purpose ships should comply with the provisions given Chapter 2, Section 2, except that the alternative criteria given in Section 2, 2.4.5, of this Chapter, which apply to offshore supply vessels, may be used for special purpose ships of less than 100 m in length of similar design and characteristics.

## 2.6 Mobile Offshore Drilling Units (MODUs)


### 2.6.1. Application

- 2.6.1.1. The provisions given hereunder apply to mobile offshore drilling units as defined Chapter 1, Section 2 (Definitions) of the Introduction, the keels of which are laid or which are at a similar stage of construction on or after 1 May 1991. For MODUs constructed before that date, the corresponding provisions of chapter 3 of resolution A. 414(XI) should apply.

2.6.1.2. The coastal State may permit any unit designed to a lesser standard than that of this chapter to engage in operations, having taken account of the local environmental conditions. Any such unit should, however, comply with safety requirements which in the opinion of the coastal State are adequate for the intended operation and ensure the overall safety of the unit and the personnel on board.

## 2.6.2. Righting moment and wind heeling moment curves

2.6.2.1. Curves of righting moments and of wind heeling moments similar to figure 3.2.2 below with supporting calculations should be prepared covering the full range of operating draughts, including those in transit conditions, taking into account the maximum deck cargo and equipment in the most unfavorable position applicable. The righting moment curves and wind heeling moment curves should be related to the most critical axes. Account should be taken of the free surface of liquids in tanks.



**Figure 3.2.2: Righting moment and wind heeling moment curves**

2.6.2.2. Where equipment is of such a nature that it can be lowered and stowed, additional wind heeling moment curves may be required and such data should clearly indicate the position of such equipment.

2.6.2.3. The curves of wind heeling moment should be drawn for wind forces calculated by the following formula:

$$F = 0.5 * C_S * C_H * \rho_a * V^2 * A$$

Where:

F = Wind force (N);

C<sub>S</sub> = Shape coefficient depending on the shape of the structural member exposed to the wind (see table 3.2.1);

C<sub>H</sub> = Height coefficient depending on the height above sea level of the structural member exposed to wind (see table 3.2.2.);

- $\rho_a$  = Air mass density (1.222 kg/m<sup>3</sup>);
- V = Wind velocity (m/s);
- A = Projected area of all exposed surfaces in either the upright or the heeled condition (m<sup>2</sup>).

**Table 3.2.1: Values of the coefficient  $C_s$** 

Shape	$C_s$
Spherical	0.40
Cylindrical	0.50
Large flat surface (hull, deck-house, smooth under-deck areas)	1.00
Drilling derrick	1.25
Wires	1.20
Exposed beams and girders under deck	1.30
Small parts	1.40
Isolated shapes (crane, beam, etc.)	1.50
Clustered deck-houses or similar structures	1.10


**Table 3.2.2: Values of the coefficient  $C_H$** 

Height above sea level (m)	$C_H$
0-15.3	1
15.3- 30.5	1.1
30.5- 46	1.2
46.0- 61	1.3
61.0- 76	1.37
76.0- 91.5	1.43
91.5- 106.5	1.48
106.5- 122	1.52
122.0- 137	1.56
137.0- 152.5	1.6
152.5- 167.5	1.63
167.5- 183	1.67
183.0- 198	1.7
198.0- 213.5	1.72
213.5- 228.5	1.75
228.5- 244	1.77
244.0- 256	1.79
Above 256	1.8

2.6.2.4. Wind forces should be considered from any direction relative to the unit and the value of the wind velocity should be as follows:

- a. In general, a minimum wind velocity of 36 m/s (70 knots) for offshore service should be used for normal operating conditions and a minimum wind velocity of 51.5 m/s (100 knots) should be used for the severe storm conditions; and
  - b. Where a unit is to be limited in operation to sheltered locations (protected inland waters such as lakes, bays, swamps, rivers, etc.), consideration should be given to a reduced wind velocity of not less than 25.8 m/s (50 knots) for normal operating conditions.
- 2.6.2.5. In calculating the projected areas to the vertical plane, the area of surfaces exposed to wind due to heel or trim, such as under decks, etc., should be included, using the appropriate shape factor. Open truss work may be approximated by taking 30% of the projected block area of both the front and back section, i.e. 60% of the projected area of one side.
- 2.6.2.6. In calculating the wind heeling moments, the lever of the wind overturning force should be taken vertically from the center of pressure of all surfaces exposed to the wind to the center of lateral resistance of the underwater body of the unit. The unit is to be assumed floating free of mooring restraint.
- 2.6.2.7. The wind heeling moment curve should be calculated for a sufficient number of heel angles to define the curve. For ship-shaped hulls the curve may be assumed to vary as the cosine function of ship heel.
- 2.6.2.8. Wind heeling moments derived from wind-tunnel tests on a representative model of the unit may be considered as alternatives to the method given in 2.6.2.3 to 2.6.2.7. Such heeling moment determination should include lift and drag effects at various applicable heel angles.
- 2.6.3. Intact stability criteria
- 2.6.3.1. The stability of a unit in each mode of operation should meet the following criteria (see also figure 3.2.3):
- a. For surface and self-elevating units, the area under the righting moment curve to the second intercept or down-flooding angle, whichever is less, should be not less than 40% in excess of the area under the wind heeling moment curve to the same limiting angle;
  - b. For column-stabilized units the area under the righting moment curve to the angle of down-flooding should be not less than 30% in excess of the area under the wind heeling moment curve to the same limiting angle; and
  - c. The righting moment curve should be positive over the entire range of angles from upright to the second intercept.

Figure 3.2.3 Righting moment and heeling moment curves



2.6.3.2. Each unit should be capable of attaining a severe storm condition in a period of time consistent with the meteorological conditions. The procedures recommended and the approximate length of time required, considering both operating conditions and transit conditions, should be contained in the operating manual, as referred to in Chapter 3 Section 3, 3.6.2. It should be possible to achieve the severe storm condition without the removal or relocation of solid consumables or other variable load. However, the Administration may permit loading a unit past the point at which solid consumables would have to be removed or relocated to go to severe storm condition under the following conditions, provided the allowable KG requirement is not exceeded:

- a. In a geographic location where weather conditions annually or seasonally do not become sufficiently severe to require a unit to go to severe storm condition; or
- b. Where a unit is required to support extra deck load for a short period of time that is well within the bounds of a favorable weather forecast.

The geographic locations and weather conditions and loading conditions when this is permitted should be identified in the operating manual.

2.6.3.3. Alternative stability criteria may be considered by the Administration provided an equivalent level of safety is maintained and if they are demonstrated to afford adequate positive initial stability. In determining the acceptability of such criteria, the Administration should consider at least the following and take into account as appropriate:

- a. Environmental conditions representing realistic winds (including gusts) and waves appropriate for world-wide service in various modes of operation;
- b. Dynamic response of a unit. Analysis should include the results of wind-tunnel tests, wave tank model tests, and non-linear simulation, where appropriate. Any wind and wave spectra used should cover sufficient frequency ranges to ensure that critical motion responses are obtained;
- c. Potential for flooding taking into account dynamic responses in a seaway;
- d. Susceptibility to capsizing considering the unit's restoration energy and the static inclination due to the mean wind speed and the maximum dynamic response; and
- e. An adequate safety margin to account for uncertainties.

An example of alternative criteria for twin-pontoon column-stabilized semi-submersible units is given in section 2.6.4 below.

2.6.4. An example of alternative intact stability criteria for twin-pontoon column-stabilized semi-submersible units

2.6.4.1. The criteria given below apply only to twin-pontoon column-stabilized semi-submersible units in severe storm conditions which fall within the following ranges of parameters:

$V_p/V_t$  is between 0.48 and 0.58

$A_{wp}/(V_c)^{2/3}$  is between 0.72 and 1.00

$L_{wp}/[V_c * (L_{ptn}/2)]$  is between 0.40 and 0.70

The parameters used in the above equations are defined in paragraph 2.6.4.3.

2.6.4.2. Intact stability criteria

The stability of a unit in the survival mode of operation should meet the following criteria.

a. *Capsize criteria*

These criteria are based on the wind heeling moment and righting moment curves calculated as shown in Section 2, 2.6.2 of this Chapter at the survival draught. The reserve energy area 'B' should be equal to or greater than 10% of the dynamic response area 'A' as shown in figure 3.2.4.

$$\text{Area 'B'}/\text{Area 'A'} \geq 0.10$$

Where:

Area 'A' = Area under the righting moment curve measured from  $\Phi_1$  to  $(\Phi_1 + 1.15 * \Phi_{dyn})$ .

Area 'B' = Area under the righting moment curve measured from  $(\Phi_1 + 1.15 * \Phi_{dyn})$  to  $\Phi_2$ .

$\Phi_1$  = First intercept with the 100 knot wind moment curve.

$\Phi_2$  = Second intercept with the 100 knot wind moment curve.

$\Phi_{dyn}$  = Dynamic response angle due to waves and fluctuating wind.

$$\varphi_{dyn} = (10.3 + 17.8 * C) / (1 + GM / (1.46 + 0.28 * BM))$$

$$C = (L_{ptn}^{5/3} * VCP_{w1} * A_w * V_p * V_c^{1/3}) / (L_{wp}^{5/3} * V_t)$$

Parameters used in the above equations are defined in paragraph 2.6.4.3.




Figure 3.2.4 Righting moment and heeling moment curves

b. Down-flooding criteria

These criteria are based on the physical dimensions of the unit and the relative motion of the unit about a static inclination due to a 75 knot wind measured at the survival draught. The initial down-flooding distance ( $DFD_0$ ) should be greater than the reduction in down-flooding distance at the survival draught as shown in figure 3.2.5.

$$DFD_0 - RDFD > 0.0$$

Where:

$DFD_0$  is the initial down-flooding distance to  $T_{is}$  (m).

$RDFD$  is the reduction in down-flooding distance (m) equal to:

$$SF(k * QSD_1 + RMW)$$

SF is equal to 1.1, which is a safety factor to account for uncertainties in the analysis, such as non-linear effects;

k (correlation factor) =  $0.55 + 0.08 * (a - 4) + 0.056 * (1.52 - GM)$ ;

(GM cannot be taken to be greater than 2.44m)

$$a = (FBD_0/T_{is}) * (S_{ptn} * L_{ccc})/A_{wp}$$


(a cannot be taken to be less than 4)

$QSD_1$  is equal to  $DFD_0$  minus quasi-static down-flooding distance at  $\Phi_1$  (m), but not to be taken less than 3m;

$RMW$  is the relative motion due to waves about  $\Phi_1$  (m), equal to  $9.3 + 0.11 * (X - 12.19)$ ;

$$X = T_{is} * (V_t/V_p) * (A_{wp}^2/I_{wp}) * (L_{ccc}/L_{ptn})$$

(X cannot be taken to be less than 12.19m).



**Figure 3.2.5 Definition of down-flooding distance and relative motion**

The parameters used in the above equations are defined in paragraph 6.4.3.

#### 2.6.4.3. Geometric parameters

$A_{wp}$  = Water plane area at the survival draught, including the effects of bracing members as applicable ( $m^2$ ).

$A_w$  = Effective wind area with the unit in the upright position (i.e. the product of projected area, shape coefficient and height coefficient) ( $m^2$ ).

$BM$  = Vertical distance from the metacenter to the center of buoyancy with the unit in the upright position (m).

$T_{is}$  = Initial survival draught (m).

$FBD_0$  = Vertical distance from  $T_{is}$ , to the top of the upper exposed weather tight deck at the side (m).

$GM$  = (for paragraph 2.6.4.2.a) Metacentric height measured about the roll or diagonal axis, whichever gives the minimum reserve energy ratio, 'B'/A'. This axis is usually the diagonal axis as it possesses a characteristically larger projected wind area which influences the three characteristic angles mentioned above (m).

$GM$  = (for paragraph 2.6.4.2.b) Metacentric height measured about the axis which gives the minimum down-flooding distance margin (i.e. generally the direction that gives the largest  $QSD_1$ ) (m).

$I_{wp}$  = Water plane second moment of inertia at the survival draught, including the effects of bracing members as applicable ( $m^4$ ).

- $L_{ccc}$  = Longitudinal distance between centers of the corner columns (m).
- $L_{ptn}$  = Length of each pontoon (m).
- $S_{ptn}$  = Transverse distance between the centerlines of the pontoons (m).
- $V_c$  = Total volume of all columns from the top of the pontoons to the top of the column structure, except for any volume included in the upper deck (m<sup>3</sup>).
- $V_p$  = Total combined volume of both pontoons (m<sup>3</sup>).
- $V_t$  = Total volume of the structures (pontoons, columns and bracings) contributing to the buoyancy of the unit, from its baseline to the top of the column structure, except for any volume included in the upper deck (m<sup>3</sup>).
- $VCP_{w1}$  = Vertical center of wind pressure above  $T_{is}$ (m).

2.6.4.4. Capsize criteria assessment form

Input data

- GM .....=.....m
- BM .....=.....m
- $VCP_{w1}$  .....=.....m
- $A_w$  .....=.....m<sup>2</sup>
- $V_t$  .....=.....m<sup>3</sup>
- $V_c$  .....=.....m<sup>3</sup>
- $V_p$  .....=.....m<sup>3</sup>
- $l_{wp}$  .....=.....m<sup>4</sup>
- $L_{ptn}$  .....=.....m

Determine

- $\Phi_1$  .....=.....deg
- $\Phi_2$  .....=.....deg
- $C = (L_{ptn}^{5/3} * VCP_{w1} * A_w * V_p * V_c^{1/3}) / (l_{wp}^{5/3} * V_t)$  .....=.....m<sup>-1</sup>
- $\varphi_{dyn} = (10.3 + 17.8C) / (1 + GM / (1.46 + 0.28BM))$  .....=.....deg
- Area 'A' .....=.....m-deg
- Area 'B' .....=.....m-deg

Results

Reserve energy ratio:

- 'B'/'A' = ..... (minimum=0.1)
- GM = .....m (KG = .....m)

Note: The minimum GM is that which produces a 'B'/'A' ratio = 0.1.

## 2.6.4.5. Down-flooding criteria assessment form

## Input data

$DFD_0$  ..... = ..... m  
 $FBD_0$  ..... = ..... m  
 $GM$  ..... = ..... m  
 $T_{is}$  ..... = ..... m  
 $V_t$  ..... = ..... m<sup>3</sup>  
 $V_p$  ..... = ..... m<sup>3</sup>  
 $A_{wp}$  ..... = ..... m<sup>2</sup>  
 $l_{wp}$  ..... = ..... m<sup>4</sup>  
 $L_{ccc}$  ..... = ..... m  
 $L_{ptn}$  ..... = ..... m  
 $S_{ptn}$  ..... = ..... m  
 $SF$  ..... = 1.1

## Determine

$\varphi_1$  ..... = ..... deg  
 $DFD_1$  ..... = ..... m  
 $QSD_1 = DFD_0 - DFD_1$  ..... = ..... m  
 $a = (FBD_0/T_{is}) * (S_{ptn} * L_{ccc}) / A_{wp}$  ..... = ..... (a<sub>min</sub>=4)  
 $k = 0.55 + 0.08 * (a - 4) + 0.056 * (1.52 - GM)$  ..... = ..... m (GM<sub>max</sub>=2.44m)  
 $X = T_{is} * (V_t / V_p) * (A_{wp}^2 / l_{wp}) * (L_{ccc} / L_{ptn})$  ..... = ..... m (X<sub>min</sub>=12.19m)  
 $RMW = 9.3 + 0.11 * (X - 12.19)$  ..... = ..... m  
 $RDFD = SF * (k * QSD_1 + RMW)$  ..... = ..... m

## Results

Down-flooding margin:

 $DFD_0 - RDFD = \dots\dots\dots$  (minimum=0.0m)

GM = .....m

(KG=.....m)

**Note:** The minimum GM is that which produces a down-flooding margin = 0.0 m.

---

**SECTION 3 GUIDANCE IN PREPARING STABILITY INFORMATION****Contents**

3.1	Effect Of Free Surfaces Of Liquids In Tanks.....	48
3.2	Permanent Ballast .....	49
3.3	Assessment Of Compliance With Stability Criteria .....	49
3.4	Standard Conditions Of Loading To Be Examined .....	49
3.5	Calculation Of Stability Curves.....	52
3.6	Stability Booklet.....	53
3.7	Operational Measures For Ships Carrying Timber Deck Cargoes.....	54
3.8	Operating Booklets For Certain Ships.....	55

**3.1 Effect of Free Surfaces Of Liquids In Tanks**

## 3.1.1. Effect of free surfaces of liquids in tanks

- 3.1.1.1. For all loading conditions, the initial metacentric height and the righting lever curve should be corrected for the effect of free surfaces of liquids in tanks.
- 3.1.1.2. Free surface effects should be considered whenever the filling level in a tank is less than 98% of full condition. Free surface effects need not be considered where a tank is nominally full, i.e. filling level is 98% or above. Free surface effects for small tanks may be ignored under condition specified in 3.1.1.12 below.  
But nominally, full cargo tanks should be corrected for free surface effects at 98% filling level. In doing so, the correction to initial metacentric height should be based on the inertia moment of liquid surface at 5° of heeling angle divided by displacement, and the correction to righting lever is suggested to be on the basis of real shifting moment of cargo liquids.
- 3.1.1.3. Tanks which are taken into consideration when determining the free surface correction may be in one of two categories:
- Tanks with filling levels fixed (e.g., liquid cargo, water ballast). The free surface correction should be defined for the actual filling level to be used in each tank; or
  - Tanks with filling levels variable (e.g., consumable liquids such as fuel oil, diesel oil and fresh water, and also liquid cargo and water ballast during liquid transfer operations). Except as permitted in 3.1.1.5 and 3.1.1.6 below, the free surface correction should be the maximum value attainable between the filling limits envisaged for each tank, consistent with any operating instructions.
- 3.1.1.4. In calculating the free surface effects in tanks containing consumable liquids, it should be assumed that for each type of liquid at least one transverse pair or a single centerline tank has a free surface and the tank or combination of tanks taken into account should be those where the effect of free surfaces is the greatest.
- 3.1.1.5. Where water ballast tanks, including anti-rolling tanks and anti-heeling tanks, are to be filled or discharged during the course of a voyage, the free surface effects should be calculated to take account of the most onerous transitory stage relating to such operations.
- 3.1.1.6. For ships engaged in liquid transfer operations, the free surface corrections at any stage of the liquid transfer operations may be determined in accordance with the filling level in each tank at that stage of the transfer operation.
- 3.1.1.7. The corrections to the initial metacentric height and to the righting lever curve should be addressed separately as follows.
- 3.1.1.8. In determining the correction to initial metacentric height, the transverse moments of inertia of the tanks should be calculated at 0° angle of heel according to the categories indicated in 3.1.1.3.
- 3.1.1.9. The righting lever curve may be corrected by any of the following methods subject to the agreement of the Administration:

- a. Correction based on the actual moment of fluid transfer for each angle of heel calculated; or
- b. Correction based on the moment of inertia, calculated at 0° angle of heel, modified at each angle of heel calculated.

3.1.1.10. Corrections may be calculated according to the categories indicated in 3.1.1.2.

3.1.1.11. Whichever method is selected for correcting the righting lever curve, only that method should be presented in the ship's stability booklet. However, where an alternative method is described for use in manually calculated loading conditions, an explanation of the differences which may be found in the results, as well as an example correction for each alternative, should be included.

3.1.1.12. Small tanks which satisfy the following condition corresponding to an angle of inclination of 30°, need not be included in the correction:

$$M_{fs}/\Delta_{min} < 0.01 m$$

Where:

$M_{fs}$  = Free surface moment (m-t);

$\Delta_{min}$  = Minimum ship displacement calculated at  $T_{min}(t)$ ;

$T_{min}$  = Minimum mean service draught of the ship without cargo, with 10% stores and minimum water ballast, if required (m).

3.1.1.13. The usual remainder of liquids in empty tanks need not be taken into account in calculating the corrections, provided that the total of such residual liquids does not constitute a significant free surface effect.

## 3.2 Permanent Ballast

If used, permanent ballast should be located in accordance with a plan approved by the Administration and in a manner that prevents shifting of position. Permanent ballast should not be removed from the ship or relocated within the ship without the approval of the Administration. Permanent ballast particulars should be noted in the ship's stability booklet.

## 3.3 Assessment of Compliance with Stability Criteria

3.3.1. Except as otherwise required by this Code, for the purpose of assessing in general whether the stability criteria are met, stability curves using the assumptions given in this Code should be drawn for the loading conditions intended by the owner in respect of the ship's operations.

3.3.2. If the owner of the ship does not supply sufficiently detailed information regarding such loading conditions, calculations should be made for the standard loading conditions.

## 3.4 Standard Conditions of Loading to Be Examined

3.4.1. Loading conditions

The standard loading conditions referred to in the text of the present Code are as follows.

3.4.1.1. For a passenger ship

- a. Ship in the fully loaded departure condition with cargo, full stores and fuel and with the full number of passengers with their luggage;

- b. Ship in the fully loaded arrival condition, with cargo, the full number of passengers and their luggage but with only 10% stores and fuel remaining;
- c. Ship without cargo, but with full stores and fuel and the full number of passengers and their luggage; and
- d. Ship in the same condition as at 0 above with only 10% stores and fuel remaining.

#### 3.4.1.2. For a cargo ship

- a. Ship in the fully loaded departure condition, with cargo homogeneously distributed throughout all cargo spaces and with full stores and fuel;
- b. Ship in the fully loaded arrival condition with cargo homogeneously distributed throughout all cargo spaces and with 10% stores and fuel remaining;
- c. Ship in ballast in the departure condition, without cargo but with full stores and fuel; and.
- d. Ship in ballast in the arrival condition, without cargo and with 10% stores and fuel remaining.

#### 3.4.1.3. For a cargo ship intended to carry deck cargoes

- a. Ship in the fully loaded departure condition with cargo homogeneously distributed in the holds and with cargo specified in extension and mass on deck, with full stores and fuel; and
- b. Ship in the fully loaded arrival condition with cargo homogeneously distributed in holds and with a cargo specified in extension and mass on deck, with 10% stores and fuel.

#### 3.4.1.4. For a ship intended to carry timber deck cargoes

The loading conditions which should be considered for ships carrying timber deck cargoes are specified in 3.4.1.3 above. The stowage of timber deck cargoes should comply with the provisions of chapter 3 of the Code of Safe Practice for Ships Carrying Timber Deck Cargoes, 1991(resolution A. 715(17)).

#### 3.4.1.5. For offshore supply vessel

- a. Vessel in fully loaded departure condition with cargo distributed below deck and with cargo specified by position and weight on deck, with full stores and fuel, corresponding to the worst service condition in which all the relevant stability criteria are met;
- b. Vessel in fully loaded arrival condition with cargo as specified in '1' above, but with 10% stores and fuel;
- c. Vessel in ballast departure condition, without cargo but with full stores and fuel;
- d. Vessel in ballast arrival condition, without cargo and with 10% stores and fuel remaining; and
- e. Vessel in the worst anticipated operating condition.

#### 3.4.1.6. For fishing vessel

For fishing vessels, the standard loading conditions referred to in Chapter 3, Section 2, 2.1 are as follows:

- a. Departure conditions for the fishing grounds with full fuel, stores, ice, fishing gear, etc.
- b. Departure from the fishing grounds with full catch and a percentage of stores, fuel, etc., as agreed by the Administration;
- c. Arrival at home port with 10% stores, fuel, etc. remaining and full catch; and

- d. Arrival at home port with 10% stores, fuel, etc. and a minimum catch, which should normally be 20% of full catch but may be up to 40% provided the Administration is satisfied that operating patterns justify such a value.

#### 3.4.2. Assumptions for calculating loading conditions

- 3.4.2.1. For the fully loaded conditions mentioned in 3.4.1.2.a, 3.4.1.2.b, 3.4.1.3.a and 3.4.1.3.b of this section, if a dry cargo ship has tanks for liquid cargo, the effective deadweight in the loading conditions therein described should be distributed according to two assumptions, i.e. with cargo tanks full, and with cargo tanks empty.
- 3.4.2.2. In the conditions mentioned in 3.4.1.1.a, 3.4.1.2.a and 3.4.1.3.a, it should be assumed that the ship is loaded to its subdivision load line or summer load line or if intended to carry a timber deck cargo, to the summer timber load line with water ballast tanks empty.
- 3.4.2.3. If in any loading condition water ballast is necessary, additional diagrams should be calculated taking into account the water ballast. Its quantity and disposition should be stated.
- 3.4.2.4. In all cases, the cargo in holds is assumed to be fully homogeneous unless this condition is inconsistent with the practical service of the ship.
- 3.4.2.5. In all cases, when deck cargo is carried, a realistic stowage mass should be assumed and stated, including the height of the cargo.
- 3.4.2.6. Considering timber deck cargo the following assumptions are to be made for calculating the loading conditions referred to in 3.4.1.4 of this Section:
  - a. The amount of cargo and ballast should correspond to the worst service condition in which all the relevant stability criteria of Chapter 2 Section 2, 2.2 or the optional criteria given in Chapter 2, Section 3, 3.3.2, are met. In the arrival condition, it should be assumed that the weight of the deck cargo has increased by 10% owing to water absorption.
- 3.4.2.7. For offshore supply vessels, the assumptions for calculating loading conditions should be as follows:
  - a. If a vessel is fitted with cargo tanks, the fully loaded conditions of 3.4.1.5.a, 3.4.1.5.b should be modified, assuming first the cargo tanks full and then the cargo tanks empty;
  - b. If in any loading condition water ballast is necessary, additional diagrams should be calculated, taking into account the water ballast, the quantity and disposition of which should be stated in the stability information;
  - c. In all cases when deck cargo is carried a realistic stowage weight should be assumed and stated in the stability information, including the height of the cargo and its center of gravity;
  - d. Where pipes are carried on deck, a quantity of trapped water equal to a certain percentage of the net volume of the pipe deck cargo should be assumed in and around the pipes. The net volume should be taken as the internal volume of the pipes, plus the volume between the pipes. This percentage should be 30 if the freeboard amidships is equal to or less than 0.015 L and 10 if the freeboard amidships is equal to or greater than 0.03 L. For intermediate values of the freeboard amidships the percentage may be obtained by linear interpolation. In assessing the quantity of trapped

- water, the Administration may take into account positive or negative sheer aft, actual trim and area of operation; or
- e. If a vessel operates in zones where ice accretion is likely to occur, allowance for icing should be made in accordance with the provisions of Chapter 3, Section 6 (Icing considerations).

3.4.2.8. For fishing vessels, the assumptions for calculating loading conditions should be as follows:

- a. Allowance should be made for the weight of the wet fishing nets and tackle, etc., on deck;
- b. allowance for icing, where this is anticipated to occur, should be made in accordance with the provisions of Chapter 3, Section 6, 6.3.
- c. In all cases the cargo should be assumed to be homogeneous unless this is in consistent with practice;
- d. In conditions referred to in 3.4.1.6.b and 3.4.1.6.c deck cargo should be included if such a practice is anticipated;
- e. Water ballast should normally only be included if carried in tanks which are specially provided for this purpose.

### 3.5 Calculation of Stability Curves

#### 3.5.1. General

Hydrostatic and stability curves should be prepared for the trim range of operating loading conditions taking into account the change in trim due to heel (free trim hydrostatic calculation). The calculations should take into account the volume to the upper surface of the deck sheathing. Furthermore, appendages and sea chests need to be considered when calculating hydrostatics and cross curves of stability. In the presence of port-starboard asymmetry, the most unfavorable righting lever curve should be used.

#### 3.5.2. Superstructures, deckhouses, etc., which may be taken into account

3.5.2.1. Enclosed superstructures complying with regulation 3(10)(b) of the 1966 Load Line Convention and the Protocol of 1988 relating thereto, as amended, may be taken into account.

3.5.2.2. Additional tiers of similarly enclosed superstructures may also be taken into account. As guidance windows (pane and frame) that are considered without deadlights in additional tiers above the second tier if considered buoyant should be designed with strength to sustain a safety margin with regard to the required strength of the surrounding structure.

3.5.2.3. Deckhouses on the freeboard deck may be taken into account, provided that they comply with the conditions for enclosed superstructures laid down in regulation 3(10)(b) of the 1966 Load Line Convention and the Protocol of 1988 relating thereto, as amended.

3.5.2.4. Where deckhouses comply with the above conditions, except that no additional exit is provided to a deck above, such deckhouses should not be taken into account; however, any deck openings inside such deckhouses should be considered as closed even where no means of closure are provided.

3.5.2.5. Deckhouses, the doors of which do not comply with the requirements of regulation 12 of the 1966 Load Line Convention and the Protocol of 1988 relating thereto, as amended, should not be taken into account; however, any deck

openings inside the deckhouse are regarded as closed where their means of closure comply with the requirements of regulations 15, 17 or 18 of the 1966 Load Line Convention and the Protocol of 1988 relating thereto, as amended.

- 3.5.2.6. Deckhouses on decks above the freeboard deck should not be taken into account, but openings within them may be regarded as closed.
- 3.5.2.7. Superstructures and deckhouses not regarded as enclosed can, however, be taken into account in stability calculations up to the angle at which their openings are flooded (at this angle, the static stability curve should show one or more steps, and in subsequent computations the flooded space should be considered non-existent).
- 3.5.2.8. In cases where the ship would sink due to flooding through any openings, the stability curve should be cut short at the corresponding angle of flooding and the ship should be considered to have entirely lost its stability.
- 3.5.2.9. Small openings such as those for passing wires or chains, tackle and anchors, and also holes of scuppers, discharge and sanitary pipes should not be considered as open if they submerge at an angle of inclination more than 30°. If they submerge at an angle of 30° or less, these openings should be assumed open if the Administration considers this to be a source of significant flooding.
- 3.5.2.10. Trunks may be taken into account. Hatchways may also be taken into account having regard to the effectiveness of their closures.

### 3.5.3. Calculation of stability curves for ships carrying timber deck cargoes

In addition to the provisions given above, the Administration may allow account to be taken of the buoyancy of the deck cargo assuming that such cargo has a permeability of 25% of the volume occupied by the cargo. Additional curves of stability may be required if the Administration considers it necessary to investigate the influence of different permeabilities and/or assumed effective height of the deck cargo.

## 3.6 Stability Booklet

- 3.6.1. Stability data and associated plans should be drawn up in the working language of the ship and any other language the Administration may require. Reference is also made to the International Safety Management (ISM) Code, adopted by the Organization by resolution A.741(18). All translations of the stability booklet should be approved.
- 3.6.2. Each ship should be provided with a stability booklet, approved by the Administration, which contains sufficient information to enable the master to operate the ship in compliance with the applicable requirements contained in the Code. The Administration may have additional requirements. On a mobile offshore drilling unit, the stability booklet may be referred to as an operating manual. The stability booklet may include information on longitudinal strength. This Code addresses only the stability-related contents of the booklet.
- 3.6.3. For ships carrying timber deck cargoes
  - a. Comprehensive stability information should be supplied which takes into account timber deck cargo. Such information should enable the master, rapidly and simply, to obtain accurate guidance as to the stability of the ship under varying conditions of service. Comprehensive rolling period tables or diagrams have proved to be very useful aids in verifying the actual stability conditions;

- b. The Administration may deem it necessary that the master be given information setting out the changes in deck cargo from that shown in the loading conditions, when the permeability of the deck cargo is significantly different from 25% (refer Section 3, 3.5.3 of this Chapter); and
  - c. Conditions should be shown indicating the maximum permissible amount of deck cargo having regard to the lightest stowage rate likely to be met in service.
- 3.6.4. The format of the stability booklet and the information included will vary dependent on the ship type and operation. In developing the stability booklet, consideration should be given to including the following information:
- a. A general description of the ship;
  - b. Instructions on the use of the booklet;
  - c. General arrangement plans showing watertight compartments, closures, vents, down flooding angles, permanent ballast, allowable deck loadings and freeboard diagrams;
  - d. Hydrostatic curves or tables and cross curves of stability calculated on a free-trimming basis, for the ranges of displacement and trim anticipated in normal operating conditions;
  - e. Capacity plan or tables showing capacities and centers of gravity for each cargo stowage space;
  - f. Tank sounding tables showing capacities, centers of gravity, and free surface data for each tank;
  - g. Information on loading restrictions, such as maximum KG or minimum GM curve or table that can be used to determine compliance with the applicable stability criteria;
  - h. Standard operating conditions and examples for developing other acceptable loading conditions using the information contained in the stability booklet;
  - i. A brief description of the stability calculations done including assumptions;
  - j. General precautions for preventing unintentional flooding;
  - k. Information concerning the use of any special cross-flooding fittings with descriptions of damage conditions which may require cross-flooding;
  - l. Any other necessary guidance for the safe operation of the ship under normal and emergency conditions;
  - m. A table of contents and index for each booklet;
  - n. Inclining test report for the ship, or:
    - i. Where the stability data is based on a sister ship, the inclining test report of that sister ship along with the lightship measurement report for the ship in question; or
    - ii. Where lightship particulars are determined by other methods than from inclining of the ship or its sister, a summary of the method used to determine those particulars;
  - o. Recommendation for determination of ship's stability by means of an in-service inclining test.
- 3.6.5. As an alternative to the stability booklet mentioned in 3.6.1 above, a simplified booklet in an approved form containing sufficient information to enable the master to operate the ship in compliance with the applicable provisions of the Code as may be provided at the discretion of the Administration concerned.

### 3.7 Operational Measures for Ships Carrying Timber Deck Cargoes

- 3.7.1. The stability of the ship at all times, including during the process of loading and unloading timber deck cargo, should be positive and to a standard acceptable to the Administration. It should be calculated having regard to:

- a. The increased weight of the timber deck cargo due to absorption of water in dried or seasoned timber,
  - b. Variations in consumables;
  - c. The free surface effect of liquid in tanks; and
  - d. Weight of water trapped in broken spaces within the timber deck cargo and especially logs.
- 3.7.2. The master should:
- a. Cease all loading operations if a list develops for which there is no satisfactory explanation and it would be imprudent to continue loading;
  - b. Before proceeding to sea, ensure that:
    - i. The ship is upright;
    - ii. The ship has an adequate metacentric height; and
    - iii. The ship meets the required stability criteria.
- 3.7.3. The masters of ships having a length less than 100 m should also:
- a. Exercise good judgment to ensure that a ship which carries stowed logs on deck has sufficient additional buoyancy so as to avoid overloading and loss of stability at sea;
  - b. Be aware that the calculated  $GM_0$  in the departure condition may decrease continuously owing to water absorption by the deck cargo of logs, consumption of fuel, water and stores and ensure that the ship has adequate  $GM_0$  throughout the voyage; and
  - c. Be aware that ballasting after departure may cause the ship's operating draught to exceed the timber load line. Ballasting and deballasting should be carried out in accordance with the guidance provided in the Code of Safe Practice for Ships Carrying Timber Deck Cargoes, 1991 (resolution A.715(17)).
- 3.7.4. Ships carrying timber deck cargoes should operate, as far as possible, with a safe margin of stability and with a metacentric height which is consistent with safety requirements but such metacentric height should not be allowed to fall below the recommended minimum, as specified in Chapter 2, Section 3, 3.3.2.
- 3.7.5. However, excessive initial stability should be avoided as it will result in rapid and violent motion in heavy seas which will impose large sliding and racking forces on the cargo causing high stresses on the lashings. Operational experience indicates that metacentric height should preferably not exceed 3% of the breadth in order to prevent excessive accelerations in rolling provided that the relevant stability criteria given in Chapter 3, Section 3, 3.3.2 are satisfied. This recommendation may not apply to all ships and the master should take into consideration the stability information obtained from the ship's stability booklet.

### 3.8 Operating Booklets for Certain Ships

- 3.8.1. Special purpose ships and novel craft, should be provided with additional information in the stability booklet such as design limitations, maximum speed, worst intended weather conditions or other information regarding the handling of the craft that the master needs to operate the ship safely.
- 3.8.2. For double hull oil tankers of single cargo tank across design, an operation manual for loading and unloading cargo oil should be provided, including operational procedures of loading and unloading cargo oil and detailed data of the initial metacentric height of the oil tanker and that of free surface correction of liquids in cargo oil tanks and ballast tanks during loading and unloading cargo oil (including ballasting and discharging) and cargo oil washing of tanks.

- 3.8.3. The stability booklet of Ro-Ro passenger ships should contain information concerning the importance of securing and maintaining all closures watertight due to the rapid loss of stability which may result when water enters the vehicle deck and the fact that capsize can rapidly follow.

---

## SECTION 4 STABILITY CALCULATIONS PERFORMED BY STABILITY INSTRUMENTS

### Contents

4.1 Stability Instruments .....	58
---------------------------------	----

---

**4.1 Stability Instruments****4.1.1. General**

A stability instrument installed onboard should cover all stability requirements applicable to the ship. The software is subject to approval by the Administration. Active and passive systems are defined in 4.1.2 below. These requirements cover passive systems and the off-line operation mode of active systems only.

4.1.1.1. The scope of stability calculation software should be in accordance with the approved stability booklet and should at least include all information and perform all calculations or checks as necessary to ensure compliance with the applicable stability requirements.

4.1.1.2. An approved stability instrument is not a substitute for the approved stability booklet, and is used as a supplement to the approved stability booklet to facilitate stability calculations.

4.1.1.3. The input/output information should be easily comparable with the approved stability booklet so as to avoid confusion and possible misinterpretation by the operator.

4.1.1.4. An operation manual should be provided for the stability instrument.

4.1.1.5. The language in which the stability calculation results are displayed and printed out as well as the operation manual is written should be the same as used in the ship's approved stability booklet. A translation into a language considered appropriate may be required.

4.1.1.6. The stability instrument is ship specific equipment and the results of the calculations are only applicable to the ship for which it has been approved.

4.1.1.7. In case of modifications of the ship which cause alterations in the stability booklet, the specific approval of any original stability calculation software is no longer valid. The software should be modified accordingly and re-approved.

4.1.1.8. Any change in software version related to the stability calculation should be reported to and be approved by the Administration.

**4.1.2. Data entry system**

4.1.2.1. A passive system requires manual data entry.

4.1.2.2. An active system replaces partly the manual entry with sensors reading and entering the contents of tanks, etc.

4.1.2.3. Any integrated system which controls or initiates actions based on the sensor-supplied inputs is not within the scope of this Code except the part calculating the stability.

**4.1.3. Types of stability software**

Three types of calculations performed by stability software are acceptable depending upon a vessel's stability requirements:

## Type 1

Software calculating intact stability only (for vessels not required to meet a damage stability criterion).

## Type 2

Software calculating intact stability and checking damage stability on basis of a limit curve (e.g., for vessels applicable to SOLAS part B-1 damage stability calculations, etc.) or previously approved loading conditions.

## Type 3

Software calculating intact stability and damage stability by direct application of pre-programmed damage cases for each loading condition (for some tankers, etc.). The results of the direct calculations performed by the stability instrument could be accepted by the Administration even if they differ from the required minimum GM or maximum VCG stated in the approved stability booklet.

Such deviations could be accepted under the condition that all relevant stability requirements will be complied with by the results of the direct calculations.

## 4.1.4. Functional requirements

4.1.4.1. The stability instrument should present relevant parameters of each loading condition in order to assist the master in his judgment on whether the ship is loaded within the approved limits. The following parameters should be presented for a given loading condition:

- a. Detailed deadweight data items including center of gravity and free surfaces, if applicable;
- b. Trim, list;
- c. Draught at the draught marks and perpendiculars;
- d. Summary of loading condition displacement, VCG, LCG, TCG, VCB, LCB, TCB, LCF, GM and GML;
- e. Table showing the righting lever versus heeling angle including trim and draught;
- f. Down-flooding angle and corresponding down-flooding opening; and
- g. Compliance with stability criteria: Listings of all calculated stability criteria, the limit values, the obtained values and the conclusions (criteria fulfilled or not fulfilled).

4.1.4.2. If direct damage stability calculations are performed, the relevant damage cases according to the applicable rules should be pre-defined for automatic check of a given loading condition.

4.1.4.3. A clear warning should be given on screen and in hard copy printout if any of the limitations are not complied with.

4.1.4.4. The data should be presented on screen and in hard copy printout in a clear unambiguous manner.

4.1.4.5. The date and time of a saved calculation should be part of the screen display and hard copy printout.

4.1.4.6. Each hard copy printout should contain identification of the calculation program including version number.

4.1.4.7. Units of measurement should be clearly identified and used consistently within a loading calculation.

## 4.1.5. Acceptable tolerances

Depending on the type and scope of programs, the acceptable tolerances should be determined differently according to 4.1.5.1 or 4.1.5.2. Deviation from these tolerances should not be accepted unless the Administration considers that there is a satisfactory explanation for the difference and that there will be no adverse effect on the safety of the ship.

The accuracy of the results should be determined using an independent program or the approved stability booklet with identical input.

- 4.1.5.1. Programs which use only pre-programmed data from the approved stability booklet as the basis for stability calculations should have zero tolerances for the printouts of input data.

Output data tolerances should be close to zero, however, small differences associated with calculation rounding or abridged input data are acceptable. Additionally, differences associated with the use of hydrostatic and stability data for trims and the method calculating free surface moments that differ from those in the approved stability booklet are acceptable subject to review by the Administration.

- 4.1.5.2. Programs which use hull form models as their basis for stability calculations should have tolerances for the printouts of basic calculated data established against either data from the approved stability booklet or data obtained using the Administration's approval model.

4.1.6. Approval procedure

4.1.6.1. Conditions of approval of the stability instrument

- a. The software approval includes:
  - i. Verification of type approval, if any;
  - ii. Verification that the data used is consistent with the current condition of the ship (refer to 4.1.6.2);
  - iii. Verification and approval of the test conditions; and
  - iv. Verification that the software is appropriate for the type of ship and stability calculations required.
- b. The satisfactory operation of the stability instrument is to be verified by testing upon installation (refer to 4.1.8). A copy of the approved test conditions and the operation manual for the stability instrument are to be available onboard.

4.1.6.2. Specific approval

- a. The accuracy of the computational results and actual ship data used by the calculation program for the particular ship on which the program will be installed should be to the satisfaction of the Administration.
- b. Upon application for data verification, minimum of four(4) loading conditions should be taken from the ship's approved stability booklet, which should be used as the test conditions. For ships carrying liquids in bulk, at least one of the conditions should include partially filled tanks. For ships carrying grain in bulk, one of the grain loading conditions should include a partially filled grain compartment. Within the test conditions, each compartment should be loaded at least once. The test conditions normally should cover the range of load draughts from the deepest envisaged loaded condition to the light ballast condition and should include at least one departure and one arrival condition.
- c. The following data, submitted by the applicant, should be consistent with arrangements and most recently approved lightship characteristics of the ship

according to current plans and documentation on file, subject to possible further verification onboard:

- i. Identification of the calculation program including version number. Main dimensions, hydrostatic particulars and, if applicable, the ship's profile;
- ii. The position of the forward and aft perpendiculars, and if appropriate, the calculation method to derive the forward and aft draughts at the actual position of the ship's draught marks;
- iii. Ship's light weight and center of gravity derived from the most recently approved inclining experiment or lightweight survey;
- iv. Lines plan, offset tables or other suitable presentation of hull form data including all relevant appendages, if necessary to model the ship;
- v. Compartment definitions, including frame spacing, and centers of volume, together with capacity tables (sounding / ullage tables), free surface corrections, if appropriate; and
- vi. Cargo and consumables distribution for each loading condition.

Verification by the Administration does not absolve the ship owner of responsibility for ensuring that the information programmed into the stability instrument is consistent with the current condition of the ship and approved stability booklet.

#### 4.1.7. User manual

A simple and straightforward user manual written in the same language as the stability booklet should be provided, containing descriptions and instructions, as appropriate, for at least the following:

- a. Installation;
- b. Function keys;
- c. Menu displays;
- d. Input and output data;
- e. Required minimum hardware to operate the software;
- f. Use of the test loading conditions;
- g. Computer-guided dialogue steps; and
- h. List of warnings.

A user manual in electronic format may be provided in addition to the written manual.

#### 4.1.8. Installation testing

4.1.8.1. To ensure correct working of the stability instrument after the final or updated software has been installed, it is the responsibility of the ship's master to have test calculations carried out according to the following pattern in the presence of an Administration's surveyor. From the approved test conditions at least one load case (other than light ship) should be calculated.

**Note:** Actual loading condition results are not suitable for checking the correct working of the stability instrument.

4.1.8.2. Normally, the test conditions are permanently stored in the stability instrument. Steps to be performed:

- a. Retrieve the test load case and start a calculation run; compare the stability results with those in the documentation;
- b. Change several items of deadweight (tank weights and the cargo weight) sufficiently to change the draught or displacement by at least 10%. The results

should be reviewed to ensure that they differ in a logical way from those of the approved test condition;

- c. Revise the above modified load condition to restore the initial test condition and compare the results. The relevant input and output data of the approved test condition should be replicated; and
- d. Alternatively, one or more test conditions should be selected and the test calculations performed by entering all deadweight data for each selected test condition into the program as if it were a proposed loading. The results should be verified as identical to the results in the approved copy of the test conditions.

#### 4.1.9. Periodical testing

4.1.9.1. It is the responsibility of the ship's master to check the accuracy of the stability instrument at each annual survey by applying at least one approved test condition. If an Administration's representative is not present for the stability instrument check, a copy of the test condition results obtained by this check should be retained on board as documentation of satisfactory testing for the Administration's representative's verification.

4.1.9.2. At each renewal survey this checking for all approved test loading conditions should be done in the presence of the Administration's representative.

4.1.9.3. The testing procedure should be carried out in accordance with 4.1.8 above.

#### 4.1.10. Other requirements

4.1.10.1. Protection against unintentional or unauthorized modification of programs and data should be provided.

4.1.10.2. The program should monitor operation and activate an alarm when the program is incorrectly or abnormally used.

4.1.10.3. The program and any data stored in the system should be protected from corruption by loss of power.

4.1.10.4. Error messages with regard to limitations such as filling a compartment beyond capacity or more than once, or exceeding the assigned load line, etc., should be included.

4.1.10.5. If any software related to stability measures such as sea keeping abilities of the vessel, evaluation of in-service inclining experiments and processing the results for further calculation, as well as the evaluation of roll period measurements is installed on board, such software should be reported to the Administration for consideration.

4.1.10.6. Program functionalities should include mass and moment calculations with numerical and graphical presentation of the results, such as initial stability values, righting lever curve, areas under the righting lever curve and range of stability.

4.1.10.7. All input data from automatically measuring sensors, such as gauging devices or draught reading systems should be presented to the user for verification. The user should have the possibility to override faulty readings manually.

---

## SECTION 5 OPERATIONAL PROVISIONS AGAINST CAPSIZING

### Contents

5.1. General Precautions Against Capsizing.....	64
5.2. Operational Precautions In Heavy Weather.....	64
5.3. Ship Handling In Heavy Weather .....	65

**5.1. General Precautions against Capsizing**

- 5.1.1. Compliance with the stability criteria does not ensure immunity against capsizing, regardless of the circumstances, or absolve the master from his responsibilities. Masters should therefore exercise prudence and good seamanship having regard to the season of the year, weather forecasts and the navigational zone and should take the appropriate action as to speed and course warranted by the prevailing circumstances.
- 5.1.2. Care should be taken that the cargo allocated to the ship is capable of being stowed so that compliance with the criteria can be achieved. If necessary, the amount should be limited to the extent that ballast weight may be required.
- 5.1.3. Before a voyage commences, care should be taken to ensure that the cargo, cargo handling cranes and sizeable pieces of equipment have been properly stowed or lashed so as to minimize the possibility of both longitudinal and lateral shifting, while at sea, under the effect of acceleration caused by rolling and pitching.
- 5.1.4. A ship, when engaged in towing operations, should possess an adequate reserve of stability to withstand the anticipated heeling moment arising from the tow line without endangering the towing ship. Deck cargo on board the towing ship should be so positioned as not to endanger the safe working of the crew on deck or impede the proper functioning of the towing equipment and be properly secured. Tow line arrangements should include towing springs and a method of quick release of the tow.
- 5.1.5. The number of partially filled or slack tanks should be kept to a minimum because of their adverse effect on stability. The negative effect on stability of filled pool tanks should be taken into consideration.
- 5.1.6. The stability criteria contained in Chapter 2, Section 2 set minimum values, but no maximum values are recommended. It is advisable to avoid excessive values of metacentric height, since these might lead to acceleration forces which could be prejudicial to the ship, its complement, its equipment and to safe carriage of the cargo. Slack tanks may, in exceptional cases, be used as a means of reducing excessive values of metacentric height. In such cases, due consideration should be given to sloshing effects.
- 5.1.7. Regard should be paid to the possible adverse effects on stability where certain bulk cargoes are carried. In this connection, attention should be paid to the IMO Code of Safe Practice for Solid Bulk Cargoes.

**5.2. Operational Precautions In Heavy Weather**

- 5.2.1. All doorways and other openings, through which water can enter into the hull or deckhouses, forecastle, etc., should be suitably closed in adverse weather conditions and accordingly all appliances for this purpose should be maintained on board and in good condition.
- 5.2.2. Weather tight and watertight hatches, doors, etc., should be kept closed during navigation, except when necessarily opened for the working of the ship and should always be ready for immediate closure and be clearly marked to indicate that these fittings are to be kept closed except for access. Hatch covers and flush deck scuttles in fishing vessels should be kept properly secured when not in use during fishing operations. All portable deadlights should be maintained in good condition and securely closed in bad weather.
- 5.2.3. Any closing devices provided for vent pipes to fuel tanks should be secured in bad weather.

- 5.2.4. Fish should never be carried in bulk without first being sure that the portable divisions in the holds are properly installed.

### 5.3. Ship Handling in Heavy Weather

- 5.3.1. In all conditions of loading necessary care should be taken to maintain a seaworthy freeboard.
- 5.3.2. In severe weather, the speed of the ship should be reduced if propeller emergence, shipping of water on deck or heavy slamming occurs.
- 5.3.3. Special attention should be paid when a ship is sailing in following, quartering or head seas because dangerous phenomena such as parametric resonance, broaching to, reduction of stability on the wave crest, and excessive rolling may occur singularly, in sequence or simultaneously in a multiple combination, creating a threat of capsizing. A ship's speed and / or course should be altered appropriately to avoid the above-mentioned phenomena.
- 5.3.4. Reliance on automatic steering may be dangerous as this prevents ready changes to course which may be needed in bad weather.
- 5.3.5. Water trapping in deck wells should be avoided. If freeing ports are not sufficient for the drainage of the well, the speed of the ship should be reduced or the course changed, or both. Freeing ports provided with closing appliances should always be capable of functioning and are not to be locked.
- 5.3.6. Masters should be aware that steep or breaking waves may occur in certain areas, or in certain wind and current combinations (river estuaries, shallow water areas, funnel shaped bays, etc.). These waves are particularly dangerous, especially for small ships.
- 5.3.7. In severe weather, the lateral wind pressure may cause a considerable angle of heel. If anti-heeling measures (e.g., ballasting, use of anti-heeling devices, etc.) are used to compensate for heeling due to wind, changes of the ship's course relative to the wind direction may lead to dangerous angles of heel or capsizing. Therefore, heeling caused by the wind should not be compensated with anti-heeling measures, unless, subject to the approval by the Administration, the vessel has been proven by calculation to have sufficient stability in worst case conditions (i.e. improper or incorrect use, mechanism failure, unintended course change, etc.). Guidance on the use of anti-heeling measures should be provided in the stability booklet.
- 5.3.8. Use of operational guidelines for avoiding dangerous situations in severe weather conditions or an on-board computer based system is recommended. The method should be simple to use.
- 5.3.9. High-speed craft should not be intentionally operated outside the worst intended conditions and limitations specified in the relevant certificates, or in documents referred to therein.

---

## SECTION 6 ICING CONSIDERATIONS

### Contents

6.1. General .....	67
6.2. Cargo Ships Carrying Timber Deck Cargoes .....	67
6.3. Fishing Vessels .....	67
6.4. Offshore Supply Vessels 24 M To 100 M In Length .....	69

**6.1. General**

- 6.1.1. For any ship operating in areas where ice accretion is likely to occur, adversely affecting a ship's stability, icing allowances should be included in the analysis of conditions of loading.
- 6.1.2. Administrations are advised to take icing into account and are permitted to apply national standards where environmental conditions are considered to warrant a higher standard than those recommended in the following sections.

**6.2. Cargo Ships Carrying Timber Deck Cargoes**

- 6.2.1. The master should establish or verify the stability of his ship for the worst service condition, having regard to the increased weight of deck cargo due to water absorption and/or ice accretion and to variations in consumables.
- 6.2.2. When timber deck cargoes are carried and it is anticipated that some formation of ice will take place, an allowance should be made in the arrival condition for the additional weight.

**6.3. Fishing Vessels****6.3.1. General**

The calculations of loading conditions for fishing vessels (refer to Chapter 3 Section 3, 3.4.2.8) should, where appropriate, include allowance for ice accretion, in accordance with the following provisions.

**6.3.2. Allowance for ice accretion**

6.3.2.1. For vessels operating in areas where ice accretion is likely to occur, the following icing allowance should be made in the stability calculations:

- a. 30 kg per square meter on exposed weather decks and gangways;
- b. 7.5 kg per square meter for projected lateral area of each side of the vessel above the water plane;
- c. The projected lateral area of discontinuous surfaces of rail, sundry booms, spars (except masts) and rigging of vessels having no sails and the projected lateral area of other small objects should be computed by increasing the total projected area of continuous surfaces by 5% and the static moments of this area by 10%.

Vessels intended for operation in areas where ice is known to occur should be:

- d. Designed to minimize the accretion of ice; and
- e. Equipped with such means for removing ice as the Administration may require; for example, electrical and pneumatic devices, and/or special tools such as axes or wooden clubs for removing ice from bulwarks, rails and erections.

**6.3.3. Guidance relating to ice accretion**

6.3.3.1. In the application of the above standards, the following icing areas should apply:

- a. The area north of latitude 65° 30' N, between longitude 28° W and the west coast of Iceland; north of the north coast of Iceland; north of the rhumb line running from latitude 66° N, longitude 15° W to latitude 73° 30' N, longitude 15° E, north of latitude 73° 30' N between longitude 15° E and 35° E, and east of longitude 35° E, as well as north of latitude 56° N in the Baltic Sea;

- b. The area north of latitude 43° N bounded in the west by the North American coast and the east by the rhumb line running from latitude 43° N, longitude 48° W to latitude 63° N, longitude 28° W and thence along longitude 28° W;
- c. All sea areas north of the North American Continent, west of the areas defined in 6.3.3.1a and 6.3.3.1b;
- d. The Bering and Okhotsk Seas and the Tartary Strait during the icing season; and
- e. South of latitude 60° S.

A chart to illustrate the areas is attached at the end of this chapter.

For vessels operating in areas where ice accretion may be expected:

- f. Within the areas defined in 6.3.3.1.a, 6.3.3.1.c, 6.3.3.1.d and 6.3.3.1.e known to having icing conditions significantly different from those described in 3.3.1, ice accretion requirements of one half to twice the required allowance may be applied; and
- g. Within the area defined in 6.3.3.1.b, where ice accretion in excess of twice the allowance required by 6.3.2 may be expected, more severe requirements than those given in 6.3.2 may be applied.

6.3.4. Brief survey of the causes of ice formation and its influence upon the seaworthiness of the vessel

6.3.4.1. The skipper of a fishing vessel should bear in mind that ice formation is a complicated process which depends upon meteorological conditions, condition of loading and behavior of the vessel in stormy weather as well as on the size and location of superstructures and rigging. The most common cause of ice formation is the deposit of water droplets on the vessel's structure. These droplets come from spray driven from wave crests and from ship-generated spray.

6.3.4.2. Ice formation may also occur in conditions of snowfall, sea fog (including arctic sea smoke), a drastic fall in ambient temperature, as well as from the freezing of drops of rain on impact with the vessel's structure.

6.3.4.3. Ice formation may sometimes be caused or accentuated by water shipped on board and retained on deck.

6.3.4.4. Intensive ice formation generally occurs on stem, bulwark and bulwark rail, front walls of superstructures and deck-houses, hawse holes, anchors, deck gear, forecastle deck and upper deck, freeing ports, aerials, stays, shrouds, masts and spars.

6.3.4.5. It should be borne in mind that the most dangerous areas as far as ice formation is concerned are the sub-Arctic regions.

6.3.4.6. The most intensive ice formation takes place when wind and sea come from ahead. In beam and quartering winds, ice accumulates quicker on the windward side of the vessel, thus leading to a constant list which is extremely dangerous.

6.3.4.7. Listed below are meteorological conditions causing the most common type of ice formation due to spraying of a vessel. Examples of the weight of ice formation on a typical fishing vessel of displacement in the range 100 t to 500 t are also given. For larger vessels the weight will be correspondingly greater.

6.3.4.8. Slow accumulations of ice take place:

- a. At ambient temperature from  $-1^{\circ}\text{C}$  to  $-3^{\circ}\text{C}$  and any wind force;
- b. At ambient temperature  $-4^{\circ}\text{C}$  and lower and wind force from 0 m/s to 9 m/s; and
- c. Under the conditions of precipitation, fog or sea mist followed by a drastic fall of the ambient temperature.

Under all these conditions the intensity of ice accumulation may not exceed 1.5 t/h.

6.3.4.9. At ambient temperature of  $-4^{\circ}\text{C}$  to  $-8^{\circ}\text{C}$  and wind force 10 m/s to 15 m/s, rapid accumulation of ice takes place. Under these conditions the intensity of ice accumulation can lie within the range 1.5 t/h to 4 t/h.

6.3.4.10. Very fast accumulation of ice takes place:

- a. At ambient temperature of  $-4^{\circ}\text{C}$  and lower and wind forces of 16 m/s and over; and
- b. At ambient temperature  $-9^{\circ}\text{C}$  and lower and wind force 10 m/s to 15 m/s.

Under these conditions, the intensity of ice accumulation can exceed 4 t/h.

6.3.4.11. The skipper should bear in mind that ice formation adversely affects the seaworthiness of the vessel as ice formation leads to:


- a. An increase in the weight of the vessel due to accumulation of ice on the vessel's surfaces which causes the reduction of freeboard and buoyancy;
- b. A rise of the vessel's center of gravity due to the high location of ice on the vessel's structures with corresponding reduction in the level of stability;
- c. An increase of windage area due to ice formation on the upper parts of the vessel and hence an increase in the heeling moment due to the action of the wind;
- d. A change of trim due to uneven distribution of ice along the vessel's length;
- e. The development of a constant list due to uneven distribution of ice across the breadth of the vessel; and
- f. Impairment of the maneuverability and reduction of the speed of the vessel.

6.3.5. Operational procedures related to ensuring a fishing vessel's endurance in conditions of ice formation are given in Annex 2 (Recommendations for skippers of fishing vessels on ensuring a vessel's endurance in conditions of ice formation).

#### 6.4. Offshore Supply Vessels 24 m to 100 m in Length

For vessels operating in areas where ice accretion is likely to occur:

- a. No shutters should be fitted in the freeing ports; and
- b. With regard to operational precautions against capsizing, reference is made to the recommendations for skippers of fishing vessels on ensuring a vessel's endurance in conditions of ice formation, as given in paragraph 6.3.4 above and in Annex 2 (Recommendations for skippers of fishing vessels on ensuring a vessel's endurance in conditions of ice formation).



---

## SECTION 7 CONSIDERATIONS FOR WATERTIGHT AND WEATHERTIGHT INTEGRITY

### Contents

7.1. Hatchways .....	72
7.2. Machinery Space Openings .....	73
7.3. Doors .....	73
7.4. Cargo Ports And Other Similar Openings .....	74
7.5. Sidescuttles, Window Scuppers, Inlets And Discharges.....	74
7.6. Other Deck Openings .....	76
7.7. Ventilators, Air Pipes And Sounding Devices .....	76
7.8. Freeing Ports .....	77
7.9. Miscellaneous .....	78

**7.1. Hatchways**

- 7.1.1. All hatchways should be provided with covers and those which may be opened during Cargo and other hatchways in ships to which the International Convention on Load Lines, 1966, applies should comply with regulations 13, 14, 15, 16 and 26(5) of this Convention.
- 7.1.2. Hatchways in fishing vessels to which the 1993 Torremolinos Protocol applies should comply with regulations II/5 and II/6 of this Protocol.
- 7.1.3. In decked fishing vessels of 12 m in length and over but less than 24 m in length hatchways should comply with the following:
- 7.1.4. Fishing operations should normally be arranged near to the vessel's centerline.
- 7.1.4.1. For the purpose of strength calculations, it should be assumed that hatchway covers other than wood are subject to static load of 10 kN/m<sup>2</sup> or the weight of cargo intended to be carried on them, whichever is the greater.
- 7.1.4.2. Where covers are constructed of mild steel, the maximum stress according to 7.1.3.2 multiplied by 4.25 should not exceed the minimum ultimate strength of the material. Under these loads the deflections should not be more than 0.0028 times the span.
- 7.1.4.3. Covers made of materials other than mild steel or wood should be at least of equivalent strength to those made of mild steel and their construction should be of sufficient stiffness to ensure weather tightness under the loads specified in 7.1.3.2.
- 7.1.4.4. Covers should be fitted with clamping devices and gaskets or other equivalent arrangements sufficient to ensure weather tightness.
- 7.1.4.5. The use of wooden hatchway covers is generally not recommended in view of the difficulty of rapidly securing their weather tightness. However, where fitted they should be capable of being secured weather tight.
- 7.1.4.6. The finished thickness of wood hatchway covers should include an allowance for abrasion due to rough handling. In any case, the finished thickness of these covers should be at least 4 mm for each 100 mm of unsupported span subject to a minimum of 40 mm and the width of their bearing surfaces should be at least 65 mm.
- 7.1.4.7. The height above deck of hatchway coamings on exposed parts of the working deck should be at least 300 mm for vessels of 12 m in length and at least 600 mm for vessels of 24 m in length. For vessels of intermediate length, the minimum height should be obtained by linear interpolation. The height above deck of hatchway coamings on exposed parts of the superstructure deck should be at least 300 mm.
- 7.1.4.8. Where operating experience has shown justification and on approval of the competent authority the height of hatchway coamings, except those which give direct access to machinery spaces may be reduced from the height as specified in 7.1.3.8 or the coamings may be omitted entirely, provided that efficient watertight hatch covers other than wood are fitted. Such hatchways should be kept as small as practicable and the covers should be permanently attached by hinges or equivalent means and be capable of being rapidly closed or battened down.

**7.2. Machinery Space Openings**

- 7.2.1. In ships to which the International Convention on Load Lines, 1966 or the Protocol of 1988 relating thereto as amended, as applicable, applies, machinery space openings should comply with regulation 17.
- 7.2.2. In fishing vessels to which the 1993 Torremolinos Protocol applies and in new decked fishing vessels of 12 m in length and over, but less than 24 m in length, the following requirements of regulation II/7 of this Protocol should be met:
- a. Machinery space openings should be framed and enclosed by casings of a strength equivalent to the adjacent superstructure. External access openings therein should be fitted with doors complying with the requirements of regulation II/4 of the Protocol or, in vessels less than 24 m in length, with hatch covers other than wood complying with the requirements of 1.1.3 of Section 1 this chapter; and
  - b. Openings other than access openings should be fitted with covers of equivalent strength to the un-pierced structure, permanently attached thereto and capable of being closed weather tight.
- 7.2.3. In offshore supply vessels, access to the machinery space should, if possible, be arranged within the forecastle. Any access to the machinery space from the exposed cargo deck should be provided with two weather tight closures. Access to spaces below the exposed cargo deck should preferably be from a position within or above the superstructure deck.

**7.3. Doors**

- 7.3.1. In passenger ships to which the International Convention for the Safety of Life at Sea, 1974, applies, doors should comply with regulations II-I/13 and 16 of this Convention.
- 7.3.2. In ships to which the International Convention on Load Lines, 1966 or the Protocol of 1988 relating thereto, as amended, as applicable, applies, doors should comply with regulation 12 of this Convention.
- 7.3.3. In fishing vessels to which the 1993 Torremolinos Protocol applies, doors should comply with regulation II/2 and regulation II/4 of this Protocol.
- 7.3.4. In decked fishing vessels of 12 m in length and over but less than 24 m in length:
- a. Watertight doors may be of the hinged type and should be capable of being operated locally from each side of the door. A notice should be attached to the door on each side stating that the door should be kept closed at sea.
  - b. All access openings in bulkheads of enclosed deck erections, through which water could enter and endanger the vessel, should be fitted with doors permanently attached to the bulkhead, framed and stiffened so that the whole structure is of equivalent strength to the un-pierced structure, and weather tight when closed, and means should be provided so that they can be operated from each side of the bulkhead.
  - c. The height above deck of sills in those doorways, companionways, deck erections and machinery casings situated on the working deck and on superstructure decks which give direct access to parts of that deck exposed to the weather and sea should be at least equal to the height of hatchway coamings as specified in 7.1.3.8 of section 1 of this chapter
  - d. Where operating experience has shown justification and on approval of the competent authority, the height above deck of sills in the doorways specified in 7.3.4.c except those giving direct access to machinery spaces, may be reduced to not less than 150 mm on superstructure decks and not less than 380 mm on the working deck for vessels 24 m in length, or not less than 150 mm on the working deck for vessels of 12

m in length. For vessels of intermediate length, the minimum acceptable reduced height for sills in doorways on the working deck should be obtained by linear interpolation.

#### 7.4. Cargo Ports and Other Similar Openings

- 7.4.1. Cargo ports and other similar openings in ships to which the International Convention on Load Lines, 1966 or the Protocol of 1988 relating thereto, as amended, as applicable, applies should comply with regulation 21 of this Convention.
- 7.4.2. Openings through which water can enter the vessel and fish flaps on stern trawlers in fishing vessels to which the 1993 Torremolinos Protocol applies should comply with regulation II/3 of this Protocol.
- 7.4.3. Cargo port and other similar openings in passenger ships to which the International Convention for the Safety of Life at Sea, 1974 applies should comply with regulations II-1/15, 17 and 22 of this Convention. In addition, such openings in Ro-Ro passenger ships to which this Convention applies, should comply with regulation II-1/17-1 of this Convention.
- 7.4.4. Cargo port and other similar openings in cargo ships to which the International Convention for the Safety of Life at Sea, 1974 applies should comply with regulation II-1/15-1 of this Convention.

#### 7.5. Side scuttles, Window Scuppers, Inlets and Discharges

- 7.5.1. In passenger ships to which the International Convention for the Safety of Life at Sea, 1974 applies, openings in shell plating below the bulkhead deck should comply with regulation II-1/15 of this Convention.  
Watertight integrity above the bulkhead deck should comply with regulation II-1/17 of this Convention.  
In addition, in Ro-Ro passenger ships, watertight integrity below the bulkhead deck should comply with regulation II-1/23 and integrity of the hull and superstructure should comply with regulation II-1/17-1 of this Convention.
- 7.5.2. In ships to which the International Convention on Load Lines, 1966 or the Protocol of 1988 relating thereto, as amended, as applicable, applies, scuppers, inlets and discharges should comply with regulation 22 and side scuttles should comply with regulation 23 of this Convention.
- 7.5.3. In fishing vessels to which the 1993 Torremolinos Protocol applies, side scuttles and windows should comply with regulation II/12 and inlets and discharges should comply with regulation II/13 of this Protocol.
- 7.5.4. In decked fishing vessels of 12 m in length and over but less than 24 m in length, side scuttles, windows and other openings and inlets and discharges should comply with the following:
  - 7.5.4.1. Side scuttles to spaces below the working deck and to enclosed spaces on the working deck should be fitted with hinged deadlights capable of being closed watertight;
  - 7.5.4.2. Sidescuttles should be fitted in a position such that their sills are above a line drawn parallel to the working deck at side having its lowest point 500 mm above the deepest operating waterline;
  - 7.5.4.3. Sidescuttles, together with their glasses and deadlights, should be of substantial construction to the satisfaction of the competent authority;

- 7.5.4.4. Skylights leading to spaces below the working deck should be of substantial construction and capable of being closed and secured weather tight, and with provision for adequate means of closing in the event of damage to the inserts. Skylights leading to machinery spaces should be avoided as far as practicable;
- 7.5.4.5. Toughened safety glass or suitable permanently transparent material of equivalent strength should be fitted in all wheelhouse windows exposed to the weather. The means of securing windows and the width of the bearing surfaces should be adequate, having regard to the window material used. Openings leading to spaces below deck from a wheelhouse whose windows are not provided with the protection required by 0 should be fitted with a weather tight closing appliance;
- 7.5.4.6. Deadlights or a suitable number of storm shutters should be provided where there is no other method of preventing water from entering the hull through a broken window or side scuttle;
- 7.5.4.7. The competent authority may accept side scuttles and windows without deadlights in side or aft bulkheads of deck erections located on or above the working deck if satisfied that the safety of the vessel will not be impaired;
- 7.5.4.8. The number of openings in the sides of the vessel below the working deck should be the minimum compatible with the design and proper working of the vessel and such openings should be provided with closing arrangements of adequate strength to ensure water tightness and the structural integrity of the surrounding structure;
- 7.5.4.9. Discharges led through the shell either from spaces below the working deck or from spaces within deck erections should be fitted with efficient and accessible means for preventing water from passing inboard. Normally, each separate discharge should have an automatic non-return valve with a positive means of closing it from a readily accessible position. Such a valve is not required if the competent authority considers that the entry of water into the vessel through the opening is not likely to lead to dangerous flooding and that the thickness of the pipe is sufficient. The means for operating the valve with a positive means of closing should be provided with an indicator showing whether the valve is open or closed. The open inboard end of any discharge system should be above the deepest operating waterline at an angle of heel satisfactory to the competent authority;
- 7.5.4.10. In machinery spaces main and auxiliary sea inlets and discharges essential for the operation of machinery should be controlled locally. Controls should be readily accessible and should be provided with indicators showing whether the valves are open or closed. Suitable warning devices should be incorporated to indicate leakage of water into the space; and
- 7.5.4.11. Fittings attached to the shell and all valves should be of steel, bronze or other ductile material. All pipes between the shell and valves should be of steel, except that in vessels constructed of material other than steel, other suitable materials may be used.
- 7.5.5. In cargo ships to which the International Convention for the Safety of Life at Sea, 1974 applies, external openings should comply with regulation II-1/15-1 of this Convention.

**7.6. Other Deck Openings**

- 7.6.1. Miscellaneous openings in freeboard and superstructure decks in ships to which the International Convention on Load Lines, 1966 or the Protocol of 1988 relating thereto, as amended, as applicable, applies should comply with regulation 18 of this Convention.
- 7.6.2. In decked fishing vessels of 12 m and over where it is essential for fishing operations, flush deck scuttles of the screw, bayonet or equivalent type and manholes may be fitted provided these are capable of being closed watertight and such devices should be permanently attached to the adjacent structure. Having regard to the size and disposition of the openings and the design of the closing devices, metal-to-metal closures may be fitted if they are effectively watertight. Openings other than hatchways, machinery space openings, manholes and flush scuttles in the working or superstructure deck should be protected by enclosed structures fitted with weather tight doors or their equivalent. Companionways should be situated as close as practicable to the centerline of the vessel.

**7.7. Ventilators, Air Pipes And Sounding Devices**

- 7.7.1. Ventilators in ships to which the International Convention on Load Lines, 1966 or the Protocol of 1988 relating thereto, as amended, as applicable, applies should comply with regulation 19 and air pipes should comply with regulation 20 of this Convention.
- 7.7.2. Ventilators in fishing vessels to which the 1993 Torremolinos Protocol applies should comply with regulation II/9 and air pipes should comply with regulation II/10 of this Protocol. Sounding devices should comply with regulation II/11 of this Protocol.
- 7.7.3. Ventilators and air pipes in fishing vessels of 12 m in length and over but less than 24 m in length should comply with the following:
- 7.7.3.1. Ventilators should have coamings of substantial construction and should be capable of being closed weather tight by devices permanently attached to the ventilator or adjacent structure. Ventilators should be arranged as close to the vessel's centerline as possible and, where practicable, should extend through the top of a deck erection or companionway;
- 7.7.3.2. The coamings of ventilators should be as high as practicable. On the working deck the height above deck of coamings of ventilators, other than machinery space ventilators should be not less than 760 mm and on superstructure decks not less than 450 mm. When the height of such ventilators may interfere with the working of the vessel their coaming heights may be reduced to the satisfaction of the competent authority. The height above deck of machinery space ventilator openings should be to the satisfaction of the competent authority;
- 7.7.3.3. Closing appliances need not be fitted to ventilators the coamings of which extend more than 2.5 m above the working deck or more than 1.0 m above a deck-house top or superstructure deck;
- 7.7.3.4. Where air pipes to tanks or other spaces below deck extend above the working or superstructure decks the exposed parts of the pipes should be of substantial construction and, as far as is practicable, located close to the vessel's centerline and protected from damage by fishing or lifting gear. Openings of such pipes should be protected by efficient means of closing, permanently attached to the pipe or adjacent structure, except that where the competent authority is satisfied that they are protected against water trapped on deck, these means of closing may be omitted; and

7.7.3.5. Where air pipes are situated near the side of the vessel their height above deck to the point where water may have access below should be at least 760 mm on the working deck and at least 450 mm on the superstructure deck. The competent authority may accept reduction of the height of an air pipe to avoid interference with the fishing operations.

7.7.4. In offshore supply vessels air pipes and ventilators should comply with the following:

7.7.4.1. Air pipes and ventilators should be fitted in protected positions in order to avoid damage by cargo during operations and to minimize the possibility of flooding. Air pipes on the exposed cargo and forecastle decks should be fitted with automatic closing devices; and

7.7.4.2. Due regard should be given to the position of machinery space ventilators. Preferably they should be fitted in a position above the superstructure deck, or above an equivalent level if no superstructure deck is fitted.

## 7.8. Freeing Ports

7.8.1. Where bulwarks on the weather portion of the freeboard or superstructure decks or, in fishing vessels, the working decks form wells, freeing ports should be arranged along the length of the bulwark as to ensure that the deck is freed of water most rapidly and effectively. Lower edges of freeing ports should be as near the deck as practicable.

7.8.2. In ships to which the International Convention on Load Lines, 1966 or the Protocol of 1988 relating thereto as amended, as applicable, applies, freeing ports should comply with regulation 24 of this Convention.

7.8.3. In decked fishing vessels of 12 m in length and over, freeing ports should comply with the following:

7.8.3.1. The minimum freeing port area  $A_{fp}$  in  $m^2$  on each side of the vessel for each well on the working deck, should be determined in relation to the length  $l$  and height of bulwark in the well as follows:

a.  $A_{fp} = K * l$

where:

$K = 0.07$  for vessels of 24 m in length and over;

$K = 0.035$  for vessels of 12 m in length;

For intermediate lengths the value of  $K$  should be obtained by linear interpolation (' $l$ ' need not be taken as greater than 70% of the vessel length);

b. Where the bulwark is more than 1.2 m in average height, the required area should be increased by 0.004  $m^2$  per meter of length of well for each 0.1 m difference in height; and

c. Where the bulwark is less than 0.9 m in average height, the required area may be decreased by 0.004  $m^2$  per meter of length of well for each 0.1 m difference in height.

7.8.3.2. The freeing port area calculated according to 7.8.3.1 should be increased where the Administration or competent authority considers that the vessel's sheer is not sufficient to ensure rapid and effective freeing of the deck of water.

7.8.3.3. Subject to the approval of the Administration or competent authority, the minimum freeing port area for each well on the superstructure deck should be not less than one-half the area  $A_{fp}$  given in 7.8.3.1 except that where the superstructure deck forms

a working deck for fishing operations the minimum area on each side should be not less than 75% of the area  $A_{fp}$ .

- 7.8.3.4. Freeing ports should be so arranged along the length of bulwarks as to provide the most rapid and effective freeing of the deck from water. Lower edges of freeing ports should be as near the deck as practicable.
- 7.8.3.5. Pound boards and means for stowage and working the fishing gear should be arranged so that the effectiveness of the freeing ports will not be impaired or water trapped on deck and prevented from easily reaching the freeing ports. Pound boards should be so constructed that they can be locked in position when in use and will not hamper the discharge of shipped water.
- 7.8.3.6. Freeing ports over 0.3 m in depth should be fitted with bars spaced not more than 0.23 m nor less than 0.15 m apart or provided with other suitable protective arrangements. Freeing port covers, if fitted, should be of approved construction. If devices are considered necessary for locking freeing port covers during fishing operations they should be to the satisfaction of the competent authority and easily operable from a readily accessible position.
- 7.8.3.7. In vessels intended to operate in areas subject to icing, covers and protective arrangements for freeing ports should be capable of being easily removed to restrict ice accumulation. Size of opening and means provided for removal of these protective arrangements should be to the satisfaction of the competent authority.
- 7.8.3.8. In addition, in fishing vessels of 12 m in length and above but less than 24 m in length where wells or cockpits are fitted in the working deck or superstructure deck with their bottoms above the deepest operating waterline, efficient non-return means of drainage overboard should be provided. Where bottoms of such wells or cockpits are below the deepest operating waterline, drainage to the bilges should be provided.
- 7.8.4. In offshore supply vessels, the Administration should give special attention to adequate drainage of pipe stowage positions, having regard to the individual characteristics of the vessel. However, the area provided for drainage of the pipe stowage positions should be in excess of the required freeing port area in the cargo deck bulwark and should not be fitted with shutters.

## 7.9. Miscellaneous

Ships engaged in towing operations should be provided with means for quick release of the towing hawser.

---

## SECTION 8 DETERMINATION OF LIGHTSHIP PARAMETERS

### Contents

8.1. Application .....	80
8.2. Preparations For The Inclining Test .....	80
8.3. Plans Required .....	83
8.4. Test Procedure .....	83
8.5. Inclining Test for MODUs .....	84
8.6. Stability Test for Pontoons .....	84

**8.1. Application**

8.1.1. Every passenger ship regardless of size and every cargo ship having a length, as defined in the International Convention on Load Lines, 1966 or the Protocol of 1988 relating thereto, as amended, as applicable, of 24 m and upwards, should be inclined upon its completion and the elements of its stability determined.

8.1.2. The Administration may allow the inclining test of an individual ship as required by 8.1.1 to be dispensed with provided basic stability data are available from the inclining test of a sister ship and it is shown to the satisfaction of the Administration that reliable stability information for the exempted ship can be obtained from such basic data

To be dispensed from an inclining test, the deviation of lightship mass is not to exceed:

For  $L < 50\text{m}$ : 2% of the lightship mass of the lead ship or as given in the information on stability;

For  $L > 160\text{ m}$ : 1% of the lightship mass of the lead ship or as given in the information on stability;

For intermediate L: by linear interpolation,

and the deviation of the lightship's longitudinal center of gravity (LCG) referred to L should not be greater than 0.5% of the lightship's LCG of the lead ship or as given in the information on stability regardless of the ship's length.

8.1.3. The Administration may allow the inclining test of an individual ship or class of ships especially designed for the carriage of liquids or ore in bulk to be dispensed with when reference to existing data for similar ships clearly indicates that due to the ship's proportions and arrangements more than sufficient metacentric height will be available in all probable loading conditions.

8.1.4. Where any alterations are made to a ship so as to materially affect the stability, the ship should be re-inclined.

8.1.5. At periodic intervals not exceeding five years, a lightweight survey should be carried out on all passenger ships to verify any changes in lightship displacement and longitudinal center of gravity. The ship should be re-inclined whenever, in comparison with the approved stability information, a deviation from the lightship displacement exceeding 2% or a deviation of the longitudinal center of gravity exceeding 1% of L is found, or anticipated.

8.1.6. The inclining test prescribed is adaptable for ships with a length below 24 m if special precautions are taken to ensure the accuracy of the test procedure.

**8.2. Preparations for the Inclining Test****8.2.1. Notification of the Administration**

Written notification of the inclining test should be sent to the Administration as it requires or in due time before the test. An Administration representative should be present to witness the inclining test and the test results be submitted for review.

The responsibility for making preparations, conducting the inclining test and lightweight survey, recording the data, and calculating the results rests with the shipyard, owner or naval

architect. While compliance with the procedures outlined herein will facilitate an expeditious and accurate inclining test, it is recognized that alternative procedures or - arrangements may be equally efficient. However, to minimize risk of delay, it is recommended that all such variances be submitted to the Administration for review prior to the inclining test.

#### 8.2.1.1. Details of notification

Written notification should provide the following information as the Administration may require:

- a. Identification of the ship by name and shipyard hull number, if applicable;
- b. Date, time, and location of the test;
- c. Inclining weight data:
  - i. Type;
  - ii. Amount (number of units and weight of each);
  - iii. Certification;
  - iv. Method of handling (i.e. sliding rail or crane);
  - v. Anticipated maximum angle of heel to each side;
- d. Measuring devices:
  - i. Pendulums approximate location and length;
  - ii. U-tubes approximate location and length;
  - iii. Inclinometers location and details of approvals and calibrations;
- e. Approximate trim;
- f. Condition of tanks;
- g. Estimated weights to deduct, to complete, and to relocate in order to place the ship in its true lightship condition;
- h. Detailed description of any computer software to be used to aid in calculations during the inclining test; and
- i. Name and telephone number of the person responsible for conducting the inclining test.

#### 8.2.2. General condition of the ship

8.2.2.1. A ship should be as complete as possible at the time of the inclining test. The test should be scheduled to minimize the disruption in the ship's delivery date or its operational commitments.

8.2.2.2. The amount and type of work left to be completed (mass to be added) affect the accuracy of the lightship characteristics, so good judgment should be used. If the mass or center of gravity of an item to be added cannot be determined with confidence, it is best to conduct the inclining test after the item is added.

8.2.2.3. Temporary material, tool boxes, staging, sand, debris, etc., on board should be reduced to absolute minimum before the inclining test. Excess crew or personnel not directly involved in the inclining test should be removed from on board the ship before the test.

8.2.2.4. Decks should be free of water. Water trapped on deck may shift and pocket in a fashion similar to liquids in a tank. Any rain, snow or ice accumulated on the ship should be removed prior to the test.

8.2.2.5. The anticipated liquid loading for the test should be included in the planning for the test. Preferably, all tanks should be empty and clean, or completely full. The number

of slack tanks should be kept to an absolute minimum. The viscosity of the fluid, the depth of the fluid and the shape of the tank should be such that the free surface effect can be accurately determined.

- 8.2.2.6. The ship should be moored in a quiet, sheltered area free from extraneous forces such as propeller wash from passing vessels, or sudden discharges from shore side pumps. The tide conditions and the trim of the ship during the test should be considered. Prior to the test, the depth of water should be measured and recorded in as many locations as are necessary to ensure that the ship will not contact the bottom. The specific gravity of water should be accurately recorded. The ship should be moored in a manner to allow unrestricted heeling. The access ramps should be removed. Power lines, hoses, etc., connected to shore should be at a minimum, and kept slack at all times.
- 8.2.2.7. The ship should be as upright as possible; with inclining weights in the initial position, up to one-half degree of list is acceptable. The actual trim and deflection of keel, if practical, should be considered in the hydrostatic data. In order to avoid excessive errors caused by significant changes in the water plane area during heeling, hydrostatic data for the actual trim and the maximum anticipated heeling angles should be checked beforehand.
- 8.2.2.8. The total weight used should be sufficient to provide a minimum inclination of one (1) degree and a maximum of four(4) degrees of heel to each side. The Administration may, however, accept a smaller inclination angle for large ships provided that the requirements on pendulum deflection or U-tube difference in height in 8.2.2.9 are complied with. Test weights should be compact and of such a configuration that the vertical center of gravity of the weights can be accurately determined. Each weight should be marked with an identification number and its mass. Re-certification of the test weights should be carried out prior to the incline. A crane of sufficient capacity and reach, or some other means, should be available during the inclining test to shift weights on the decking in an expeditious and safe manner. Water ballast transfer may be carried out, when it is impractical to incline using solid weights if acceptable to the Administration.
- 8.2.2.9. The use of three pendulums is recommended but a minimum of two should be used to allow identification of bad readings at any one pendulum station. They should each be located in an area protected from the wind. One or more pendulums may be substituted by other measuring devices (U-tubes or inclinometers) at the discretion of the Administration. Alternative measuring devices should not be used to reduce the minimum inclining angles recommended in 8.2.2.8.
- The use of an inclinometer or U-tube should be considered in each separate case. It is recommended that inclinometers or other measuring devices only be used in conjunction with at least one pendulum.
- 8.2.2.10. Efficient two-way communications should be provided between central control and the weight handlers and between central control and each pendulum station. One person at a central control station should have complete control over all personnel involved in the test.

**8.3. Plans Required**

The person in charge of the inclining test should have available a copy of the following plans at the time of the inclining test:

- a. Lines plan;
- b. Hydrostatic curves or hydrostatic data;
- c. General arrangement plan of decks, holds, inner bottoms, etc.;
- d. Capacity plan showing capacities and vertical and longitudinal centers of gravity of cargo spaces, tanks, etc. When ballast water is used as inclining weight, the transverse and vertical centers of gravity for the applicable tanks for each angle of inclination, must be available;
- e. Tank sounding tables;
- f. Draught mark locations; and
- g. Docking drawing with keel profile and draught mark corrections (if available).

**8.4. Test Procedure**

8.4.1. Procedures followed in conducting the inclining test and lightweight survey should be in accordance with the recommendations laid out in annex 1 (Detailed guidance for the conduct of an inclining test) to this Code.

8.4.1.1. Freeboard/draught readings should be taken to establish the position of the waterline in order to determine the displacement of the ship at the time of the inclining test. It is recommended that at least five freeboard readings, approximately equally spaced, be taken on each side of the ship or that all draught marks (forward, midship and aft) be read on each side of the ship. Draught/ freeboard readings should be read immediately before or immediately after the inclining test.

8.4.1.2. The standard test employs eight distinct weight movements. Movement No.8, a recheck of the zero point, may be omitted if a straight line plot is achieved after movement No.7. If a straight line plot is achieved after the initial zero and six weight movements, the inclining test is complete and the second check at zero may be omitted. If a straight line plot is not achieved, those weight movements that did not yield acceptable plotted points should be repeated or explained.

8.4.2. A copy of the inclining data should be forwarded to the Administration along with the calculated results of the inclining test in an acceptable report format, if required.

8.4.3. All calculations performed during the inclining test and in preparation of an inclining test report may be carried out by a suitable computer program. Output generated by such a program may be used for presentation of all or partial data and calculations included in the test report if it is clear, concise, well documented, and generally consistent in form and content with Administration requirements.

**8.5. Inclining Test for MODUs**

- 8.5.1. An inclining test should be required for the first unit of a design, when as near to completion as possible, to determine accurately the lightship data (weight and position of center of gravity).
- 8.5.2. For successive units which are identical by design, the lightship data of the first unit of the series may be accepted by the Administration in lieu of an inclining test, provided the difference in lightship displacement or position of center of gravity due to weight changes for minor differences in machinery, outfitting or equipment, confirmed by the results of a deadweight survey, are less than 1% of the values of the lightship displacement and principal horizontal dimensions as determined for the first of the series. Extra care should be given to the detailed weight calculation and comparison with the original unit of a series of column-stabilized, semi-submersible types as these, even though identical by design, are recognized as being unlikely to attain an acceptable similarity of weight or center of gravity to warrant a waiver of the inclining test.
- 8.5.3. The results of the inclining test, or deadweight survey and inclining experiment adjusted for weight differences, should be indicated in the Operating Manual.
- 8.5.4. A record of all changes to machinery, structure, outfit and equipment that affect the lightship data should be maintained in the Operating Manual or a lightship data alterations log and be taken into account in daily operations.
- 8.5.5. For column-stabilized units, a deadweight survey should be conducted at intervals not exceeding five years. Where the deadweight survey indicates a change from the calculated lightship displacement in excess of 1% of the operating displacement, an inclining test should be conducted.
- 8.5.6. An inclining test or a deadweight survey should be carried out in the presence of an officer of the Administration, or a duly authorized person or representative of an approved organization.

**8.6. Stability Test for Pontoons**

An inclining experiment is not normally required for a pontoon, provided a conservative value of the lightship vertical center of gravity (KG) is assumed for the stability calculations. The KG can be assumed at the level of the main deck although it is recognized that a lesser value could be acceptable if fully documented. The lightship displacement and longitudinal center of gravity should be determined by calculation based on draught and density readings.

---

## CHAPTER 4 DAMAGE STABILITY

### CONTENTS

SECTION 1 DAMAGE STABILITY .....	86
SECTION 2 SUBDIVISION, WATERTIGHT AND WEATHERTIGHT INTEGRITY .....	102

---

## SECTION 1 DAMAGE STABILITY

### Contents

1.1. Application.....	87
1.2. Definitions .....	87
1.3. Stability information to be supplied to Master .....	89
1.4. Required Subdivision Index "R" .....	89
1.5. Attained Subdivision Index "A" .....	90
1.6. Calculation of the factor $p_i$ .....	91
1.7. Calculation of the factor $s_i$ .....	95
1.8. Permeability .....	100
1.9. Special Requirements concerning passenger ship stability.....	100

## 1.1. Application

- 1.1.1. The damage stability requirements in this Chapter shall apply to cargo ships of 80 m in length (L) and upwards and to all passenger ships regardless of length but shall exclude those cargo ships which are shown to comply with subdivision and damage stability regulations in other instruments developed by the Organization.
- 1.1.2. The Administration may, for a particular ship or group of ships, accept alternative methodologies if it is satisfied that at least the same degree of safety as represented by these regulations is achieved. Any Administration which allows such alternative methodologies shall communicate to the Organization particulars thereof.
- 1.1.3. Ships shall be as efficiently subdivided as is possible having regard to the nature of the service for which they are intended. The degree of subdivision shall vary with the subdivision length ( $L_s$ ) of the ship and with the service, in such manner that the highest degree of subdivision corresponds with the ships of greatest subdivision length ( $L_s$ ), primarily engaged in the carriage of passengers.
- 1.1.4. Where it is proposed to fit decks, inner skins or longitudinal bulkheads of sufficient tightness to seriously restrict the flow of water, the Administration shall be satisfied that proper consideration is given to beneficial or adverse effects of such structures in the calculations.

## 1.2. Definitions

**Subdivision length ( $L_s$ ):** The subdivision length of the ship is the greatest projected molded length of that part of the ship at or below deck or decks limiting the vertical extent of flooding with the ship at the deepest subdivision draught.

**Mid-length:** The mid-point of the subdivision length of the ship is termed as mid-length.

**Aft terminal:** This is the aft limit of the subdivision length.

**Forward terminal:** This is the forward limit of the subdivision length.

**Length (L)** is the length as defined in the International Convention on Load Lines in force.

**Freeboard deck** is the deck as defined in the International Convention on Load Lines in force.

**Forward perpendicular** is the forward perpendicular as defined in the International Convention on Load Lines in force.

**Breadth ( $B_m$ ):** The greatest molded breadth of the ship at or below the deepest subdivision draught.

**Draught (T):** This is the vertical distance from the keel line at mid-length to the waterline in question.

**Deepest subdivision draught ( $T_s$ ):** This is the waterline which corresponds to the Summer Load Line draught of the ship.

**Light service draught (T):** This is the service draught corresponding to the lightest anticipated loading and associated tankage, including, however, such ballast as may be necessary for stability and/or immersion. Passenger ships should include the full complement of passengers and crew on board.

**Partial subdivision draught ( $T_p$ ):** This is the light service draught plus 60% of the difference between the light service draught and the deepest subdivision draught.

**Trim:** Trim is the difference between the draught forward and the draught aft, where the draughts are measured at the forward and aft terminals respectively, disregarding any rake of keel.

**Permeability ( $\mu$ ):** The permeability of a space is the proportion of the immersed volume of that space which can be occupied by water.

**Machinery spaces:** The spaces that lie in between the watertight boundaries of a space containing the main and auxiliary propulsion machinery, including boilers, generators and electric motors primarily intended for propulsion. In the case of unusual arrangements, the Administration may define the limits of the machinery spaces.

**Weather tight:** Weather tight means that in any sea condition water will not penetrate into the ship.

**Watertight:** Watertight means having scantlings and arrangements capable of preventing the passage of water in any direction under the head of water likely to occur in intact and damaged conditions. In the damaged condition, the head of water is to be considered in the worst situation at equilibrium, including intermediate stages of flooding.

**Design pressure:** The hydrostatic pressure for which each structure or appliance assumed watertight in the intact and damage stability calculations is designed to withstand.

**Bulkhead deck:** In a passenger ship, bulkhead deck means the uppermost deck at any point in the subdivision length ( $L_s$ ) to which the main bulkheads and the ship's shell are carried watertight and the lowermost deck from which passenger and crew evacuation will not be impeded by water in any stage of flooding for damage cases defined in 1.9 below. The bulkhead deck may be a stepped deck. In a cargo ship the freeboard deck may be taken as the bulkhead deck.

**Deadweight:** The difference in tonnes between the displacement of a ship in water of a specific gravity of 1.025 at the draught corresponding to the assigned summer freeboard and the lightweight of the ship.

**Light weight:** This refers to the displacement of a ship in tonnes without cargo, fuel, lubricating oil, ballast water, fresh water and feed water in tanks, consumable stores, and passengers and crew and their effects.

**Oil tanker** is the oil tanker defined in Regulation 1 of Annex I of the Protocol of 1978 relating to the International Convention for the Prevention of Pollution from Ships, 1973.

**Ro–Ro passenger ship:** A passenger ship with Ro–Ro spaces or special category spaces.

**Bulk carrier** means a ship which is intended primarily to carry dry cargo in bulk, including such types as ore carriers and combination carriers.

**Keel line:** This line is parallel to the slope of the keel passing amidships through:

1. The top of the keel at centerline or line of intersection of the inside of shell plating with the keel if a bar keel extends below that line, on a ship with a metal shell; or
2. In wood and composite ships, the distance is measured from the lower edge of the keel rabbet. When the form at the lower part of the midship section is of a hollow character, or where thick garboards are fitted, the distance is measured from the point where the line of the flat of the bottom continued inward intersects the centerline amidships.

*Amidships* is at the middle of the length (L).

### 1.3. Stability information to be supplied to Master

- 1.3.1. The master shall be supplied with such information satisfactory to the Administration as is necessary to enable him by rapid and simple processes to obtain accurate guidance as to the stability of the ship under varying conditions of service. A copy of the stability information shall be furnished to the Administration.
- 1.3.2. The information should include:
1. Curves or tables of minimum operational metacentric height (GM) versus draught which assures compliance with the relevant intact and damage stability requirements, alternatively corresponding curves or tables of the maximum allowable vertical center of gravity (KG) versus draught, or with the equivalents of either of these curves;
  2. instructions concerning the operation of cross-flooding arrangements; and
  3. all other data and aids which might be necessary to maintain the required intact stability and stability after damage.
- 1.3.3. The stability information shall show the influence of various trims in cases where the operational trim range exceeds  $\pm 0.5\%$  of  $L_s$ .
- 1.3.4. For ships which have to fulfill the stability requirements of this chapter, information referred to in paragraph 1.3.2 above, is determined from considerations related to the subdivision index, in the following manner:  
Minimum required GM (or maximum permissible vertical position of center of gravity KG) for the three draughts  $T_s$ ,  $T_p$  and  $T_l$  are equal to the GM (or KG values) of corresponding loading cases used for the calculation of survival factor 'si'. For intermediate draughts, values to be used shall be obtained by linear interpolation applied to the GM value only between the deepest subdivision draught and the partial subdivision draught and between the partial load line and the light service draught respectively. Intact stability criteria will also be taken into account by retaining for each draft the maximum among minimum required GM values or the minimum of maximum permissible KG values for both criteria. If the subdivision index is calculated for different trims, several required GM curves will be established in the same way.
- 1.3.5. When curves or tables of minimum operational metacentric height (GM) versus draught are not appropriate, the master should ensure that the operating condition does not deviate from a studied loading condition, or verify by calculation that the stability criteria are satisfied for this loading condition.

### 1.4. Required Subdivision Index "R"

- 1.4.1. The subdivision of a ship is considered sufficient if the attained subdivision index A, determined in accordance with 1.5 below, is not less than the required subdivision index R calculated in accordance with this regulation and if, in addition, the partial indices  $A_s$ ,  $A_p$  and  $A_t$  are not less than 0.9R for passenger ships and 0.5R for cargo ships.
- 1.4.2. For all ships to which the damage stability requirements of this chapter apply, the degree of subdivision to be provided shall be determined by the required subdivision index R, as follows:
- a. In the case of cargo ships greater than 100 m in length ( $L_s$ ):

$$R = 1 - \frac{128}{L_s + 152}$$

- b. In the case of cargo ships not less than 80 m in length ( $L_s$ ) and not greater than 100 m in length ( $L_s$ ):

$$R = 1 - \left[ 1 / \left( 1 + \frac{L_s}{100} \times \frac{R_o}{1 - R_o} \right) \right]$$

Where,

$R_o$  is the value of  $R$  as calculated in accordance with the formula in subparagraph 'a' above.

- c. In the case of passenger ships:

$$R = 1 - \frac{5000}{L_s + 2.5 N + 15,225}$$

Where:

$$N = N_1 + 2 N_2$$

$N_1$  = number of persons for whom lifeboats are provided

$N_2$  = number of persons (including officers and crew) the ship is permitted to carry in excess of  $N_1$ .

- d. Where the conditions of service are such that compliance with paragraph c above, on the basis of  $N = N_1 + 2N_2$  is impracticable and where the Administration considers that a suitably reduced degree of hazard exists, a lesser value of  $N$  may be taken but in no case less than  $N = N_1 + N_2$ .

## 1.5. Attained Subdivision Index "A"

- 1.5.1. The attained subdivision index  $A$  is obtained by the summation of the partial indices  $A_s$ ,  $A_p$  and  $A_l$ , (weighted as shown) calculated for the draughts  $d_s$ ,  $d_p$  and  $d_l$  defined 1.2 above, in accordance with the following formula:

$$A = 0.4 A_s + 0.4 A_p + 0.2 A_l$$

Each partial index is a summation of contributions from all damage cases taken in consideration, using the following formula:

$$A = \sum p_i s_i$$

Where:

$i$  represents each compartment or group of compartments under consideration,

$p_i$  accounts for the probability that only the compartment or group of compartments under consideration may be flooded, disregarding any horizontal subdivision, as defined in 1.6 below,

$s_i$  accounts for the probability of survival after flooding the compartment or group of compartments under consideration, and includes the effect of any horizontal subdivision, as defined in 1.7 below.

- 1.5.2. In the calculation of A, the level trim shall be used for the deepest subdivision draught and the partial subdivision draught. The actual service trim shall be used for the light service draught. If, in any service condition, the trim variation in comparison with the calculated trim is greater than 0.5% of  $L_s$ , one or more additional calculations of A are to be submitted for the same draughts but different trims so that, for all service conditions, the difference in trim in comparison with the reference trim used for one calculation will be less than 0.5% of  $L_s$ .
- 1.5.3. When determining the positive righting lever (GZ) of the residual stability curve, the displacement used should be that of the intact condition. That is, the constant-displacement method of calculation should be used.
- 1.5.4. The summation indicated by the above formula shall be taken over the ship's subdivision length ( $L_s$ ) for all cases of flooding in which a single compartment or two or more adjacent compartments are involved. In the case of unsymmetrical arrangements, the calculated A value should be the mean value obtained from calculations involving both sides. Alternatively, it should be taken as that corresponding to the side which evidently gives the least favorable result.
- 1.5.5. Wherever wing compartments are fitted, contribution to the summation indicated by the formula shall be taken for all cases of flooding in which wing compartments are involved. Additionally, cases of simultaneous flooding of a wing compartment or group of compartments and the adjacent inboard compartment or group of compartments, but excluding damage of transverse extent greater than one half of the ship breadth B, may be added. For the purpose of this regulation, transverse extent is measured inboard from ship's side, at right angles to the centerline at the level of the deepest subdivision draught.
- 1.5.6. In the flooding calculations carried out according to the regulations, only one breach of the hull and only one free surface need to be assumed. The assumed vertical extent of damage is to extend from the baseline upwards to any watertight horizontal subdivision above the waterline or higher. However, if a lesser extent of damage will give a more severe result; such extent is to be assumed.
- 1.5.7. If pipes, ducts or tunnels are situated within the assumed extent of damage, arrangements are to be made to ensure that progressive flooding cannot thereby extend to compartments other than those assumed flooded. However, the Administration may permit minor progressive flooding if it is demonstrated that its effects can be easily controlled and the safety of the ship is not impaired.

#### 1.6. Calculation of the factor $p_i$

- 1.6.1. The factor  $p_i$  for a compartment or group of compartments shall be calculated in accordance with paragraphs 1.6.1.1 and 1.6.1.2 below, using the following notations:

$j$  = the aft most damage zone number involved in the damage starting with No.1 at the stern;

$n$  = the number of adjacent damage zones involved in the damage;

- $k$  = the number of a particular longitudinal bulkhead as barrier for transverse penetration in a damage zone counted from shell towards the centerline. The shell has  $k = 0$ ;
- $x_1$  = the distance from the aft terminal of  $L_s$  to the aft end of the zone in question;
- $x_2$  = the distance from the aft terminal of  $L_s$  to the forward end of the zone in question;
- $b$  = the mean transverse distance in meters measured at right angles to the centerline at the deepest subdivision load line between the shell and an assumed vertical plane extended between the longitudinal limits used in calculating the factor  $p_i$  and which is a tangent to, or common with, all or part of the outermost portion of the longitudinal bulkhead under consideration. This vertical plane shall be so orientated that the mean transverse distance to the shell is a maximum, but not more than twice the least distance between the plane and the shell. If the upper part of a longitudinal bulkhead is below the deepest subdivision load line the vertical plane used for determination of  $b$  is assumed to extend upwards to the deepest subdivision waterline. In any case,  $b$  is not to be taken greater than  $B/2$ .

If the damage involves a single zone only:

$$p_i = p(x_1, x_2) \cdot [r(x_1, x_2, b_k) - r(x_1, x_2, b_{k-1})]$$

If the damage involves two adjacent zones:

$$p_i = p(x_1, x_{2j+1}) \cdot [r(x_1, x_{2j+1}, b_k) - r(x_1, x_{2j+1}, b_{k-1})] - p(x_1, x_2) \cdot [r(x_1, x_2, b_k) - r(x_1, x_2, b_{k-1})] - p(x_{1j+1}, x_{2j+1}) \cdot [r(x_{1j+1}, x_{2j+1}, b_k) - r(x_{1j+1}, x_{2j+1}, b_{k-1})]$$

If the damage involves three or more adjacent zones:

$$p_i = p(x_1, x_{2j+n-1}) \cdot [r(x_1, x_{2j+n-1}, b_k) - r(x_1, x_{2j+n-1}, b_{k-1})] - p(x_1, x_{2j+n-2}) \cdot [r(x_1, x_{2j+n-2}, b_k) - r(x_1, x_{2j+n-2}, b_{k-1})] - p(x_{1j+1}, x_{2j+n-1}) \cdot [r(x_{1j+1}, x_{2j+n-1}, b_k) - r(x_{1j+1}, x_{2j+n-1}, b_{k-1})] + p(x_{1j+1}, x_{2j+n-2}) \cdot [r(x_{1j+1}, x_{2j+n-2}, b_k) - r(x_{1j+1}, x_{2j+n-2}, b_{k-1})]$$

and where  $r(x_1, x_2, b_0) = 0$ .

1.6.1.1. The factor  $p(x_1, x_2)$  is to be calculated according to the following formulae:

$$\text{Overall normalized max damage length: } J_{max} = 10/33$$

$$\text{Knuckle point in the distribution: } J_{kn} = 5/33$$

$$\text{Cumulative probability at } J_{kn}: p_k = 11/12$$

$$\text{Maximum absolute damage length: } l_{max} = 60 \text{ m}$$

$$\text{Length where normalized distribution ends: } L^* = 260 \text{ m}$$

Probability density at  $J = 0$ :

$$b_0 = 2 \left( \frac{p_k}{J_{kn}} - \frac{1 - p_k}{J_{max} - J_{kn}} \right)$$

When  $L_s \leq L^*$ :

$$J_m = \min \left\{ J_{max}, \frac{l_{max}}{L_s} \right\}$$

$$J_k = \frac{J_m}{2} + \frac{1 - \sqrt{1 + (1 - 2p_k)b_0J_m + \frac{1}{4}b_0^2J_m^2}}{b_0}$$

$$b_{12} = b_0$$

When  $L_s > L^*$ :

$$J_m^* = \min \left\{ J_{max}, \frac{l_{max}}{L^*} \right\}$$

$$J_k^* = \frac{J_m^*}{2} + \frac{1 - \sqrt{1 + (1 - 2p_k)b_0J_m^* + \frac{1}{4}b_0^2J_m^{*2}}}{b_0}$$

$$J_m = \frac{J_m^* \cdot L^*}{L_s}$$

$$J_k = \frac{J_k^* \cdot L^*}{L_s}$$

$$b_{12} = 2 \left( \frac{p_k}{J_k} - \frac{1 - p_k}{J_m - J_k} \right)$$

$$b_{11} = 4 \frac{1 - p_k}{(J_m - J_k)J_k} - 2 \frac{p_k}{J_k^2}$$

$$b_{21} = -2 \frac{1 - p_k}{(J_m - J_k)^2}$$

The non-dimensional damage length:

$$J = \frac{x_2 - x_1}{L_s}$$

The normalized length of a compartment or group of compartments:

$J_n$  is to be taken as the lesser of  $J$  and  $J_m$

- a. Where neither limit of the compartment or group of compartments under consideration coincides with the aft or forward terminals:

$$J \leq J_k:$$

$$p(x1, x2) = p_1 = \frac{1}{6} J^2 (b_{11} J + 3b_{12})$$

$$J \geq J_k:$$

$$p(x1, x2) = p_2 = \frac{1}{3} b_{11} J_k^3 + \frac{1}{2} (b_{11} J - b_{12}) J_k^2 + b_{12} J J_k - \frac{1}{3} b_{21} (J_n^3 - J_k^3) + \frac{1}{2} (b_{21} J - b_{22}) (J_n^2 - J_k^2) + b_{22} J (J_n - J_k)$$

- b. Where the aft limit of the compartment or group of compartments under consideration coincides with the aft terminal or the forward limit of the compartment or group of compartments under consideration coincides with the forward terminal:

$$J \leq J_k:$$

$$p(x1, x2) = \frac{1}{2} (p_1 + J)$$

$$J > J_k:$$

$$p(x1, x2) = \frac{1}{2} (p_2 + J)$$

- c. Where the compartment or groups of compartments considered extends over the entire subdivision length ( $L_s$ ):

$$p(x1, x2) = 1$$

1.6.1.2. The factor  $r(x1, x2, b)$  shall be determined by the following formulae:

$$r(x1, x2, b) = 1 - (1 - C) \cdot \left[ 1 - \frac{G}{p(x1, x2)} \right]$$

Where,

$$C = 12 \cdot J_b \cdot (-45 \cdot J_b + 4),$$

where

$$J_b = \frac{b}{15 \cdot B_m}$$

- a. Where the compartment or groups of compartments considered extends over the entire subdivision length ( $L_s$ ):

$$G = G_1 = \frac{1}{2} b_{11} J_b^2 + b_{12} J_b$$

- b. Where neither limit of the compartment or group of compartments under consideration coincides with the aft or forward terminals:

$$G = G_2 = -\frac{1}{3} b_{11} J_0^3 + \frac{1}{2} (b_{11} J - b_{12}) J_0^2 + b_{12} J J_0$$

Where,

$$J_0 = \min (J, J_b)$$

- c. Where the aft limit of the compartment or group of compartments under consideration coincides with the aft terminal or the forward limit of the compartment or group of compartments under consideration coincides with the forward terminal:

$$G = \frac{1}{2} (G_2 + G_1 \cdot J)$$

## 1.7. Calculation of the factor $s_i$

- 1.7.1. The factor ' $s_i$ ' shall be determined for each case of assumed flooding, involving a compartment or group of compartments, in accordance with the following notations and the provisions in this regulation.

$\theta_e$  is the equilibrium heel angle in any stage of flooding, in degrees;

$\theta_v$  is the angle, in any stage of flooding, where the righting lever becomes negative, or the angle at which an opening incapable of being closed weather tight becomes submerged;

$GZ_{\max}$  is the maximum positive righting lever, in meters, up to the angle  $\theta_v$ ;

*Range* is the range of positive righting levers, in degrees, measured from the angle  $\theta_e$ . The positive range is to be taken up to the angle  $\theta_v$ ;

*Flooding stage* is any discrete step during the flooding process, including the stage before equalization (if any), until final equilibrium has been reached.

- 1.7.1.1. The factor  $s_i$  for any damage case at any initial loading condition,  $d_i$ , shall be obtained from the formula:

$$s_i = \text{minimum} \{S_{\text{intermediate}, i} \text{ OR } S_{\text{final}, i} \cdot S_{\text{mom}, i}\}$$

Where:

$S_{\text{intermediate}, i}$  is the probability to survive all intermediate flooding stages until the final equilibrium stage, and is calculated in accordance with paragraph 1.7.2 below;

$S_{final, i}$  is the probability to survive in the final equilibrium stage of flooding. It is calculated in accordance with paragraph 1.7.3 below;

$S_{mom, i}$  is the probability to survive heeling moments, and is calculated in accordance with paragraph 1.7.4 below.

- 1.7.2. The factor  $S_{intermediate, i}$  is applicable only to passenger ships (for cargo ships  $S_{intermediate, i}$  should be taken as unity) and shall be taken as the least of the s-factors obtained from all flooding stages including the stage before equalization, if any, and is to be calculated as follows:

$$S_{intermediate, i} = \left[ \frac{GZ_{max}}{0.05} \cdot \frac{Range}{7} \right]^{\frac{1}{4}}$$

Where,  $GZ_{max}$  is not to be taken as more than 0.05 m and  $Range$  as not more than 7°.  $S_{intermediate} = 0$ , if the intermediate heel angle exceeds 15°. Where cross-flooding fittings are required, the time for equalization shall not exceed 10 min.

- 1.7.3. The factor  $s_{final, i}$  shall be obtained from the formula:

$$s_{final, i} = K \cdot \left[ \frac{GZ_{max}}{0.12} \cdot \frac{Range}{16} \right]^{\frac{1}{4}}$$

Where:

$GZ_{max}$  is not to be taken as more than 0.12 m;

$Range$  is not to be taken as more than 16°;

$K = 1$  if  $\theta_e \geq \theta_{min}$

$K = 0$  if  $\theta_e \leq \theta_{max}$

$$K = \sqrt{\frac{\theta_{max} - \theta_e}{\theta_{max} - \theta_{min}}} \text{ Otherwise,}$$

Where:

$\theta_{min}$  is 7° for passenger ships and 25° for cargo ships; and

$\theta_{max}$  is 15° for passenger ships and 30° for cargo ships.

- 1.7.4. The factor  $s_{mom, i}$  is applicable only to passenger ships (for cargo ships  $s_{mom, i}$  shall be taken as unity) and shall be calculated at the final equilibrium from the formula:

$$s_{mom, i} = \frac{(GZ_{max} - 0.04) \cdot Displacement}{M_{heel}}$$

Where:

$Displacement$  is the intact displacement at the subdivision draught;

$M_{heel}$  is the maximum assumed heeling moment as calculated in accordance with paragraph 1.7.4.1 below; and

$$S_{mom, i} \leq 1$$

1.7.4.1. The heeling moment  $M_{heel}$  is to be calculated as follows:

$$M_{heel} = \text{maximum} \{M_{passenger} \text{ or } M_{wind} \text{ or } M_{Survival\ craft}\}$$

1.  $M_{passenger}$  is the maximum assumed heeling moment resulting from movement of passengers, and is to be obtained as follows:

$$M_{passenger} = (0.075 \cdot N_p) \cdot (0.45 \cdot B) \text{ (t-m)}$$

Where:

$N_p$  is the maximum number of passengers permitted to be on board in the service condition corresponding to the deepest subdivision draught under consideration; and

$B$  is the beam of the ship.

Alternatively, the heeling moment may be calculated assuming the passengers are distributed with 4 persons per square meter on available deck areas towards one side of the ship on the decks where muster stations are located and in such a way that they produce the most adverse heeling moment. In doing so, a weight of 75 kg per passenger is to be assumed.

2.  $M_{wind}$  is the maximum assumed wind force acting in a damage situation:

$$M_{wind} = (P \cdot A \cdot Z) / 9,806 \text{ (t-m)}$$

Where:

$$P = 120 \text{ N/m}^2;$$

$A$  = projected lateral area above waterline;

$Z$  = distance from center of lateral projected area above waterline to  $T/2$ ; and

$T$  = ship's draught.

3.  $M_{Survivalcraft}$  is the maximum assumed heeling moment due to the launching of all fully loaded davit-launched survival craft on one side of the ship. It shall be calculated using the following assumptions:

- all lifeboats and rescue boats fitted on the side to which the ship has heeled after having sustained damage shall be assumed to be swung out fully loaded and ready for lowering;
- for lifeboats which are arranged to be launched fully loaded from the stowed position, the maximum heeling moment during launching shall be taken;

- a fully loaded davit-launched life raft attached to each davit on the side to which the ship has heeled after having sustained damage shall be assumed to be swung out ready for lowering;
  - persons not in the life-saving appliances which are swung out shall not provide either additional heeling or righting moment; and .5 life-saving appliances on the side of the ship opposite to the side to which the ship has heeled shall be assumed to be in a stowed position.
- 1.7.5. Unsymmetrical flooding is to be kept to a minimum consistent with the efficient arrangements. Where it is necessary to correct large angles of heel, the means adopted shall, where practicable, be self-acting, but in any case, where controls to equalization devices are provided they shall be operable from above the bulkhead deck. These fittings, together with their controls, shall be acceptable to the Administration. Suitable information concerning the use of equalization devices shall be supplied to the master of the ship.
- 1.7.5.1. Tanks and compartments taking part in such equalization shall be fitted with air pipes or equivalent means of sufficient cross-section to ensure that the flow of water into the equalization compartments is not delayed.
- 1.7.5.2. In all cases,  $s_i$  is to be taken as zero in those cases where the final waterline, taking into account sinkage, heel and trim, immerses:
- a. the lower edge of openings through which progressive flooding may take place and such flooding is not accounted for in the calculation of factor  $s_i$ . Such openings shall include air-pipes, ventilators and openings which are closed by means of weather tight doors or hatch covers; and
  - b. any part of the bulkhead deck in passenger ships considered a horizontal evacuation route
- 1.7.5.3. The factor  $s_i$  is to be taken as zero if, taking into account sinkage, heel and trim, any of the following occur in any intermediate stage or in the final stage of flooding:
- a. immersion of any vertical escape hatch in the bulkhead deck;
  - b. any controls intended for the operation of watertight doors, equalization devices, valves on piping or on ventilation ducts intended to maintain the integrity of watertight bulkheads from above the bulkhead deck become inaccessible or inoperable;
  - c. immersion of any part of piping or ventilation ducts carried through a watertight boundary that is located within any compartment included in damage cases contributing to the attained index A, if not fitted with watertight means of closure at each boundary.
- 1.7.5.4. However, where compartments assumed flooded due to progressive flooding are taken into account in the damage stability calculations, multiple values of  $s_i$  intermediate,  $i$  may be calculated, assuming equalization in additional flooding phases.
- 1.7.5.5. Except as provided in paragraph 1.7.5.3.a, openings closed by means of watertight manhole covers and flush scuttles, small watertight hatch covers, remotely operated sliding watertight doors, side scuttles of the non-opening type as well as watertight access doors and hatch covers required to be kept closed at sea need not be considered.
- 1.7.6. Where horizontal watertight boundaries are fitted above the waterline under consideration, the  $s$ -value calculated for the lower compartment or group of compartments shall be obtained by multiplying the value as determined in paragraph 1.7.1.1 above, by the reduction factor

$v_m$  according to paragraph 1.7.6.1 below, which represents the probability that the spaces above the horizontal subdivision will not be flooded.

1.7.6.1. The factor  $v_m$  shall be obtained from the formula:

$$v_m = v(H_{j, n, m}, d) - v(H_{j, n, m-1}, d)$$

Where:

$H_{j, n, m}$  is the least height above the baseline, in meters, within the longitudinal range of  $x_{1(j)} \dots x_{2(j+n-1)}$  of the  $m^{\text{th}}$  horizontal boundary which is assumed to limit the vertical extent of flooding for the damaged compartments under consideration;

$H_{j, n, m-1}$  is the least height above the baseline, in meters, within the longitudinal range of  $x_{1(j)} \dots x_{2(j+n-1)}$  of the  $(m-1)^{\text{th}}$  horizontal boundary which is assumed to limit the vertical extent of flooding for the damaged compartments under consideration;

$j$  signifies the aft terminal of the damaged compartments under consideration;

$m$  represents each horizontal boundary counted upwards from the waterline under consideration;

$d$  is the draught in question as defined in regulation 2; and

$x_1$  and  $x_2$  represent the terminals of the compartment or group of compartments considered in 1.6 above.

a. The factors  $v(H_{j, n, m}, d)$  and  $v(H_{j, n, m-1}, d)$  shall be obtained from the formulae:

$$v(H, d) = 0.8 \frac{(H-d)}{7.8}, \text{ if } (Hm - d) \text{ is less than, or equal to, } 7.8 \text{ m;}$$

$$v(H, d) = 0.8 + 0.2 \left[ \frac{(H-d) - 7.8}{4.7} \right] \text{ in all other cases.}$$

Where:

$v(H_{j, n, m}, d)$  is to be taken as 1, if  $Hm$  coincides with the uppermost watertight boundary of the ship within the range  $(x_{1(j)} \dots x_{2(j+n-1)})$ , and

$v(H_{j, n, 0}, d)$  is to be taken as 0.

In no case is  $v_m$  to be taken as less than zero or more than 1.

1.7.6.2. In general, each contribution  $dA$  to the index A in the case of horizontal subdivisions is obtained from the formula:

$$dA = p_i \cdot [v_1 \cdot S_{min1} + (v_2 - v_1) \cdot S_{min2} + \dots + (1 - v_{m-1}) \cdot S_{minm}]$$

Where:

$V_m$  = the v-value calculated in accordance with paragraph 1.7.6.1 above;

$S_{min}$  = the least s-factor for all combinations of damages obtained when the assumed damage extends from the assumed damage height  $H_m$  downwards.

## 1.8. Permeability

1.8.1. For the purpose of the subdivision and damage stability calculations of the regulations, the permeability of each general compartment or part of a compartment shall be as follows:

Spaces	Permeability
Appropriated to stores	0.60
Occupied by accommodation	0.95
Occupied by machinery	0.85
Void Spaces	0.95
Intended for liquids	0 or 0.95, whichever results in the more severe requirement

1.8.2. For the purpose of the subdivision and damage stability calculations of the regulations, the permeability of each cargo compartment or part of a compartment shall be as follows:

Spaces	Permeability at draft $T_s$	Permeability at draft $T_p$	Permeability at draft $T_l$
Dry Cargo Spaces	0.70	0.80	0.95
Container Spaces	0.70	0.80	0.95
Ro – Ro Spaces	0.90	0.90	0.95
Cargo Liquids	0.70	0.80	0.95

1.8.3. Other figures for permeability may be used if substantiated by calculations.

## 1.9. Special Requirements concerning passenger ship stability

1.9.1. A passenger ship intended to carry 400 or more persons shall have watertight subdivision abaft the collision bulkhead so that  $s_i = 1$  for the three loading conditions on which is based the calculation of the subdivision index and for a damage involving all the compartments within  $0.08L$  measured from the forward perpendicular.

1.9.2. A passenger ship intended to carry 36 or more persons is to be capable of withstanding damage along the side shell to an extent specified in paragraph 3. Compliance with this regulation is to be achieved by demonstrating that  $s_i$ , as defined in 1.7 above, is not less than 0.9 for the three loading conditions on which is based the calculation of the subdivision index.

- 1.9.3. The damage extent to be assumed when demonstrating compliance with 1.9.2 above, is to be dependent on both  $N$  as defined in 1.4 of this section, and  $L_s$  as defined in 1.2 of this section, such that:
- a. the vertical extent of damage is to extend from the ship's molded baseline to a position up to 12.5 m above the position of the deepest subdivision draught as defined in regulation 2, unless a lesser vertical extent of damage were to give a lower value of  $s_i$ , in which case this reduced extent is to be used;
  - b. where 400 or more persons are to be carried, a damage length of  $0.03L_s$  but not less than 3 m is to be assumed at any position along the side shell, in conjunction with a penetration inboard of  $0.1B$  but not less than 0.75 m measured inboard from the ship side, at right angles to the centerline at the level of the deepest subdivision draught;
  - c. where fewer than 400 persons are carried, damage length is to be assumed at any position along the shell side between transverse watertight bulkheads provided that the distance between two adjacent transverse watertight bulkheads is not less than the assumed damage length. If the distance between adjacent transverse watertight bulkheads is less than the assumed damage length, only one of these bulkheads shall be considered effective for the purpose of demonstrating compliance with paragraph 1.9.2 above;
  - d. where 36 persons are carried, a damage length of  $0.015L_s$  but not less than 3 m is to be assumed, in conjunction with a penetration inboard of  $0.05B$  but not less than 0.75 m; and
  - e. where more than 36, but fewer than 400, persons are carried, the values of damage length and penetration inboard, used in the determination of the assumed extent of damage, are to be obtained by linear interpolation between the values of damage length and penetration which apply for ships carrying 36 persons and 400 persons as specified in subparagraphs b and d above.

## SECTION 2 SUBDIVISION, WATERTIGHT AND WEATHERTIGHT INTEGRITY

### Contents

2.1. Double Bottoms in passenger ships and cargo ships other than tankers.....	103
2.2. Watertight Bulkheads .....	104

**2.1. Double Bottoms in passenger ships and cargo ships other than tankers**

- 2.1.1. A double bottom shall be fitted extending from the collision bulkhead to the after peak bulkhead, as far as this is practicable and compatible with the design and proper working of the ship.
- 2.1.2. Where a double bottom is required to be fitted, the inner bottom shall be continued out to the ship's sides in such a manner as to protect the bottom to the turn of the bilge. Such protection will be deemed satisfactory if the inner bottom is not lower at any part than a plane parallel with the keel line and which is located not less than a vertical distance  $h$  measured from the keel line, as calculated by the formula:  
 $h = B/20$   
However, in no case is the value of  $h$  to be less than 760 mm, and need not be taken as more than 2,000 mm.
- 2.1.3. Small wells constructed in the double bottom in connection with drainage arrangements of holds, etc., shall not extend downward more than necessary. A well extending to the outer bottom is, however, permitted at the after end of the shaft tunnel. Other wells (e.g., for lubricating oil under main engines) may be permitted by the Administration if satisfied that the arrangements give protection equivalent to that afforded by a double bottom complying with this regulation. In no case shall the vertical distance from the bottom of such a well to a plane coinciding with the keel line be less than 500 mm.
- 2.1.4. A double bottom need not be fitted in way of watertight tanks, including dry tanks of moderate size, provided the safety of the ship is not impaired in the event of bottom or side damage.
- 2.1.5. In the case of passenger ships to which the provisions of regulation 1.5 apply and which are engaged on regular service within the limits of a short international voyage, the Administration may permit a double bottom to be dispensed with if satisfied that the fitting of a double bottom in that part would not be compatible with the design and proper working of the ship.
- 2.1.6. Any part of a passenger ship or a cargo ship that is not fitted with a double bottom in accordance with paragraphs 2.1.1, 2.1.4 or 2.1.5 above, shall be capable of withstanding bottom damages, as specified in paragraph 2.1.8 below, in that part of the ship.
- 2.1.7. In the case of unusual bottom arrangements in a passenger ship or a cargo ship, it shall be demonstrated that the ship is capable of withstanding bottom damages as specified in paragraph 2.1.8 below.
- 2.1.8. Compliance with paragraphs 2.1.6 or 2.1.7 is to be achieved by demonstrating that  $s_i$ , when calculated in accordance with 1.7, is not less than 1 for all service conditions when subject to a bottom damage assumed at any position along the ship's bottom and with an extent specified in subparagraph b below, for the affected part of the ship:
- Flooding of such spaces shall not render emergency power and lighting, internal communication, signals or other emergency devices inoperable in other parts of the ship.
  - Assumed extent of damage shall be as follows:

	For 0.3L from the forward perpendicular of the ship	Any other part of the ship
Longitudinal extent	1/3 L2/3 or 14.5 m, whichever is less	1/3 L2/3 or 14.5 m, whichever is less
Transverse extent	B/6 or 10 m, whichever is less	B/6 or 5 m, whichever is less
Vertical extent, measured from the keel line	B/20 or 2 m, whichever is less	B/20 or 2 m, whichever is less

- c. If any damage of a lesser extent than the maximum damage specified in subparagraph b above, would result in a more severe condition, such damage should be considered.

2.1.9. In case of large lower holds in passenger ships, the Administration may require an increased double bottom height of not more than B/10 or 3 m, whichever is less, measured from the keel line. Alternatively, bottom damages may be calculated for these areas, in accordance with paragraph 2.1.8, but assuming an increased vertical extent.

## 2.2. Watertight Bulkheads

Each watertight subdivision bulkhead, whether transverse or longitudinal, shall be capable of supporting at least the pressure due to a head of water up to the bulkhead deck.

# ANNEX 1 DETAILED GUIDANCE FOR THE CONDUCT OF AN INCLINING TEST

## CONTENTS

SECTION 1 INTRODUCTION.....	106
SECTION 2 PREPARATIONS FOR THE INCLINING TEST.....	108
SECTION 3 EQUIPMENT REQUIRED.....	116
SECTION 4 TEST PROCEDURE.....	118

## SECTION 1 INTRODUCTION

### Contents

1.1. Introduction.....	107
------------------------	-----

**1.1. Introduction**

This annex supplements the inclining standards put forth in Chapter 3, Section 8 (Determination of lightship parameters) of this Code. This annex contains important detailed procedures for conducting an inclining test in order to ensure that valid results are obtained with maximum precision at a minimal cost to owners, shipyards and the Administration. A complete understanding of the correct procedures used to perform an inclining test is imperative in order to ensure that the test is conducted properly and so that results can be examined for accuracy as the inclining experiment is conducted.

## SECTION 2 PREPARATIONS FOR THE INCLINING TEST

### Contents

2.1.	Free surface and tankage .....	109
2.2.	Mooring arrangements .....	111
2.3.	Test weights .....	112
2.4.	Pendulums .....	113
2.5.	U-tubes .....	114
2.6.	Inclinometers .....	115

## 2.1. Free surface and tankage

### 2.1.1. General

If there are liquids on board the ship when it is inclined, whether in the bilges or in the tanks, they will shift to the low side when the ship heels. This shift of liquids will exaggerate the heel of the ship. Unless the exact weight and distance of liquid shifted can be precisely calculated, the metacentric height (GM) calculated from the inclining test will be in error. Free surface should be minimized by emptying the tanks completely and making sure all bilges are dry; or by completely filling the tanks so that no shift of liquid is possible. The latter method is not the optimum because air pockets are difficult to remove from between structural members of a tank, and the weight and center of the liquid in a full tank should be accurately determined in order to adjust the lightship values accordingly. When tanks must be left slack, it is desirable that the sides of the tanks be parallel vertical planes and the tanks be regular in shape (i.e. rectangular, trapezoidal, etc.) when viewed from above, so that the free surface moment of the liquid can be accurately determined. For example, the free surface moment of the liquid in a tank with parallel vertical sides can be readily calculated by the formula:

$$M_{fs} = l_{tk} * b_{tk}^3 * \rho_t / 12$$

Where:

$l_{tk}$  = Length of tank (m);

$b_{tk}$  = Breadth of tank (m);

$\rho_t$  = Specific gravity of liquid in tank (t/m<sup>3</sup>).

$$\text{Free surface correction (m)} = \frac{\sum_x M_{fs}(1) + M_{fs}(2) \dots + M_{fs}(x)}{\Delta}$$

Where:

$M_{fs}$  = Free surface moment (mt);

$\Delta$  = Displacement (t).

Free surface correction is independent of the height of the tank in the ship, location of the tank, and direction of heel. As the width of the tank increases, the value of free surface moment increases by the third power. The distance available for the liquid to shift is the predominant factor. This is why even the smallest amount of liquid in the bottom of a wide tank or bilge is normally unacceptable and should be removed prior to the inclining experiment. Insignificant amounts of liquids in V-shaped tanks or voids (e.g., a chain locker in the bow), where the potential shift is negligible, may remain if removal of the liquid would be difficult or would cause extensive delays.

When ballast water is used as inclining weight, the actual transverse and vertical movements of the liquid should be calculated taking into account the change of heel of the ship. Free surface corrections as defined in this paragraph should not apply to the inclining tanks.

### 2.1.2. Free surface and slack tanks

The number of slack tanks should normally be limited to one port/starboard pair or one centerline tank of the following:

- a. Fresh water reserve feed tanks;
- b. Fuel/diesel oil storage tanks;
- c. Fuel/diesel oil day tanks;
- d. Lube oil tanks;
- e. Sanitary tanks; or
- f. Potable water tanks.

To avoid pocketing, slack tanks should normally be of regular (i.e. rectangular, trapezoidal, etc.) cross section and be 20% to 80% full if they are deep tanks and 40% to 60% full if they are double-bottom tanks. These levels ensure that the rate of shifting of liquid remains constant throughout the heel angles of the inclining test. If the trim changes as the ship is inclined, then consideration should also be given to longitudinal pocketing. Slack tanks containing liquids of sufficient viscosity to prevent free movement of the liquids, as the ship is inclined (such as bunker at low temperature), should be avoided since the free surface cannot be calculated accurately. A free surface correction for such tanks should not be used unless the tanks are heated to reduce viscosity. Communication between tanks should never be allowed. Cross-connections, including those via manifolds, should be closed. Equal liquid levels in slack tank pairs can be a warning sign of open cross connections. A bilge, ballast, and fuel oil piping plan can be referred to, when checking for cross connection closures.

### 2.1.3. Pressed-up tanks

“Pressed up” means completely full with no voids caused by trim or inadequate venting. Anything less than 100% full, for example the 98% condition regarded as full for operational purposes, is not acceptable. Preferably, the ship should be rolled from side to side to eliminate entrapped air before taking the final sounding. Special care should be taken when pressing fuel oil tanks to prevent accidental pollution. An example of a tank that would appear “pressed up” but actually contains entrapped air, is shown in figure A1-2.1.




Fig A1-2.1

## 2.1.4. Empty tanks

It is generally not sufficient to simply pump tanks until suction is lost. Enter the tank after pumping to determine if final stripping with portable pumps or by hand is necessary. The exceptions are very narrow tanks or tanks where there is a sharp dead rise, since free surface would be negligible. Since all empty tanks should be inspected, all manholes should be open and the tanks well ventilated and certified as safe for entry. A safe testing device should be on hand to test for sufficient oxygen and minimum toxic levels. A certified marine chemist's certificate certifying that all fuel oil and chemical tanks are safe for human entry should be available, if necessary.

## 2.2. Mooring arrangements

- 2.2.1. The importance of good mooring arrangements cannot be overemphasized. The arrangement selections will be dependent upon many factors. Among the most important is depth of water, wind and current effects. Whenever possible, the ship should be moored in a quiet, sheltered area free from extraneous forces such as propeller wash from passing ships, or sudden discharges from shore side pumps. The depth of water under the hull should be sufficient to ensure that the hull will be entirely free of the bottom. The tide conditions and the trim of the ship during the test should be considered. Prior to the test, the depth of water should be measured and recorded in as many locations as necessary to ensure the ship will not contact the bottom. If marginal, the test should be conducted during high tide or the ship moved to deeper water.
- 2.2.2. The mooring arrangement should ensure that the ship will be free to list without restraint for a sufficient period of time to allow a satisfactory reading of the heeling angle, due to each weight shift, to be recorded.
- 2.2.3. The ship should be held by lines at the bow and the stern, attached to bollards and/or cleats on the deck. If suitable restraint of the ship cannot be achieved using deck fittings, then temporary pad eyes should be attached as close as possible to the centerline of the ship and as near the waterline as practical. Where the ship can be moored to one side only, it is good practice to supplement the bow and stern lines with two spring lines in order to maintain positive control of the ship, as shown in figure A1-2.2. The leads of the spring lines should be as long as practicable. Cylindrical camels should be provided between the ship and the dock. All lines should be slack, with the ship free of the pier and camels, when taking readings.




Figure A1-2.2

- 2.2.3.1. If the ship is held off the pier by the combined effect of the wind and current, a superimposed heeling moment will act on the ship throughout the test. For steady conditions this will not affect the results. Gusty winds or uniformly varying wind and/or current will cause these superimposed heeling moments to change, which may require additional test points to obtain a valid test. The need for additional test points can be determined by plotting test points as they are obtained.
- 2.2.3.2. If the ship is pressed against the fenders by wind and/or current, all lines should be slack. The cylindrical camels will prevent binding but there will be an additional superimposed heeling moment due to the ship bearing against the camels. This condition should be avoided where possible but, when used, consideration should be given to pulling the ship free of the dock and camels and letting the ship drift as readings are taken.
- 2.2.3.3. Another acceptable arrangement is where the combined wind and current are such that the ship may be controlled by only one line at either the bow or the stern. In this case, the control line should be led from on or near the centerline of the ship with all lines but the control line slack, the ship is free to veer with the wind and / or current as readings are taken. This can sometimes be troublesome because varying wind and/or current can cause distortion of the plot.
- 2.2.4. The mooring arrangement should be submitted to the approval authority for review prior to the test.
- 2.2.5. If a floating crane is used for handling inclining weights, it should not be moored to the ship.

### 2.3. Test weights

- 2.3.1. Weights, such as porous concrete, that can absorb significant amounts of moisture should only be used if they are weighed just prior to the inclining test or if recent weight certificates are presented. Each weight should be marked with an identification number and its weight. For small ships, drums completely filled with water may be used. Drums should normally be full and capped to allow accurate weight control. In such cases, the weight of the drums should be verified in the presence of the Administration representative using a recently calibrated scale.
- 2.3.2. Precautions should be taken to ensure that the decks are not overloaded during weight movements. If deck strength is questionable then a structural analysis should be performed to determine if existing framing can support the weight.
- 2.3.3. Generally, the test weights should be positioned as far outboard as possible on the upper deck. The test weights should be on board and in place prior to the scheduled time of the inclining test.
- 2.3.4. Where the use of solid weights to produce the inclining moment is demonstrated to be impracticable, the movement of ballast water may be permitted as an alternative method. This acceptance would be granted for a specific test only, and approval of the test procedure by the Administration is required. As a minimal prerequisite for acceptability, the following conditions should be required:
- Inclining tanks should be wall-sided and free of large stringers or other internal members that create air pockets. Other tank geometries may be accepted at the discretion of the Administration;
  - Tanks should be directly opposite to maintain ship's trim;
  - Specific gravity of ballast water should be measured and recorded;

- d. Pipelines to inclining tanks should be full. If the ship's piping layout is unsuitable for internal transfer, portable pumps and pipes/hoses may be used;
- e. Blanks must be inserted in transfer manifolds to prevent the possibility of liquids being "leaked" during transfer. Continuous valve control must be maintained during the test;
- f. All inclining tanks must be manually sounded before and after each shift;
- g. Vertical, longitudinal and transverse centers should be calculated for each movement;
- h. Accurate sounding / ullage tables must be provided. The ship's initial heel angle should be established prior to the incline in order to produce accurate values for volumes and transverse and vertical centers of gravity for the inclining tanks at every angle of heel. The draught marks amidships (port and starboard) should be used when establishing the initial heel angle;
- i. Verification of the quantity shifted may be achieved by a flow meter or similar device; and
- j. The time to conduct the inclining must be evaluated. If time requirements for transfer of liquids are considered too long, water may be unacceptable because of the possibility of wind shifts over long periods of time.

#### 2.4. Pendulums

- 2.4.1. The pendulums should be long enough to give a measured deflection, to each side of upright, of at least 15 cm. Generally, this will require a pendulum length of at least 3 m. It is recommended that pendulum lengths of 4 to 6 m be used. Usually, the longer the pendulum the greater the accuracy of the test; however, if excessively long pendulums are used on a tender ship the pendulums may not settle down and the accuracy of the pendulums would then be questionable. On large ships with high GM, pendulum lengths in excess of the length recommended above may be required to obtain the minimum deflection. In such cases, the trough, as shown in figure A1-2.3, should be filled with high-viscosity oil. If the pendulums are of different lengths, the possibility of collusion between station recorders is avoided.
- 2.4.2. On smaller ships, where there is insufficient headroom to hang long pendulums, the 15 cm deflection should be obtained by increasing the test weight so as to increase the heel. On most ships the typical inclination is between one and four degrees.
- 2.4.3. The pendulum wire should be piano wire or other monofilament material. The top connection of the pendulum should afford unrestricted rotation of the pivot point. An example is that of a washer with the pendulum wire attached suspended from a nail.
- 2.4.4. A trough filled with a liquid should be provided to dampen oscillations of the pendulum after each weight movement. It should be deep enough to prevent the pendulum weight from touching the bottom. The use of a winged plumb bob at the end of the pendulum wire can also help to dampen the pendulum oscillations in the liquid.
- 2.4.5. The battens should be smooth, light-colored wood, 1 to 2 cm thick, and should be securely fixed in position so that an inadvertent contact will not cause them to shift. The batten should be aligned close to the pendulum wire but not in contact with it.
- 2.4.6. A typical satisfactory arrangement is shown in figure A1-2.3. The pendulums may be placed in any location on the ship, longitudinally and transversely. The pendulums should be in place prior to the scheduled time of the inclining test.
- 2.4.7. It is recommended that inclinometers or other measuring devices only be used in conjunction with at least one pendulum. The Administration may approve an alternative arrangement when this is found impractical.




Figure A1-2.3

## 2.5. U-tubes

- 2.5.1. The legs of the device should be securely positioned as far as outboard as possible and should be parallel to the centerline plane of the ship. The distance between the legs should be measured perpendicular to the centerline plane. The legs should be vertical, as far as practical.
- 2.5.2. Arrangements should be made for recording all readings at both legs. For easy reading and checking for air pockets, clear plastic tube or hose should be used throughout. The U-tube should be pressure-tested prior to the inclining test to ensure water tightness.
- 2.5.3. The horizontal distance between the legs of the U-tube should be sufficient to obtain a level difference of at least 15 cm between the upright and the maximum inclination to each side.
- 2.5.4. Normally, water would be used as the liquid in the U-tube. Other low-viscosity liquids may also be considered.
- 2.5.5. The tube should be free of air pockets. Arrangements should be made to ensure that the free flow of the liquid in the tube is not obstructed.
- 2.5.6. Where a U-tube is used as a measuring device, due consideration should be given to the prevailing weather conditions (see Chapter 4 Section 1, 1.1.3):
  - a. If the U-tube is exposed to direct sunlight, arrangements should be made to avoid temperature differences along the length of the tube;
  - b. If temperatures below 0HC are expected, the liquid should be a mixture of water and an anti-freeze additive; and
  - c. Where heavy rain squalls can be expected, arrangements should be made to avoid additional water entering the U-tube.

**2.6. Inclinerometers**

2.6.1. The use of inclinometers should be subject to at least the following recommendations:

- a. The accuracy should be equivalent to that of the pendulum;
- b. The sensitivity of the inclinometer should be such that the non-steady heeling angle of the ship can be recorded throughout the measurement;
- c. The recording period should be sufficient to accurately measure the inclination. The recording capacity should be generally sufficient for the whole test;
- d. The instrument should be able to plot or print the recorded inclination angles on paper;
- e. The instrument should have linear performance over the expected range of inclination angles;
- f. The instrument should be supplied with the manufacturer's instructions giving details of calibration, operating instructions, etc.; and
- g. It should be possible to demonstrate the required performance to the satisfaction of the Administration during the inclining test.

**SECTION 3 EQUIPMENT REQUIRED**

**Contents**

3.1. Equipment required..... 117

**3.1. Equipment required**

Besides the physical equipment necessary such as the inclining weights, pendulums, small boat, etc., the following are necessary and should be provided by or made available to the person in charge of the inclining:

- a. Engineering scales for measuring pendulum deflections (rules should be subdivided sufficiently to achieve the desired accuracy);
- b. Sharp pencils for marking pendulum deflections;
- c. Chalk for marking the various positions of the inclining weights;
- d. A sufficiently long measuring tape for measuring the movement of the weights and locating different items on board;
- e. A sufficiently long sounding tape for sounding tanks and taking freeboard readings;
- f. One or more well maintained specific gravity hydrometers with range sufficient to cover 0.999 to 1.030, to measure the specific gravity of the water in which the ship is floating (a hydrometer for measuring specific gravity of less than 1.000 may be needed in some locations);
- g. Other hydrometers as necessary to measure the specific gravity of any liquids on board;
- h. Graph paper to plot inclining moments versus tangents;
- i. A straight edge to draw the measured waterline on the lines drawing;
- j. A pad of paper to record data;
- k. An explosion-proof testing device to check for sufficient oxygen and absence of lethal gases in tanks and other closed spaces such as voids and cofferdams;
- l. A thermometer; and
- m. Draught tubes (if necessary).

## SECTION 4 TEST PROCEDURE

### Contents

4.1.	General.....	119
4.2.	Initial walk through and survey.....	119
4.3.	Freeboard/draught readings.....	120
4.4.	The incline .....	121

**4.1. General**

The inclining experiment, the freeboard/draught readings and the survey may be conducted in any order and still achieve the same results. If the person conducting the inclining test is confident that the survey will show that the ship is in an acceptable condition and there is the possibility of the weather becoming unfavorable, then it is suggested that the inclining be performed first and the survey last. If the person conducting the test is doubtful that the ship is complete enough for the test, it is recommended that the survey be performed first since this could invalidate the entire test, regardless of the weather conditions. It is very important that all weights, the number of people on board, etc., remain constant throughout the test.

**4.2. Initial walk through and survey**

The person responsible for conducting the inclining test should arrive on board the ship well in advance of the scheduled time of the test to ensure that the ship is properly prepared for the test. If the ship to be inclined is large, a preliminary walk through may need to be done the day preceding the actual incline. To ensure the safety of personnel conducting the walk through, and to improve the documentation of surveyed weights and deficiencies, at least two persons should make the initial walk through. Things to check include: all compartments are open, clean, and dry, tanks are well ventilated and gas-free, movable or suspended items are secured and their position documented, pendulums are in place, weights are on board and in place, a crane or other method for moving weights is available, and the necessary plans and equipment are available. Before beginning the inclining test, the person conducting the test should:

- 4.2.1. Consider the weather conditions. The combined adverse effect of wind, current and sea may result in difficulties or even an invalid test due to the following:
  - a. Inability to accurately record freeboards and draughts;
  - b. Excessive or irregular oscillations of the pendulums;
  - c. Variations in unavoidable superimposed heeling moments.

In some instances, unless conditions can be sufficiently improved by moving the ship to a better location, it may be necessary to delay or postpone the test. Any significant quantities of rain, snow, or ice should be removed from the ship before the test. If bad weather conditions are detected early enough and the weather forecast does not call for improving conditions, the Administration representative should be advised prior to departure from the office and an alternative date scheduled;

- 4.2.2. Make a quick overall survey of the ship to make sure the ship is complete enough to conduct the test and to ensure that all equipment is in place. An estimate of items which will be outstanding at the time of the inclining test should be included as part of any test procedure submitted to the Administration. This is required so that the Administration representative can advise the shipyard/naval architect if in their opinion the ship will not be sufficiently complete to conduct the incline and that it should be rescheduled. If the condition of the ship is not accurately depicted in the test procedure and at the time of the inclining test the Administration representative considers that the ship is in such condition that an accurate incline cannot be conducted, the representative may refuse to accept the incline and require that the incline be conducted at a later date;
- 4.2.3. Enter all empty tanks after it is determined that they are well ventilated and gas-free to ensure that they are dry and free of debris. Ensure that any pressed-up tanks are indeed full and free of air pockets. The anticipated liquid loading for the incline should be included in the procedure required to be submitted to the Administration;

- 4.2.4. Survey the entire ship to identify all items which need to be added to the ship, removed from the ship, or relocated on the ship to bring the ship to the lightship condition. Each item should be clearly identified by weight and vertical and longitudinal location. If necessary, the transverse location should also be recorded. The inclining weights, the pendulums, any temporary equipment and dunnage, and the people on board during the inclining test are all among the weights to be removed to obtain the lightship condition. The person calculating the lightship characteristics from the data gathered during the incline and survey and/or the person reviewing the inclining test may not have been present during the test and should be able to determine the exact location of the items from the data recorded and the ship's drawings. Any tanks containing liquids should be accurately sounded and the soundings recorded;
- 4.2.5. It is recognized that the weight of some items on board, or that are to be added, may have to be estimated. If this is necessary, it is in the best interest of safety to be on the safe side when estimating, so the following rules of thumb should be followed:
- a. When estimating weights to be added:
    - i. Estimate high for items to be added high in the ship; and
    - ii. Estimate low for items to be added low in the ship;
  - b. When estimating weights to be removed:
    - i. Estimate low for items to be removed from high in the ship; and
    - ii. Estimate high for items to be removed from low in the ship;
  - c. When estimating weights to be relocated:
    - i. Estimate high for items to be relocated to a higher point in the ship; and
    - ii. Estimate low for items to be relocated to a lower point in the ship.

### 4.3. Freeboard/draught readings

- 4.3.1. Freeboard/draught readings should be taken to establish the position of the waterline in order to determine the displacement of the ship at the time of the inclining test. It is recommended that at least five freeboard readings, approximately equally spaced, be taken on each side of the ship or that all draught marks (forward, midship, and aft) be read on each side of the ship. Draught mark readings should be taken to assist in determining the waterline defined by freeboard readings, or to verify the vertical location of draught marks on ships where their location has not been confirmed. The locations for each freeboard reading should be clearly marked. The longitudinal location along the ship should be accurately determined and recorded since the (molded) depth at each point will be obtained from the ship's lines. All freeboard measurements should include a reference note clarifying the inclusion of the coaming in the measurement and the coaming height.
- 4.3.2. Draught and freeboard readings should be read immediately before or immediately after the inclining test. Weights should be on board and in place and all personnel who will be on board during the test, including those who will be stationed to read the pendulums, should be on board and in location during these readings. This is particularly important on small ships. If readings are made after the test, the ship should be maintained in the same condition as during the test. For small ships, it may be necessary to counterbalance the list and trim effects of the freeboard measuring party. When possible, readings should be taken from a small boat.
- 4.3.3. A small boat should be available to aid in the taking of freeboard and draught mark readings. It should have low freeboard to permit accurate observation of the readings.

- 4.3.4. The specific gravity of the flotation water should be determined at this time. Samples should be taken from a sufficient depth of the water to ensure a true representation of the flotation water and not merely surface water, which could contain fresh water from run-off of rain. A hydrometer should be placed in a water sample and the specific gravity read and recorded. For large ships, it is recommended that samples of the flotation water be taken forward, midship, and aft and the readings averaged. For small ships, one sample taken from midships should be sufficient. The temperature of the water should be taken and the measured specific gravity corrected for deviation from the standard, if necessary. A correction to water specific gravity is not necessary if the specific gravity is determined at the inclining experiment site. Correction is necessary if specific gravity is measured when sample temperature differs from the temperature at the time of the inclining (e.g., if check of specific gravity is done at the office).
- 4.3.5. A draught mark reading may be substituted for a given freeboard reading at that longitudinal location if the height and location of the mark have been verified to be accurate by a keel survey while the ship was in dry dock.
- 4.3.6. A device, such as a draught tube, can be used to improve the accuracy of freeboard/draught readings by damping out wave action.
- 4.3.7. The dimensions given on a ship's lines drawing are normally molded dimensions. In the case of depth, this means the distance from the inside of the bottom shell to the inside of the deck plate. In order to plot the ship's waterline on the lines drawing, the freeboard readings should be converted to molded draughts. Similarly, the draught mark readings should be corrected from extreme (bottom of keel) to molded (top of keel) before plotting. Any discrepancy between the freeboard/draught readings should be resolved.
- 4.3.8. The mean draught (average of port and starboard readings) should be calculated for each of the locations where freeboard/draught readings are taken and plotted on the ship's lines drawing or outboard profile to ensure that all readings are consistent and together define the correct waterline. The resulting plot should yield either a straight line or a waterline which is either hogged or sagged. If inconsistent readings are obtained, the freeboards/draughts should be retaken.

#### 4.4. The incline

- 4.4.1. Prior to any weight movements the following should be checked:
- The mooring arrangement should be checked to ensure that the ship is floating freely (this should be done just prior to each reading of the pendulums);
  - The pendulums should be measured and their lengths recorded. The pendulums should be aligned so that when the ship heels, the wire will be close enough to the batten to ensure an accurate reading but will not come into contact with the batten. The typical satisfactory arrangement is shown in figure A1-4.1;
  - The initial position of the weights is marked on the deck. This can be done by tracing the outline of the weights on the deck;
  - The communications arrangement is adequate; and
  - All personnel are in place.
- 4.4.2. A plot should be run during the test to ensure that acceptable data are being obtained. Typically, the abscissa of the plot will be heeling moment  $W(x)$  (weight times distance  $x$ ) and the ordinate will be the tangent of the heel angle (deflection of the pendulum divided by the length of the pendulum). This plotted line does not necessarily pass through the origin or any other particular point for no single point is more significant than any other point. A linear regression analysis is often used to fit the straight line. The weight movements shown in figure A2-4.1 give a good spread of points on the test plot.




Figure A1-4.1

The plotting of all the readings for each of the pendulums during the inclining experiment aids in the discovery of bad readings. Since  $W(x)/\tan \phi$  should be constant, the plotted line should be straight. Deviations from a straight line are an indication that there were other moments acting on the ship during the inclining. These other moments should be identified, the cause corrected, and the weight movements repeated until a straight line is achieved. Figures A1-4.2 to A1-4.5 illustrates examples of how to detect some of these other moments during the inclining, and a recommended solution for each case. For simplicity, only the average of the readings is shown on the inclining plots.




Figure A1-4.2




Figure A1-4.3




Figure A1-4.4




Figure A1-4.5

4.4.3. Once everything and everyone is in place, the zero position should be obtained and the remainder of the experiment conducted as quickly as possible, while maintaining accuracy and proper procedures, in order to minimize the possibility of a change in environmental conditions during the test.

- 4.4.4. Prior to each pendulum reading, each pendulum station should report to the control station when the pendulum has stopped swinging. Then, the control station will give a "standby" warning and then a "mark" command. When "mark" is given, the batten at each position should be marked at the location of the pendulum wire. If the wire was oscillating slightly, the center of the oscillations should be taken as the mark. If any of the pendulum readers does not think the reading was a good one, the reader should advise the control station and the point should be retaken for all pendulum stations. Likewise, if the control station suspects the accuracy of a reading, it should be repeated for all the pendulum stations. Next to the mark on the batten should be written the number of the weight movement, such as zero for the initial position and one to seven for the weight movements.
- 4.4.5. Each weight movement should be made in the same direction, normally transversely, so as not to change the trim of the ship. After each weight movement, the distance the weight was moved (center to center) should be measured and the heeling moment calculated by multiplying the distance by the amount of weight moved. The tangent is calculated for each pendulum by dividing the deflection by the length of the pendulum. The resultant tangents are plotted on the graph. Provided there is good agreement among the pendulums with regard to the tan value, the average of the pendulum readings may be graphed instead of plotting each of the readings.
- 4.4.6. Inclining data sheets should be used so that no data are forgotten and so that the data are clear, concise, and consistent in form and format. Prior to departing the ship, the person conducting the test and the Administration representative should initial each data sheet as an indication of their concurrence with the recorded data.

---

## ANNEX 2 RECOMMENDATIONS FOR SKIPPERS OF FISHING VESSELS ON ENSURING A VESSEL'S ENDURANCE IN CONDITIONS OF ICE FORMATION

### CONTENTS

SECTION 1 PRIOR TO DEPARTURE.....	126
SECTION 2 AT SEA.....	128
SECTION 3 DURING ICE FORMATION.....	131
SECTION 4 LIST OF EQUIPMENT AND HAND TOOLS .....	134

---

**SECTION 1 PRIOR TO DEPARTURE**

1.1. Prior to departure ..... 127

**1.1. Prior to departure**

- 1.1.1. Firstly, the skipper should, as in the case of any voyages in any season, ensure that the vessel is generally in a seaworthy condition, giving full attention to basic requirements such as:
  - a. Loading of the vessel within the limits prescribed for the season (paragraph 1.1.2 below);
  - b. Weather tightness and reliability of the devices for closing cargo and access hatches, outer doors and all other openings in the decks and superstructures of the vessel and the water tightness of the side scuttles and of ports or similar openings in the sides below the freeboard deck to be checked;
  - c. Condition of the freeing ports and scuppers as well as operational reliability of their closures to be checked;
  - d. Emergency and life-saving appliances and their operational reliability;
  - e. Operational reliability of all external and internal communication equipment; and
  - f. Condition and operational reliability of the bilge and ballast pumping systems.
  
- 1.1.2. Further, with special regard to possible ice accretion, the skipper should:
  - 1.1.2.1. Consider the most critical loading condition against approved stability documents with due regard to fuel and water consumption, distribution of supplies, cargoes and fishing gear and with allowance for possible ice accretion;
  - 1.1.2.2. Be aware of the danger in having supplies and fishing gear stored on open weather deck spaces due to their large ice accretion surface and high center of gravity;
  - 1.1.2.3. Ensure that a complete set of warm clothing for all members of the crew is available on the vessel as well as a complete set of hand tools and other appliances for combating ice accretion, a typical list thereof for small vessels is shown in section 4 of this annex;
  - 1.1.2.4. Ensure that the crew is acquainted with the location of means for combating ice accretion, as well as the use of such means, and that drills are carried out so that members of the crew know their respective duties and have the necessary practical skills to ensure the vessel's endurance under conditions of ice accretion;
  - 1.1.2.5. Acquaint himself with the meteorological conditions in the region of fishing grounds and en route to the place of destination; study the synoptical maps of this region and weather forecasts; be aware of warm currents in the vicinity of the fishing grounds, of the nearest coastline relief, of the existence of protected bays and of the location of ice fields and their boundaries; and
  - 1.1.2.6. Acquaint himself with the timetable of the radio stations transmitting weather forecasts and warnings of the possibility of ice accretion in the area of the relevant fishing grounds.

**SECTION 2 AT SEA**

**Contents**

2.1. At sea ..... 129

**2.1. At sea**

- 2.1.1. During the voyage and when the vessel is on the fishing grounds, the skipper should keep himself informed on all long-term and short-term weather forecasts and should arrange for the following systematic meteorological observations to be systematically recorded:
- Temperatures of the air and of the sea surface;
  - Wind direction and force;
  - Direction and height of waves and sea state;
  - Atmospheric pressure, air humidity; and
  - Frequency of splashing per minute and the intensity of ice accumulation on different parts of the vessel per hour.
- 2.1.2. All observed data should be recorded in the vessel's log-book. The skipper should compare the weather forecasts and icing charts with actual meteorological conditions, and should estimate the probability of ice formation and its intensity.
- 2.1.3. When the danger of ice formation arises, the following measures should be taken without delay:
- All the means of combating ice formation should be ready for use;
  - All the fishing operations should be stopped; the fishing gear should be taken on board and placed in the under-deck spaces. If this cannot be done all the gear should be fastened for storm conditions on its prescribed place. It is particularly dangerous to leave the fishing gear suspended since its surface for ice formation is large and the point of suspension is generally located high;
  - Barrels and containers with fish, packing, all gear and supplies located on deck as well as portable mechanisms should be placed in closed spaces as low as possible and firmly lashed;
  - All cargoes in holds and other compartments should be placed as low as possible and firmly lashed;
  - The cargo booms should be lowered and fastened;
  - Deck machinery, hawser reels and boats should be covered with duck covers;
  - Lifelines should be fastened on deck;
  - Freeing ports fitted with covers should be brought into operative condition, all objects located near scuppers and freeing ports and preventing water drainage from deck should be taken away;
  - All cargo and companion hatches, manhole covers, watertight outside doors in superstructures and deck-houses and portholes should be securely closed in order to ensure complete weather tightness of the vessel, access to the weather deck from inner compartments should be allowed only through the superstructure deck;
  - A check should be carried out as to whether the amount of water ballast on board and its location is in accordance with that recommended in "Stability guidance to skippers"; if there is sufficient freeboard, all the empty bottom tanks fitted with ballast piping should be filled with seawater;
  - All fire-fighting, emergency and life-saving equipment should be ready for use;
  - All drainage systems should be checked for their effectiveness;
  - Deck lighting and searchlights should be checked;
  - A check should be carried out to make sure that each member of the crew has warm clothing; and
  - Reliable two-way radio communication with both shore stations and other vessels should be established; radio calls should be arranged for set times.
- 2.1.4. The skipper should seek to take the vessel away from the dangerous area, keeping in mind that the lee edges of ice fields, areas of warm currents and protected coastal areas are a good refuge for the vessel during weather when ice formation occurs.

- 2.1.5. Small fishing vessels on fishing grounds should keep nearer to each other and to larger vessels.
  
- 2.1.6. It should be remembered that the entry of the vessel into an ice field presents certain danger to the hull, especially when there is a high sea swell. Therefore the vessel should enter the ice field at a right angle to the ice field edge at low speed without inertia. It is less dangerous to enter an ice field bow to the wind. If a vessel must enter an ice field with the wind on the stern, the fact that the edge of the ice is more dense on the windward side should be taken into consideration. It is important to enter the ice field at the point where the ice floes are the smallest.

## SECTION 3 DURING ICE FORMATION

### Contents

3.1. During ice formation .....	132
---------------------------------	-----

**3.1. During ice formation**

- 3.1.1. If in spite of all measures taken the vessel is unable to leave the dangerous area, all means available for removal of ice should be used as long as it is subjected to ice formation.
- 3.1.2. Depending on the type of vessel, all or many of the following ways of combating ice formation may be used:
- Removal of ice by means of cold water under pressure;
  - Removal of ice with hot water and steam; and
  - Breaking up of ice with ice crow's, axes, picks, scrapers, or wooden sledge-hammers and clearing it with shovels.
- 3.1.3. When ice formation begins, the skipper should take into account the recommendations listed below and ensure their strict fulfillment:
- Report immediately ice formation to the ship owner and establish with him constant radio communication;
  - Establish radio communication with the nearest vessels and ensure that it is maintained;
  - Do not allow ice formation to accumulate on the vessel, immediately take steps to remove from the vessel's structures even the thinnest layer of ice and ice sludge from the upper deck;
  - Check constantly the vessel's stability by measuring the roll period of the vessel during ice formation. If the rolling period increases noticeably, immediately take all possible measures in order to increase the vessel's stability;
  - Ensure that each member of the crew working on the weather deck is warmly dressed and wears a safety line securely attached to the guardrail;
  - Bear in mind that the work of the crew on ice clearing entails the danger of frost-bite. For this reason it is necessary to make sure that members of the crew working on deck are replaced periodically;
  - Keep the following structures and gears of the vessel first free from ice:
    - Aerials;
    - Running and navigational lights;
    - Freeing ports and scuppers;
    - Lifesaving craft;
    - Stays, shrouds, masts and rigging;
    - Doors of superstructures and deck-houses; and
    - Windlass and hawse holes;
  - Remove the ice from large surfaces of the vessel, beginning with the upper structures (such as bridges, deck-houses, etc.), because even a small amount of ice on them causes a drastic worsening of the vessel's stability;
  - When the distribution of ice is not symmetrical and a list develops, the ice must be cleared from the lower side first. Bear in mind that any correction of the list of the vessel by pumping fuel or water from one tank to another may reduce stability during the process when both tanks are slack;
  - When a considerable amount of ice forms on the bow and a trim appears, ice must be quickly removed. Water ballast may be redistributed in order to decrease the trim;
  - Clear ice from the freeing ports and scuppers in due time in order to ensure free drainage of the water from the deck;
  - Check regularly for water accumulation inside the hull;
  - Avoid navigating in following seas since this may drastically worsen the vessel's stability;
  - Register in the vessel's log-book the duration, nature and intensity of ice formation, amount of ice on the vessel, measures taken to combat ice formation and their effectiveness; and

- o. If, in spite of all the measures taken to ensure the vessel's endurance in conditions of ice formation, the crew is forced to abandon the vessel and embark on life-saving craft (lifeboats, rafts) then, in order to preserve their lives, it is necessary to do all possible to provide all the crew with warm clothing or special bags as well as to have a sufficient number of lifelines and bailers for speedy bailing out of water from the life-saving craft.

## SECTION 4 LIST OF EQUIPMENT AND HAND TOOLS

### Contents

4.1.	List of equipment and hand tools .....	135
------	--	-----

**4.1. List of equipment and hand tools**

4.1.1. A typical list of equipment and hand tools required for combating ice formation:

- a. Ice crows or crowbars;
- b. Axes with long handles;
- c. Picks;
- d. Metal scrapers;
- e. Metal shovels;
- f. Wooden sledge-hammers;
- g. Fore and aft lifelines to be rigged each side of the open deck fitted with travelers to which lizards can be attached.

4.1.2. Safety belts with spring hooks should be provided for no less than 50% of the members of the crew (but not less than 5 sets), which can be attached to the lizards.

**Notes:**

1. The number of hand tools and lifesaving appliances may be increased, at the ship owner's discretion.
2. Hoses which may be used for ice combating should be readily available on board.